LE DON 52 1110

DCH 05/09

07

EFFECT OF SILICA AND CLAY ON TEAR AND ABRASION RESISTANCE OF NATURAL RUBBER

43

THIS DISSERTATION WAS SUBMITTED BY N. AJITH ASANKA SILVA AS PARTIAL FULFILMENT OF THE REQUIREMENTS FOR THE DEGREE OF MASTER OF SCIENCE IN POLYMER TECHNOLOGY AT THE UNIVERSITY OF MORATUWA.

54897

um These coll

678 · 4 . 55

AUGUST 1989.

ACKNOWLEDGEMENT

I wish to express my sincere thanks to Dr. W.S.E.Fernando of the Rubber Research Institute, Dr. (Mrs.) L.Sivagurunathan and Dr. K.P.Fernando of the University of Moratuwa for their guidance and encouragement throughout the course of this work.

I wish to express my gratitude to the Staff of Rubber Technology Department of the Rubber Research Institute for the co-operation extended to me throughout the work.

SUMMARY

It is well known that Silica gives reinforcement to Natural Rubber to give good mechanical properties. In this comparison of cure characteristics, physical and mechanical properties of Silica filled Natural Rubber compounds prepared with varying accelerator systems, stearic acid content and anti-oxidants were studied.

The results indicated that the MBTS/ZDC and TBBS/ZDC systems with Phenolic type anti-oxidant give better properties than other systems. According to the results obtained MBTS/ZDC and TBBS/ZDCsystems are quite different from other systems with respect to tensile strength, tear strength and hardness. On the other hand TBBS/ZDC system with Nonox SP gives better Abrasion Resistance than other systems, if Silica and Clay are used as fillers.

CONTENTS

CHAPTER	1.		INTRODUCTION	1
	1.	1.	Classification and properties of inorganic	3
			rubber fillers.	
	1.	2.	Particle size characteristics of fillers.	6
	1.	3.	Comparison of specific gravities.	6
	1.	4.	Tensile strength properties of inorganic	7
	1.	5.	Modulus.	8
	1.	6.	Tear strength.	10
	1.	7.	Abrasion.	11
	1.	8.	Properties of silica fillers.	11
	1.	8.1.	Fume silica or pyrogenic silica.	12
	1.	8.2.	Precipitated or hydrated silica.	12
	1.	8.3.	Ground mineral silica.	12
	1.	8.4.	Kieselguhr.	13
	1.	9.	Clays.	13
	1.	9.1.	Soft clays.	13
	1.	9.2.	Hard clays.	13
	1.	9.3.	Calcined clays.	14
	1.	9.4.	Treated clays.	14

CONTENTS

<u>CHAPTER</u>	2.		EXPERIMENTAL	15
	2.	1.	Compound design.	15
	2.	2.	Formulations used.	16
	2.	3.	Compounding sequences.	17
	2.	4.	Determination of mooney viscosity.	17
	2.	5.	Rheometer studies.	18
	2.	6.	Hardness.	19
	2.	7.	Rebound resili _e nce.	20
	2.	8.	Tensile strength, elongation at break,	21
			modulus at 100% extension and 300% extension.	
	2.	9.	Tear strength.	23
	2.	10.	Abrasion.	24
CHAPTER	3.		RESULTS	25
	3.	1.	Assessment of vulcanization characteristics.	25
	3.	2.	Other physical properties.	27

CONTENTS

<u>CHAPTER</u>	4.	DISCUSSION	28
	4. 1.	Cure characteristics.	28
	4.2.	Tensile strength.	29
	4.3.	Tear strength.	30
	4.4.	Abrasion.	31
	4. 5.	Tear related abrasion properties.	32
	4.6.	Hardness.	33
	4.7.	Resilience.	33
	4.8.	Mooney viscosity.	34
	4.9.	Conclusion.	34
	4.10.	Suggestions for further work.	35