## Study on Variable Refrigerant Volume Air-conditioning System

S. K.P. Vitharana

### **Master of Science**

### **Building Services Engineering**

2009 / 2010



# **University of Moratuwa**

Sri Lanka

March 2013

**Supervisor:** 

Prof. R.A. Attalage

#### **Declaration**

I hereby declare that this submission is my own work and that, to the best of my knowledge and behalf, it contains no material previously published or written by another person nor material which to substantial extent, has been accepted for the award of any other academic qualification of a university or other institute of higher learning except where acknowledgment is made in the text

S. K. P. Vitharana	
Name of the Student	Signature
	Date :



Name of the Supervisor Signature

Date : .....

### Acknowledgement

This research project was carried out under the supervision of Prof. R. A. Attalage, Deputy Vice Chancellor, University of Moratuwa. His guidance, valuable comments and inputs for the project at different stages were of immense encouragement and support in completing the project at the level of a Master Degree. I sincerely believe that the experience and exposure I gained while working under the guidance of Prof. R. A. Attalage, in various associations and committees greatly helped me to complete this research project successfully. So, I am grateful for his dedication and fullest co-corporation extended to me in this endeavor.

The exposure I attained while working in the Demand Side Management Branch of the Ceylon Electricity Board was immense. Mr. Bandula S. Tilakasena, Deputy General Manager of the former Demand Side Management branch of the Board, who entrusted me with the task of facilitating the implementation of Energy Conservation Projects in the Commercial Sector in Sri Lanka, extended me with various opportunities to gain firsthand experience in the area of Energy Efficiency Energy Conservation and specially on the Energy Efficiency of Airsconditioner systems the helped me a lot to develop my self-confidence and to play a leading role in the promotion of Energy Efficiency in the Commercial Sector in Sri Lanka. I am indebted to him for his kind help and for the trust he kept on me.

I am grateful to Mr. K.L.L. Fernando; former Addl. Director of Facilities Management Department of the Central Bank of Sri Lanka, Mr. Raj Fonseka; Asst. Maintenance Engineer of the same organization and Mr. Vidhura Ralapanawa of Mas Holdings for providing me with information and software support required for this research study and sharing their views and experience on the VRV Air-conditioners, Operation and Maintenance aspects and the Energy Efficiency of Air-conditioners available in the local market.

Further, I appreciate all of my friends and colleagues who encouraged and assisted me in different ways towards the completion of this thesis successfully.

#### **Abbreviations**

CBSL - Central Bank of Sri Lanka

CLF - Cooling Load Factor

COP - Coefficient of Performance

DEC - Direct Evaporative Cooling

DX - Direct Expansion

EER - Energy Efficiency Ratio

EEV - Electronic Expansion Value

FPFA - Fan-Coil Plus Fresh Air

IGH - Internal Heat Gain

LCC Life Cycle Gestrsity of Moratuwa, Sri Lanka.

OAC Everall Average Annual Cost & Dissertations

www.lib.mrt.ac.lk

VRF - Variable Refrigerant flow

VRV - Variable Refrigerant Volume

#### **Abstract**

During the last two decades, air-conditioning has become a basic requirement in industrial, commercial and residential sectors. With the widened use of air-conditioning in all the sectors, the human community has faced serious environmental and socio economic problems. Prevailing energy crisis and ever increasing energy pieces has made the situation worst. Under the scenario, various novel technologies have been emerged to the air-conditioner market. Variable Refrigerant Volume (VRV) air-conditioning technology is also considered as an advanced technology developed to cater the need of efficient use of energy for air-conditioning.

The major objective of the research study was to analyze the suitability of VRV air-conditioning system, analyze the actual saving potential and cost effectiveness of VRV air-conditioning system compared to the other available types of air-conditioning systems and access the maintainability of VRV air-conditioning system. The study was conducted at a selected representative installation namely at the Sovereign Residences of Central Bank of Sri Lanka. Summary of findings are as followeratuwa. Sri Lanka.

- VRV ar conditioners are suitable for medium scale hotel applications. However, www.lib.mrt.ac.lk
  this conclusion cannot be generalized for all the installations and the appropriate air-conditioning system for particular building should be selected only after performing a comprehensive analysis of energy performance of considered options on that particular installation (preferably after a computer simulation and life cycle cost analysis of different options). Therefore, though the demand for VRV air-conditioning system is prevailing due to the higher efficiency rating and the part load performance of the air-conditioning appliances, the desires of the purchases on energy saving potential of VRV air-conditioners could be satisfied only when it is selected for an appropriate application.
- Saving potential of VRV air conditioners could be high as 18 % compared to the energy consumed by split air-conditioning systems when used for appropriate applications. Therefore, the VRV system can be considered as a potential candidate for the installations where the building occupancy and cooling load are regularly varying. Further, Chiller (Central) air-conditioning system can also be considered as a potential candidate as it performs almost efficiently as the VRV system. It consumes around 4 % more energy than VRV system.

- Computer simulation (Equest) shown that VRV air-conditioning system is the most
  efficient option among the potentially applicable options considered for the
  building. However, the Life Cycle Cost (LCC) analysis shows that Chiller system is
  the most economical air-conditioning system for the same building. Therefore, it is
  vital to perform LCC analysis in addition to performance analysis when selecting
  the appropriate air-conditioning system for a building.
- Maintainability of the VRV air-conditioning systems is acceptable. It is necessary
  to select the correct density and thickness of the refrigerant pipe insulation to
  minimize the possibilities of formation of condensation along the refrigerant pipes.
  Also, the power quality should be maintained at an acceptable level to ensure the
  durability and proper functionality of electronics of the VRV air conditioning
  equipment.



# **Table of Contents**

Declaration		i
Acknowledg	gement	ii
Abbreviation	as	iii
Abstract		iv
1	Introduction	1
1.1 Backgro	und	1
1.2 Problem	statement	2
1.3 Objectiv	es of the project	2
1.4 Methodo	ology followed for the study	2
1.5 Significa	ance of the study, scope and limitations	4
1.6 Influence	e of building certification systems on air-conditioning industry	5
1.7 Summar	y of the Results of the research project and recommendations	6
2	Literature Review	8
2.1 World so	University of Moratuwa, Sri Lanka.  Separation of usage of air-conditioners.  Electronic Theses & Dissertations The property of Moratuwa, Sri Lanka.  Electronic Theses & Dissertations The property of Moratuwa, Sri Lanka.	8
2.2 Advance	hent of air-conditioning systems.	10
2.2.1	Www.lib.mrt.ac.lk Usage of various air-conditioning systems and technologies in Sri Lanka	ı 10
2.3 Appropri	iate technologies	11
2.3.1	Evaporative cooling technology	11
2.3.2	Variable refrigerant volume technology	13
2.3.2	.1 Basic principle of VRV technology	13
2.3.2	.2 Advantages and limitations of the VRV systems	14
2.4 Desired	applications of VRV technology	15
2.5 Previous	studies on the VRV systems	17
2.5.1	Experimental studies	18
2.5.2	Modeling studies	21
2.5.3	Case studies	27
2.5.3	.1 Scope of the study	27
2.5.3	.2 Results and discussion	30
2.5.3	.3 Breakdown of electricity end-users in HVAC systems	30
2.5.3	.4 Electricity consumption of different systems	33
2.5.3	.5 Conclusion of the case study	34

	2.5.4	Overall summary of the literature review	. 35
3		Methodology	. 37
3.1	Appropr	iate method selected for the collection of information	. 37
3.2	Installati	on selected for the study	. 38
3.3	Methodo	ology followed for the study	. 39
4		Comprehensive Study on a VRV Installation and Analysis	. 40
4.1	Installati	on selected for the study - Center for Banking Studies	. 40
	4.1.1	Description of the installed air-conditioning system	. 40
	4.1.2	Description of the installed air-conditioning system	. 41
4.2	Selection	n of appropriate air-conditioning system for the building	. 42
	4.2.1	Installation of split type air-conditioners	. 42
	4.2.2	Installation of a chiller	. 43
	4.2.3	Installation of a VRV air-conditioning system	. 44
	4.2.4	Operation pattern of the system	. 45
		nability and problems encountered during the operation of the system	
	4.3.1	Weakening the insulation of refrigerant pipes.  University of Moratuwa, Sri Lanka.  Tenant's concerns regarding the VRV system  Electronic Theses & Dissertations  Plicency of the installed air- conditioning system  www.lib.mrt.ac.lk	. 46
	4.3.2	Tenant's concerns regarding the VRV system	. 47
4.4	Energy 6	efficiency of the installed air- conditioning system	. 47
	4.4.1	Scope and Findings of the Energy Audit	. 48
	4.4.2	Computer simulation on different options of air-conditioning systems	. 52
	4.4.2	2.1 Building Modeling	. 52
	4.4.2	2.2 Simulation for Chiller Air-conditioning System	. 57
	4.4.2	Simulation for VRV and Split Air-conditioning Systems	anc
	Com	parison of Energy Performances	. 61
	4.4.2	2.4 Comparison of actual energy consumption records with the simula	tior
	resul	ts of the existing VRV air-conditioning system	. 63
	4.4.2	2.5 Comparison and Analysis of the Monthly Energy Consumption	1 of
	Chill	er, VRV and Split Type Air-conditioning Systems	. 64
4.5	Life cyc	le cost analysis of the potentially applicable air- conditioning systems	. 66
	4.5.1	Estimation of Life cycle cost	. 66
	4.5.2	Sensitivity analysis for + 10 % variation of electricity tariff and initial cost	.69
5		Conclusion and Recommendations	. 72
5.1	Ability of	of VRV air-conditioners to satisfy the desires of the purchaser	. 72

5.2 Computer simulation of different air-conditioning options considered for the bu	ıilding
and saving potential of VRV air-conditioners	74
5.3 Life cycle cost analysis of the potentially applicable air-conditioning systems	74
5.4 Maintainability of the VRV air-conditioners	75
5.5 Conclusions and Recommendations	75
References 78	
Annexure A Error! Bookmark not defined.	
Annexure B Error! Bookmark not defined.	
Annexure C Error! Bookmark not defined.	



# **List of Tables**

Γable 1 : Brief descriptions of the sample building and HVAC systems28
Table 2: Construction thermal properties
Table 3: power consumption with different indoor units operation
Table 4: Consumption of power consumption of existing system and split AC units 52
Table 5 : Summary of appliance and lighting load
Table 6 : Schedule of occupancy, fan and cooling
Table 7 : Chiller operating hours in different loading conditions
Table 8: Hourly load profile of the chiller for a day of each month
Table 9: Comparison of electricity billing data with the simulation results of VRV system
63
Table 10: Comparison of monthly energy consumption of Chiller, VRV & Split type air-
conditioning systems64
Table 11: LCC and OAC of potentially applicable air-conditioning systems68



# **List of Figures**

Figure 1: Comparison on the daily amplitude between VRF-1 system and the window air-
conditioners. 24
Figure 2: Typical floor plan of the sample building (unit in drawing: meters)31
Figure 3: Comparison of energy usage among three systems
Figure 4: Part-load range of the three kinds of systems
Figure 5: Building ground floor plan
Figure 6: Building 3D model
Figure 7: Building zoning arrangement
Figure 8: Monthly energy consumption of chiller
Figure 9: Chiller load profile for each month
Figure 10: Hourly load profile of the chiller for a day of each month
Figure 11: Monthly energy consumption of VRV Type air-conditioning system
Figure 12: Monthly energy consumption of Split Type air-conditioning system
Figure 13: Monthly energy consumption of Chiller, VRV and Split Type air-conditioning
systems University of Moratuwa, Sri Lanka. 65
Figure 14: One of potentially applicable air-conditioning systems against initial cost 68
Figure 15: Economical initial cost of VRV and Chiller air-conditioning systems69
Figure 16: Sensitivity of OAC of potentially applicable air-conditioning systems against
electricity tariff
Figure 17: Sensitivity of OAC of potentially applicable air-conditioning systems against
initial cost 70