


LB/DON/10/04

PEATY CLAY IMPROVEMENT WITH PREFABRICATED VERTICAL DRAINS



Thesis submitted in partial fulfillment of the requirements for the
Degree of Master of Science.



Rasiah Kugan

624 "04"

624.131.22

UM Thesis coll

Department of Civil Engineering
University of Moratuwa
Sri Lanka
January 2004


79576

79576

University of Moratuwa



79576



DECLARATION

The work included in this thesis in part or whole, has not been submitted for any other academic qualification at any institution.




Signature of the candidate



University of Moratuwa, Sri Lanka
Electronic Theses & Dissertations
www.lib.mrt.ac.lk

Certified

UOM Verified Signature



Signature of the Supervisor



ABSTRACT

Peaty clay obtained from the Colombo-Katunayake Expressway route was tested in the laboratory for its consolidation characteristics. The main objective was to quantify the improvement in peaty clay by the use of pre-fabricated vertical drains (PVD).

Two large-scale model set-ups were erected to monitor the consolidation process of peaty clay, one without the use of PVD, and the other with the PVD installed. Both tests were conducted by depositing remoulded peaty clay in cylindrical barrels, and load was applied by several increments. Settlements and pore-water pressure were monitored over a long period. Axi-symmetric conditions were simulated by these tests. Based on the test results, the performance of PVD in accelerating the consolidation process is quantified. The model test results are back-analysed using the finite difference method, in order to give an indication of an appropriate numerical modeling process which can be used to model other instances of similar process.

In addition, the effect of sample size and the duration of the load increment period on consolidation in peaty clay is investigated. Tests were carried out in three different sizes of specimen dimensions. Values of c_v were calculated by several methods found in the literature, after carrying out tests using different load increment periods. Load increment periods for different sample thicknesses were calculated according to Terzaghi theory, for time simulation tests. The time necessary to obtain a specified degree of consolidation was calculated by an appropriate equation. The values of c_v obtained by these methods are of the same order for the time simulation tests. The secondary compression index of the peaty clay is found to be very high.

The improvement of shear strength in peaty clay due to consolidation is also investigated. Shear strength of peaty clay was measured at the end of laboratory tests and the results were compared with the strength of sample taken prior to consolidation. Soil strength after the treatment was evaluated by undrained triaxial tests, vane shear tests and consolidated drained triaxial tests. Soil strength before the treatment was evaluated only by vane shear tests as sample preparation with the soft soil was not possible. Gain in shear strength in peaty clay due to consolidation is quantified.



ACKNOWLEDGMENT

Even a small research owes its existence to many more people than the one whose name appears as researcher. Among those who deserve credit for the assistance extended during the research programme, Dr.U.G.A.Puswewala, who proved an excellent supervisor to work with, has contributed a great deal to this research. His guidance, support and stimulating criticisms made the research a complete success. The support of research co-ordinator Dr.S.A.S.Kulathilake is highly appreciated. I wish to acknowledge and express my gratitude to Dr.S.A.S.Kulathilake, who found time to supervise me throughout the study period. His devotion in the subject of soft ground improvement is also acknowledged. I express my sincere thanks to Dr.T.A.Peiris for giving necessary support and guidance. My gratitude is extended to Professor B.L.Tennekoon from whom I garnered insights and suggestions during the progress reviews and in some specific areas. A special thanks is extended to Dr.S.Thilakasiri for his valuable instructions and support. I would have not got the chance of doing this research study if not for the Scholarship granted by Asian Development Bank and the Ministry of Science and Technology, Sri Lanka, and their consideration is very much appreciated.

The assistance received from Mr.K.R. Pitipanaarachchi, technical officer, Mr.D.G.S. Vithanage, technical officer and Mr.D.Bandulasena, lab assistant, of Soil Mechanics Laboratory of the University of Moratuwa, during the laboratory-testing programme, is acknowledged. I would like to acknowledge the assistance extended by Mr.Gunaserkara, technical officer, Civil Engineering Workshop for fabricating experimental models successfully.

Mr.G.V.S.K.Kumarasri, Chief Engineer, Keang-Nam Constructions, Colombo-Katunayaka Highway Project needs to be thanked for allowing me to collect some information on the installation of vertical drains at Colombo-Katunayake Expressway Project of the Road Development Authority, and providing necessary materials to make the large-scale model.

My sincere thanks are also forwarded to all the geotechnical research students for their support throughout the research period. I extend my thanks specially to undergraduate students who supported me during the testing programme.

Rasiah Kugan

01-01-2004

CONTENTS

Page

ABSTRACT	i
ACKNOWLEDGEMENT	ii
CONTENTS	iii
List of Figures	vii
List of Tables	x

CHAPTERS

1 Introduction

1.1	Problems due to peaty clay in Sri Lanka	2
1.2	Improvement of peat	2
1.2.1	Methods applicable to cohesive soils	3
1.2.2	Ground treatment in peaty soils	3
1.2.2.1	Excavation and replacement by stable fill material	3
1.2.2.2	Displacement methods	4
1.2.2.3	Pre-loading	4
1.2.2.4	Preloading with Vertical Drains	4
1.2.2.5	Placement of compacted fill on peat	8
1.2.2.6	Dynamic compaction	8
1.2.2.7	Vacuum consolidation	9
1.2.2.8	Deep mixing method	10
1.3	Consolidation testing of peaty clay	10
1.4	Objectives and Scope of the current research	11
1.5	Arrangement of the thesis	12

2 Literature review

2.1	How to approach a project involving possible site-improvement with vertical drains	14
2.2	Prefabricated Vertical Drains (PVD)	17
2.2.1	General	17
2.2.2	Definition of PVD	18

2.2.3	History	18
2.2.4	Types, material and installation procedure for vertical drains	20
2.2.5	Installation	21
2.2.6	Factors affecting the efficiency of PVD	26
2.2.6.1	Design Factors	27
2.2.6.1.1	Drain Spacing	27
2.2.6.1.2	Equivalent Diameter	28
2.2.6.2	Well resistance	29
2.2.6.3	Smear Zone	30
2.2.6.4	Degree of consolidation	31
2.3	Preloading	34
2.4	Settlement	35
2.5	Numerical prediction of model behavior	38
2.5.1	Modeling the pore pressure response	38
2.6	Properties and behaviour	39
2.6.1	Classification of peat and other organic soils	39
2.6.2	Amorphous granular peat	41
2.6.3	Mires and Peats	41
2.6.4	Physical and chemical characteristics	42
2.6.4.1	Water content	42
2.6.4.2	Permeability	43
2.6.4.3	Void ratio	43
2.6.4.4	Specific Gravity	44
2.6	Overview of some methods proposed to find c_v .	44
3	Methodology	
3.1	Geological condition in the borrow area	54
3.2	Sample collection	54
3.2.1	Taking of undisturbed sample	54
3.2.2	Taking disturbed sample	56
3.3	Sample preparation	59


3.4	Testing programme	60
3.4.1	Testing programme for investigating the influence of the prefabricated vertical drains on the consolidation process in peaty clay	60
3.4.2	Consolidation tests on treated large-scale sample without PVD	65
3.4.3	Testing programme for investigating the improvement of shear strength in peaty clay due to consolidation	65
3.4.4	Testing programme for investigating the influence of sample thickness in consolidation	68
3.4.5	Testing programme for investigating the moisture content variation in the sample	68
4	Results	
4.1	Experimental results and analysis of improvement with PVD	69
4.2	Experimental results and analysis of improvement in shear strength	69
4.2.1	Consolidation test results	69
4.2.2	Undrained unconsolidated triaxial test results	75
4.2.3	Field vane shear test	77
4.2.4	Consolidated drained test	79
4.2.5	Moisture content variation with depth for treated sample without PVD	81
4.2.6	Effect of friction on the process of consolidation of large-scale model	81
5	Back analysis of test results	
5.1	Back analysis of test data using Terzaghi model by finite different method	82
5.2	Development of the finite difference numerical schemes	82
5.2.1	Numerical solution for one-dimensional consolidation	82
5.2.2	Numerical solution for radial drainage	84
5.2.3	Modelling of the vertical drainage	86
5.2.4	Modelling of the radial drainage	86
5.2.5	Modelling of the settlement behaviour	87
5.3	Modelling of the large-scale test using the finite difference method (FDM)	88

5.4	Analysis of results	89
6	Application of various methods to analyse test results for consolidation characteristics	
6.1	Experimental results	94
6.2	Analysis of results	94
6.3	Application of the methods to test data	97
7	Analysis of long-term consolidation test result	
7.1	Analysis of long-term consolidation test results and calculation of secondary compression index	100
7.2	Improvements in compression index and compression ratio	100
7.3	Improvements in the coefficient of volume compressibility	101
7.4	Secondary compression	102
8	Conclusions and Recommendations	
8.1	Conclusions	105
8.2	Recommendations	106
9	References	107
	Appendix A	A-1 - A-9
	Appendix B	B-1 - B-9
	Appendix C	C-1 - C-6

List of Figures

- Figure 1.1 General arrangement of preloading with vertical drains and field monitoring arrangements
- Figure 1.2 Vacuum consolidation arrangement
- Figure 2.1 Flow chart illustrating the foundation design process (Hartikainen, 1983)
- Figure 2.2 Prefabricated vertical drain
- Table 2.1 Types of vertical drains, common installation methods and typical geometric characteristics (after Jamiolkowski, Lancellotta and Wolski, 1983a)
- Table 2.2 Dimension and materials of some prefabricated drains
- Figure 2.3 Typical mandrels for band-shaped drains (Sectional plan views)
- Figure 2.4 Typical shoes
- Figure 2.5 Illustration of PVD installation procedure
- Figure 2.6 Equivalent diameters for square and triangular grid pattern
- Figure 2.7 Equivalent diameter
- Figure 2.8 Approximation of disturbed zone around the mandrel (Rixner et al., 1986)
- Figure 2.9 Schematic diagram of PVD with drain resistance and soil disturbance (Rixner et al., 1986)
- Figure 2.10 Consolidation due to vertical and radial drainage (Rixner et al., 1986)
- Figure 2.11 Graph of influence factors for calculation of immediate settlement
- Figure 2.12 Logarithm-of-time method for determination of c_v
- Figure 2.13 Square-root-of-time method for determination of c_v
- Figure 2.14 Maximum slope method for determination of c_v
- Figure 2.15 The $\log \delta - \log t$ method for determination of c_v (point A corresponds to $U = 88.3\%$)
- Figure 2.16 Asaoka's (1978) method for determination of c_v
- Figure 2.17 (a) Typical experimental $\delta - \log t$ plot
(b) $\Delta \delta / \Delta \log t - \log t$ plot
- Figure 2.18 $t / \delta - t$ plot for determination of c_v

- Figure 3.1 Location map of the sample collection area
- Figure 3.2 Removal of top vegetated layer
- Figure 3.3 Pushing the barrel vertically into the peat layer
- Figure 3.4 pushing the barrel into the peat layer by using backhoe
- Figure 3.5 Taking the barrel out from the soil by holding the bottom of the barrel with backhoe.
- Figure 3.6 Removal of undisturbed sample with barrel
- Figure 3.7 Properly sealed barrels after the sample collection
- Figure 3.8 Sample preparation
- Figure 3.9 Schematic diagram of model test apparatus (arrangement shown without PVD)
- Figure 3.10 Arrangement of excess pore pressure measuring system and settlement measuring system (arrangement shown with PVD)
- Figure 3.11 Outer casing and inner casing arrangement of filter tip
- Figure 3.12 Positioning the filter tip arrangement
- Figure 3.13 Closed hydraulic piezometer arrangement with null indicator
- Figure 3.14 Photograph of the model test arrangement
- Figure 3.15 PVD installation
- Figure 3.16 Field vane shear test arrangement
- Figure 3.17 Test in progress with the medium scale model
- Figure 3.18 Consolidation test using the small scale model (oedometer test)
- Figure 3.19 Cutting sample using guitar string
- Figure 3.20 Sample pieces
- Figure 4.1 Test result for loading without PVD
- Figure 4.2 Test result for loading with PVD installed at center of the remoulded peat slurry prior to loading
- Figure 4.3 Comparison of test results without PVD and with PVD
- Figure 4.4 Consolidation test result of top layer
- Figure 4.5 Consolidation test result of middle layer
- Figure 4.6 Consolidation test result of bottom layer
- Figure 4.7 Unconsolidated undrain Triaxial test results for top treated layer



- Figure 4.8 Unconsolidated undrain Traxial test results for middle treated layer
- Figure 4.9 Unconsolidated undrain traxial test results for bottom treated layer
- Figure 4.10 Field vane shear test result at location 1
- Figure 4.11 Field vane shear test result at location 2
- Figure 4.12 Field vane shear test result at location 3
- Figure 4.13 Field vane shear test result before treatment
- Figure 4.14 Consolidated drained traxial test results for top treated layer
- Figure 4.15 Consolidated drained traxial test results for middle treated layer
- Figure 4.16 Consolidated drain traxial test results for bottom treated layer
- Figure 4.16 The variation of moisture content with depth
- Figure 5.3 Idealized section used for FDM
- Figure 5.1 Illustration of FDM meshes
- Figure 5.2 Illustration of FDM mesh
- Figure 5.4 Excess pore water pressure mesh developed for the analysis
- Figure 5.5 Comparison of observed and estimated excess pore water pressure (constant c_v values)
- Figure 5.6 Comparison of observed and estimated excess pore water pressure dissipation (variable c_v value)
- Figure 5.7 Variation of c_v value with days
- Figure 5.8 Comparison of observed settlements with predictions c_v 11m²/yr
- Figure 5.9 Comparison of observed settlements with predictions c_v 5.5m²/yr
- Figure 5.10 Comparison of observed settlements with predictions by varying the c_v value with time
- Figure 5.11 Comparison of observed settlements with predictions by varying the c_v and c_h values with time
- Figure 5.12 Variation of c_h value with time
- Figure 6.1 Consolidation test results
- Figure 6.2. A possible deviation from Asaoka's construction (Orleach, 1983)
- Figure 6.3 Summary of c_v values by different methods
- Figure 7.1 e vs $\log(\sigma)$ plot for remoulded peaty clay (long term test results)

- Figure 7.2 Effect of preloading on m_v for remoulded peaty clay
- Figure 7.3 Test results from long term oedometer test for each load incremental
- Figure 7.4 c_α vs $\log(\sigma)$ plot for remoulded peaty clay

List of Tables

- Table 2.1 Types of vertical drains, common installation methods and typical geometric characteristics (after Jamiolkowski, Lancellotta and Wolski, 1983a)
- Table 2.2 Dimension and materials of some prefabricated drains
- Table 2.3 Classification of peat (The Canadian system after Radforth 1969)
- Table 4.1 Unconsolidated undrained triaxial test results
- Table 4.2 Field vane shear test results
- Table 4.3 Consolidated drain triaxial test results
- Table 6.1 Comparison of results obtained by using various methods
- Table 7.1 Values of Void ratio
- Table 7.2 Values of m_v
- Table 7.3 Classification of soil based on secondary compressibility (Mesri, 1973)
- Table 7.4 Values of c_α
- Table 7.5 Comparison of results obtained from samples of different size

