

## References

- [1] Ackermann Thomas, Wind power in power system. John Wiley & Sons press;2005
- [2] American wind Energy Association (AWEA). Roadmap: A 20- year industry plan for small wind turbine technology, American wind Energy Association ,122 C Street. NW, Site 380, Washington, DC 2001, June 2002,
- [3] Armenta C. Prediction of battery behavior in SAPV applications. Renew Energy 2003; 28(11): 1671 – 84.
- [4] Bansal, R.C., 2003. Bibliography on the Fuzzy set Theory applications in Power Systems (1994 – 2001)”, IEEE Trans. Energy Conversion , 18: 1291 – 1299.
- [5] Berndt D. Maintenance – free batteries. England Willey;1994.
- [6] Bogdon S.Borowy, Ziyad M. Salameh. 1996. Methodology for optimally sizing the combination of a battery bank and PV array in a wind-PV hybrid system. IEEE Transactions on energy conversion. 11(2): 367-375.
- [7] Borowy BS, Salameh ZM. Methodology for optimally sizing the combination of a battery bank and PV array in a wind/PV hybrid system. IEEE Trans Energy Converse 1996;11(2):367–73.
- [8] BP Solar BP SX150 - 150W Multi-crystalline Photovoltaic Module Datasheet, 2010
- [9] Castañer, Luis & Santiago Silvestre Modelling Photovoltaic Systems, Using PSpice John Wiley & Sons Ltd, 2002
- [10] Catherino HA, Burgel JF.et al. Modeling and simulation of lead – acid battery charging. J power sources 2001;96(1):113 – 20.
- [11] Ceraolo, M., 2000. New dynamical models of lead-acid batteries. IEEE Trans. Power Syst. 15 (4), 1184–1190.
- [12] Chan TF, Lai LL. An axial-flux permanent-magnet synchronous energy for a direct-coupled wind turbine system. IEEE Trans Energy Convers 2007; 22(1).
- [13] Chapin, D. M., C. S. Fuller, & G. L. Pearson, Bell Telephone Laboratories, Inc., Murray Hill, New Jersey “A New Silicon p-n Junction Photocell for Converting Solar Radiation into Electrical Power” Journal of Applied Physics, Volume 25, Issue5, May 1954, page 676-677
- [14] Copetti JB, Chenlo F, Lorenzo E. A general battery model for PV systemsimulation. Prog Photovoltaics Res Appl 1993;1:283–92
- [15] Cox, E., Fuzzy fundamentals, IEEE Spectrum, vol. 29, pp. 58-61, October 1992.
- [16] Dang, Thuy Lam A Digitally-controlled Power Tracker Master's Thesis, California Polytechnic State University, Pomona, 1990



- [17] D Le. Gourieres, 1982, Wind Power Plants Theory and Design, Oxford: Pergamon press, pp76-120.
- [18] Dufo-López R, Bernal-Agustín JL. Design and control strategies of PV–diesel systems using genetic algorithms. *Solar Energy* 2005;79(1):33–46.
- [19] Eken O, Eken BY, Ozerdem B. Break-evenanalysis and size optimization of a PV/wind hybrid energy conversion system with battery storage - A case study. *Applied Energy*; In Press, Corrected Proof.
- [20] E. Koutroulis, K. Kalaitzakis, April 2006, “Design of a Maximum Power Tracking System for Wind- Energy-Conversion Application”, *IEEE Transaction on Industrial Electronics*, Vol.53, No.2, pp486-494.
- [21] Ellition,D. ,Schwartz, M., Scott,G., Haymes,S.,Heimiller, D., George, R., Wind Energy Resource Atlas of Sri Lanka and the Maldives, National Renewable Energy Laborotory USA.
- [22] E. Muljadi, K. Pierce, P. Migliore, 2000, “Softcontrol control for variable-speed stall-regulated wind turbines”, *Wind Engineering*, Vol.85, pp277-291.
- [23] Francois Giraud and Zyiad M. Salmaeh.2001.Steady – state performance of a gri – connected rooftop hybrid wind – photovoltaic power system with battery storage. *IEEE Transaction of energy conversion*. Vol . 16,pp.1-6.
- [24] Green, Martin A. Solar Cells; Operating Principles, Technology, and System Applications Prentice Hall Inc., 1982
- [25] Guash D, Silvester S. Dynamic battery model for photovoltaic applications. *Prog photovoltaic Res Appl* 2003;11:193 – 206.
- [26] Hohm, D. P. & M. E. Ropp “Comparative Study of Maximum Power Point Tracking Algorithms” *Progress in Photovoltaics: Research and Applications* November 2002, page 47-62
- [27] Hussein, K. H., I. Muta, T. Hoshino, & M. Osakada “Maximum Photovoltaic Power Tracking: an Algorithm for Rapidly Changing Atmospheric Conditions” *IEE Proceedings – Generation, Transmission and Distribution – v. 142 January 1995*, page 59-64
- [28] Jossen, A., Garche, J., Sauer, D.U., 2004. Operation conditions of batteries in PV applications. *Solar Energy* 76, 759–769.
- [29] Kellogg WD, et al. Generation unit sizing and cost analysis for standalone wind, photovoltaic and hybrid wind/PV systems. *IEEE Trans Energy Convers* 1998;13(1):70–5.
- [30] Kerr MJ, Cuevas A, Generalized analysis of the illumination intensity Vs, open – circuit voltage of PV modules . *Solar energy* 2003; 76(1-3): 263 – 7.

- [31] Khan MJ, Iqbal MT. Pre-feasibility study of stand-alone hybrid energy systems for applications in Newfoundland. *Renew Energy* 2005;30(6):835–54.
- [32] Kim, S.C., Hong, W.H., 1999. Analysis of the discharge performance of a flooded lead/acid cell using mathematical modeling. *J. Power Sources* 77, 74–82.
- [33] K. Tan, S. Islam, June 2004, “Optimum Control Strategies in Energy Conversion of PMSG Wind Turbine System without Mechanical Sensors”, IEEE Transaction on Energy Conversion Vol.19, No.2, pp392-399.
- [34] Lavanya V, Gounden N Ammasai, Rao Polimera Malleswara. A simple controller using line commutated inverter with maximum power tracking for wind-driven grid-connected permanent magnet synchronous generators. In: Proceedings of IEEE PEDES; 2006. p. 1–6.
- [35] Lee Dong-Yun, Noh Hyeong-Ju, Hyun Dong-Seok, Choy Ick. An improved MPPT converter using current compensation method for small scaled PV-applications. In: IEEE Conference, vol. 3; 2003. p. 540–45.
- [36] Masters, Gilbert M. *Renewable and Efficient Electric Power Systems* John Wiley & Sons Ltd, 2004.
- [37] Md. Arifujjaman, M. T. Iqbal, J. E. Quaice, 2008, “Energy capture by a small wind-energy conversion system”, *Applied Energy*, Vol.85, pp41-51.
- [38] Messenger, Roger & Jerry Ventre *Photovoltaic Systems Engineering* 2nd Edition CRC Press, 2003
- [39] Mick Sagrillo, Apples & Oranges 02 Technical Appendix, Home Power magazine, URL: <http://wwwhomepower.com>
- [40] Mohmoud MM. On the storage batteries used in solar electric power systems and development of an algorithm for determining their ampere-hour capacity. *Electric Power Syst Res* 2004;71(1):85–9.
- [41] Mohanlal Kolhe, Sunita Kolhe and Joshi J.C. 2003. Economic viability of stand-alone solar photovoltaic system in comparison with diesel-powered system for India. *Energy economics*. Vol. 24, pp.155-165.
- [42] Muselli M, Notton G, Poggi P, Louche A. PV-hybrid power systems sizing incorporating battery storage: an analysis via simulation calculations. *Renew Energy* 2000;20(1):1–7.
- [43] Narayana M, Putrus G, Jovanovic M , Leune P. Maximum power tracking for variable speed fixed pitch small wind turbines. Prague, 8-11 June 2009, p.0542.
- [44] Ong Chee Mun. *Modeling and dynamic simulation of electric machinery using Matlab/Simulink*. Prentice Hall Press; 1998.
- [45] Piller S, Perrn M, Jossen A. Methods for state – of – charge determination and their applications. *Power sources* 2001;96(1):113-20.

- [46] Radziemska E, Klugmann E. Thermally affected parameters of the current-voltage characteristics of silicon photocell. *Energy Convers Manage* 2002;43(14):1889–900.
- [47] Salameh ZM, Cassacca MA, Lynch WA. A mathematical model for lead-acid batteries. *IEEE Trans Energy* 1992;7(1):93–7.
- [48] Simoes MG, Bose BK, Spiegel RJ. Fuzzy logic based intelligent control of a variable speed cage machine wind generation system. *IEEE Trans Power Electron* 1997;12(1):87–95.
- [49] S. Morimoto, H. Nakayama, M. Sanada, Jan/Fab 2005, Sensorless output maximization control for variable-speedwind generation systemusing IPMSG, IEE transaction on industrial applications, Vol.41, No.1, pp60-67.
- [50] Tan K, Islam S. Optimum control strategies in energy conversion of PMSG wind turbine system without mechanical sensors. *IEEE Trans Energy Convers* 2004;19(2):392–9.
- [51] T. Tanaka, T. Toumiya, 1997, “Output control by hillclimbing method for a small scale wind power generation system”, *Renewable Energy*, Vol.12, No.4, pp387-400.
- [52] Tina G, Gagliano S, Raiti S. Hybrid solar/wind power system probabilistic modeling for long term performance assessment. *Solar Energy* 2006;80: 578–88.
- [53] Tsai, Huan.-Liang, Tu, Ci.-Siang, Su, Yi.-Jie, 2008. Development of generalized photovoltaic model using MATLAB/SIMULINK. *Proceedings of the World Congress on Engineering and Computer Science 2008*. San Francisco, USA, pp. 846–851.
- [54] T. Esram, P.L. Chapman, Comparison of photovoltaic array maximum power point tracking techniques, *IEEE Transactions on Energy Conversion* 22 (June (2)) (2007)
- [55] Xinyan Zhang, Xiaobo Zhang, Peiyi Zhou, Jing Cheng, Ye Liu. Fuzzy control used in variable speed wind turbine. In: International conference on automation and logistics; 2009. p. 1194–8.
- [56] Yang HX,Lu L, Zho W.A novel optimization sizing model for hybrid solar – wind power generation system. *Solar energy* 2007;81(1): 76-84
- [57] Zadeh LA. A fuzzy-set-theoretic interpretation of linguistic hedges. *Cybernet* 1972;2:4–34.
- [58] Zoulias EI, Lymberopoulos N. Techno-economic analysis of the integration of hydrogen energy technologies in renewable energy based stand-alone power systems. *Renew Energy* 2007;32(4):680–96.