EVALUATION OF PUMPABILITY OF CONCRETE

K.D.N. Perera

178002L

Degree of Master of Science

Department of Civil Engineering

University of Moratuwa Sri Lanka

December 2019

EVALUATION OF PUMPABILITY OF CONCRETE

Kurugamage Dilini Nuwanthika Perera

178002L

Thesis submitted in partial fulfillment of the requirements for the degree of

Master of Science in Civil Engineering

Department of Civil Engineering

University of Moratuwa Sri Lanka

December 2019

DECLARATION

I declare that this is my own work and this thesis does not incorporate without acknowledgement any material previously submitted for a Degree or Diploma in any other University or institute of higher learning and to the best of my knowledge and belief it does not contain any material previously published or written by another person except where acknowledgement is made in the text.

Also, I hereby grant to University of Moratuwa the non-exclusive right to reproduce and distribute my thesis, in whole or in part in print, electronic or other medium. I retain the right to use this content in whole or part in future works (such as articles or books).

Signature:	Date:
The above candidate has carried out research	ch for the Masters under my supervision.
Name of the supervisor: Prof. S. M. A. Nar	ayakkara
Signature of the Supervisor:	Date:

DEDICATION

To my beloved parents, my loving husband and family for their overwhelming support and courage extended to me throughout this research project

And

To Prof. S. M. A. Nanayakkara, Dr. (Mrs.) M. T. P. Hettiarchchi and all of my dear teachers, who are the reasons behind my every successful step

ACKNOWLEDGEMENTS

My heartfelt gratitude goes to Prof S. M. A. Nanayakkara, my research supervisor for his expert guidance throughout the research project. Whenever, problems arose to achieve milestones and decisions had to be made, he confidently led me in the correct path.

The research project was funded by Siam City Cement (Lanka) Ltd. I am so grateful to Mr. Kalinda Dassanayake, the advisor for the research project from Siam City Cement (Lanka) Ltd; for providing all the necessary financial support and facilities for the experimental studies. The ICAR plus concrete rheometer was also provided by Siam City Cement (Lanka) Ltd.

I would like to acknowledge Prof. Asamoto for his generous advice and support for this project. He organized a diaphragm type pressure transducer and 20 strain gauges for the experiments at the time we needed. Those equipment played a major role in experiments conducted at the construction sites.

I warmly thank Dr. Takahashi for his kind advice and guidance. At some critical stages, his expert advice and recommendations were quite helpful for us to make decisions.

It was privilege to conduct research experiments at two high rise building projects with the support from Sanken Construction (Pvt) Ltd; who was the contractor of both construction sites. I would like to extend my gratitude to Ranjith San, Aruna San, Nalin San and Mr. Arshad for supporting my experimental studies. Furthermore, my special thanks goes to Rupasinghe San for providing us an altered pipe section in the pipe line circuit to fix the pressure transducer.

The dynamic data logger used to record data from pressure transducer and strain gauges was borrowed from structural Engineering Laboratory of Dept. of Civil Engineering at University of Ruhuna. My sincere thanks are to Dr. H. P. Sooriyaarachchi, Dr. N. H. Priyankara and Dr. K. S. Wanniayachchi of Dept. of Civil Engineering at University of Ruhuna for lending the data logger to use for the research experiments.

My special thanks goes to all the laboratory staff of Building Materials Laboratory and Structural Testing Laboratory; especially Mr. Leenus, Mr. Piyal and Mr. Lanka for the continuous support for my laboratory experiment.

I would also be pleased to acknowledge Dr. Damith Chathuranga, Mr. Janaka Basnayake and Mr. Uditha Roshan for their assistance in designing the bridge circuits for the strain gauges. Their technical support for the experimental investigations is much appreciated.

Last but not least, I am so much thankful to Mr. Tharanga Wickramasinghe for designing a laboratory apparatus (tribometer) as per my request.

Evaluation of Pumpability of Concrete

ABSTRACT

Current guidelines and practices at construction sites on concrete pumping has not been based on theoretical understanding of pipe flow of fresh concrete. In fact, only the slump value is monitored at construction sites, even-though any single point test is insufficient to represent flow curve properties of fresh concrete.

Based on flow curves of concrete and basic rheological properties, a theoretical model for horizontal straight flow has been developed and validated in previous studies. Yet, properties of concrete flow at horizontal and vertical bends, tapered sections and vertical lengths had to be investigated. In this research study, experimental investigations were carried out at two high rise building construction sites which included monitoring rheology of fresh concrete with ICAR plus concrete rheometer and pressure at some points of the concrete pumping pipe line with a pressure transducer and several strain gauges. In the horizontal straight section, theoretical pressure drop based on sheared plus plug flow condition could reasonably estimate the actual pressure drop with a 20% margin. Pressure drop at a horizontal bend was in between 0.5 to 1.7 bar while in a vertical bend it was around 6 bar. Pressure drop in the vertical straight length was equal to the pressure needed to overcome the self-weight only. Hence, concrete pumping pressure could be estimated within 20% margin.

Moreover, understanding on the influence of mix design parameters on concrete rheology is much useful for deciding the mix proportions of concrete at the mix design stage. A series of laboratory experiments were conducted at paste and mortar phases of concrete. Correct admixture concentration, increase of w/c ratio, decrease of fine aggregate volume concentration and round shape fine aggregates over angular shape found to be improving the rheological properties and hence the pumpability of concrete.

Key words: fresh concrete rheology, concrete pumping, concrete pipe flow

TABLE OF CONTENTS

Declaration .		i
Dedication		ii
Acknowledg	gements	iii
Abstract		v
Table of Con	ntents	vi
List of Figu	res	X
List of Table	es	xiii
List of Abbr	reviations	xiii
CHAPTER	1: Introduction	1
1.1 Ba	ckground	1
1.1.1	Current practices in Sri Lanka	2
1.1.2	Guidelines	3
1.1.3	Studies on concrete pumpability	6
1.2 Pro	oblem Statement	8
1.3 Ob	jective	9
1.4 Res	search Plan	9
1.5 Gu	ide to Thesis	10
1.5.1	Literature Review	10
1.5.2	Theoretical Investigation	10
1.5.3	Field Tests	11
1.5.4	Lab Experiments	11
1.5.5	Analysis and Conclusions	11
CHAPTER	2: Litrature review	12
2.1 Flo	ow Characteristics	12
2.1.1	Behaviour of Suspensions	12

	2.1	.2	Shear Thinning Effect	. 12
	2.1	.3	Thixotropic Behaviour	. 13
	2.2	The	eoretical Understanding on Concrete Pipe Flow	. 13
	2.2	.1	Lubrication layer	. 14
	2.2	2	Flow Curves	. 14
	2.2	3	Theoretical model by Kaplan	. 15
	2.3	App	paratus for Testing on Rheology of Concrete	. 16
	2.3	.1	Rheometers	. 16
	2.3	.2	Tribometers	. 18
	2.4	Fac	tors affecting Pumpability of Concrete	. 19
CI	HAPT	ER 3	3: Theory of Concrete Pipe-Flow	. 22
	3.1	Intr	roduction	. 22
	3.2	Flo	w curves of concrete	. 23
	3.2	.1	Flow curve of bulk concrete	. 26
	3.2	2	Flow curve of lubrication layer	. 27
	3.3	Me	chanism of concrete pipe flow	. 29
	3.4	The	eoretical model for concrete pipe flow	. 32
CI	HAPT	ER 4	4: Experimental Investigations	. 35
	4.1	Intr	oduction	. 35
	4.2	Equ	nipment	. 35
	4.2	1	Rheological Measurements with ICAR plus Rheometer	. 35
	4.2	2	Dynamic Data Logger – Kyowa Edx-100A	. 40
	4.2	3	Diaphragm type Pressure Transducer	. 41
	4.2	4	3-wire Strain Gauges	. 42
	4.3	Eva	aluation of Concrete Pumping in High-rise Building Constructions	. 44
	12	1	Duo andrum	17

4	.4	Lab	ooratory Experiments	49
	4.4	.1	Procedure of measurement of rheological properties	49
	4.4	.2	Rheometer Test	52
	4.4	.3	V funnel test	54
	4.4	.4	Flow Table Test	55
CH.	APT	ER 5	5: Results and Analysis	57
5	.1	Cha	ange of Fresh Concrete Properties and Influencing Factors	57
	5.1	.1	Discussion	60
	5.1	.2	Summary	62
5	.2	Inv	estigation on Pressure drops at horizontal and vertical bends	s and
h	orizo	ontal	and vertical straight sections	63
	5.2	.1	Instrumentation	63
	5.2	.2	Procedure	66
	5.2	.3	Analysis of field data	67
	5.2	.4	Pressure variation in Horizontal Straight pipe Section	70
	5.2	.5	Pressure drop at Horizontal Bend	74
	5.2	.6	Pumping pressure drop in Vertical pipe Length	76
	5.2	.7	Radial and Line pressure in concrete pumping pipe-line	78
	5.2	.8	Pumping pressure drop in Vertical Bend	78
	5.2	.9	Summary of the finding of the concrete pumping field test	80
5	.3	Infl	uence of Mix-Design Parameters on rheological properties of ce	ement
p	aste	and 1	mortar phases of concrete	80
	5.3	.1	Effect of PCE Dosage	80
	5.3	.2	W/C Ratio	85
	5.3	.3	Cement Type	88
	5 3	1	Fine Aggregate Concentration	90

5.3.5 Fine Aggregate Type	92
5.3.6 Summary of the important finding of lab investigation	. 95
CHAPTER 6: Conclusions	. 96
References	. 99
Appendix-I: Theoretical Derivations for Concrete Pipe Flow	103
Appendix-II: Theoretical Derivations for Sheared plus Plug Flow of Concrete	107
Appendix-III: Specifications and Calibration Report of ICAR plus Conc Rheometer	
Appendix-iv: Specifications of PWF-20MPB Pressure Transducer	111
Appendix-V: Specifications of FLA-5 Strain Gauge	112
Appendix-VI: Bridge Circuit details for Strain Gauges	113
Appendix-VII: Mix Design used for Slab Concrete at CCC	114
Appendix-VIII: Mix Design used for Slab Concrete at Luna Tower	115
Appendix-IX: Concrete Pumping Data from Several High Rise Constructions	116
Appendix-X: Observation sheets	123

LIST OF FIGURES

Figure 1-1: Estimation of Concrete Pumping Pressure Source: (Bognacki, et al., 1996)
4
Figure 1-2: Pressure loss per meter run Source: (Tamon & Hiroshi, 2010)
Figure 1-3: Research Plan
Figure 1-4: Guide to Thesis
Figure 2-1: Shear thinning effect
Figure 2-2: ConTec Viscometer 5 Source: (Feys, Khayat, Perez-Schell, & Khatib,
Development of a tribometer to characterize lubrication layer properties of self-
consolidating concrete, 2014)
Figure 2-3: ICAR plus Rheometer
Figure 2-4: Some Concrete Rheometers from literature Source: (Ferraris, et al., 2000)
Figure 2-5: Tribometer by Feys Source: (Feys, Khayat, Perez-Schell, & Khatib,
Development of a tribometer to characterize lubrication layer properties of self-
consolidating concrete, 2014)
Figure 2-6: Chapdelain's Tribometer Source: (Jolin, Burns, Bissonnette, Gagnon, &
Bolduc, 2009)
Figure 2-7: Tribometer by Ngo Source: (Ngo, Kadri, Bennacer, & Cussigh, 2010). 18
Figure 2-8: Sliding Pipe Rheometer Source: (Mechtcherine, Nerella, & Kasten, 2014)
Figure 3-1: Schematic pattern of concrete flow in pipe source: (Choi, Roussel, Kim,
& Kim, 2013b)
Figure 3-2: Shearing between layers of a fluid
Figure 3-3: Bingham Fluid Model
Figure 3-4: Flow curve of Bulk Concrete
Figure 3-5: Flow curve of Bulk Concrete
Figure 3-6: Lubrication Layer
Figure 3-7: Shear stress applied at r distance to the centre line
Figure 3-8: Shear stress, shear strain and shear rate of plug flow

Figure 3-9: Shear stress, shear strain and shear rate in case of sheared plus plug flow	W
condition	0
Figure 3-10: Resulting shear stress to induce fresh concrete pipe flow	2
Figure 3-11: Velocity Profile for Sheared flow model by Kaplan	3
Figure 3-12: Velocity profile for sheared plus plug flow	3
Figure 4-1: Assembly of the servo motor with vanes (a); Collecting a concrete sample	le
to the container (b) & Arrangement of the ICAR plus Rheometer (c)	6
Figure 4-2: Conducting a test with ICAR plus Rheometer at the construction site 3	6
Figure 4-3: Mechanism of torque and angular velocity	8
Figure 4-4: Flow condition in ICAR plus Rheometer	9
Figure 4-5: Strain gauge transducer to input to Edx-100A	0
Figure 4-6: Pressure transducer attached to the pipe line	1
Figure 4-7: Pressure transducer connection to the pipe line	.1
Figure 4-8: NDIS plug of the Pressure Transducer	2
Figure 4-9: Quarter Whenston Bridge circuit for Strain Gauge	.3
Figure 4-10: Compensation of lead wire length in 3 wire strain gauge	.3
Figure 4-11: Bridge Circuits used to connect strain gauges to the data logger 4	.4
Figure 4-12: Colombo City Centre Tower	.5
Figure 4-13: Construction site of 447 Luna	5
Figure 4-14: Field Experiment procedures	8
Figure 4-15: Procedure for lab tests	1
Figure 4-16: Stress Growth Test in ICAR plus rheometer	2
Figure 4-17: Flow Curve Test in ICAR plus rheometer	3
Figure 4-18: Schematic Diagram of the V funnel test apparatus	4
Figure 4-19: V funnel test	4
Figure 4-20: Schematic diagram of cone and hammer - flow table test for mortar 5	5
Figure 4-21: Flow Table Test for mortar	6
Figure 5-1: Pipe circuit details of Luna Tower construction site	3
Figure 5-2: Photos of the strain gauges	4
Figure 5-3: Fixing the altered pipe section to apply pressure transducer 6	5
Figure 5-4: Data Logger and Bridge circuits	6
Figure 5-5: Pressure and strain variation with pumping of LJ-0482 concrete truck6	7

Figure 5-6: Readings corresponding to several strokes	67
Figure 5-7: Prediction of dynamic pressure from strain gauge measurements	68
Figure 5-8: Averaging pressure and strain values in dynamic range	69
Figure 5-9: Pressure drop in horizontal length versus theoretical values	71
Figure 5-10: Pressure drop in horizontal section w.r.t. Plastic Viscosity	72
Figure 5-11: Asymmetric flow profile due to gravity	73
Figure 5-12: Possible flow curve patterns for fresh concrete	74
Figure 5-13: Pressure drop in 90 ⁰ Horizontal bend w.r.t. guidelines predictions	75
Figure 5-14: Pressure drop in Vertical length	77
Figure 5-15: Pressure drop in Vertical 90 ⁰ bend w.r.t. guideline predictions	79
Figure 5-16: DYS over PCE dosage - Paste phase	82
Figure 5-17: PV over PCE dosage - Paste phase	82
Figure 5-18: DYS over PCE dosage - Mortar phase	83
Figure 5-19: PV over PCE dosage - Mortar phase	83
Figure 5-20: Flow-rate prediction over PCE dosage - Mortar phase	84
Figure 5-21: DYS over w/c ratio - Paste phase	86
Figure 5-22: PV over w/c ratio - Paste phase	86
Figure 5-23: DYS over w/c ratio - Mortar phase	87
Figure 5-24: PV over w/c ratio - Mortar phase	87
Figure 5-25: Flow-rate prediction over w/c ratio - Mortar phase	88
Figure 5-26: DYS over Cement type - Paste phase	89
Figure 5-27: PV over Cement type - Paste phase	89
Figure 5-28: DYS over Fine Aggregate Concentration - Mortar Phase	91
Figure 5-29: PV over Fine Aggregate Concentration - Mortar phase	91
Figure 5-30: Flow-rate prediction over Fine Aggregate Concentration - Mortar p	hase
	92
Figure 5-31: DYS over Fine Aggregate type - Mortar phase	93
Figure 5-32: PV over Fine Aggregate type - Mortar phase	93
Figure 5-33: Flow-rate prediction over Fine Aggregate type - Mortar phase	94

LIST OF TABLES

Table 1-1: Equivalent Horizontal Pipe Length Source: (Tamon & Hiroshi, 2010)	5
Table 4-1: Mix proportions of concrete phase control specimen	49
Table 4-2: Paste phase control sample	49
Table 4-3: Control sample in mortar phase	50
Table 4-4: Mix design parameters studied in lab experiments	50
Table 5-1: Change of fresh concrete properties	59
Table 5-2: Average Dynamic pressure at each section	69
Table 5-3: Pressure Drop in 15.3 m Horizontal Straight Pipe section	71
Table 5-4: Pressure Drop in Horizontal 90 ⁰ Bend of 370 mm radius	75
Table 5-5: Pressure Drop in 39 m long Vertical Straight Pipe	76
Table 5-6: Pressure Drop in 90° Vertical Bend of 400 mm radius	78
Table 5-7: Tested Cement Types	88

LIST OF ABBREVIATIONS

ACI American Concrete Institute JSCE Japan Society of Civil Engineers rpm revolutions per minute SYS Static Yield Stress DYS Dynamic Yield Stress PV Plastic Viscosity CA Coarse Aggregate FΑ Fine Aggregate Water to Cement ratio by weight w/c CCCColombo City Centre OPC **Ordinary Portland Cement** PCE Poly Carboxylic Ether PLC Portland Limestone Cement MS Manufactures Sand