

DECLARATION

The work submitted in this dissertation is the result of my own investigation, except where otherwise stated.

It has not already been accepted for any degree, and is also not being concurrently submitted for any other degree.




University of Moratuwa, Sri Lanka.
Electronic Theses & Dissertations
www.lib.mrt.ac.lk


A.D.M. Jeeth

Date: April 30, 2009

~~We~~/ I endorse the declaration by the candidate


30/04/2009

Project supervisor: Dr. Nalin Wickramarachchi

CONTENTS

| | |
|---|----------|
| Declaration | i |
| Abstract | v |
| Acknowledgement | vii |
| Table of content | ii |
| List of Figures | viii |
| List of Tables | ix |
| 1. Introduction | 1 |
| 1.1 Background about Colombo Dockyard PLC | 1 |
| 1.2 Basic Introduction for current work practice at Colombo Dockyard PLC | 1 |
| 1.2.1 Current welding procedure which is practicing at yard | 1 |
| 1.2.2 Energy wastage during idle period due to open circuit core loss & iron loss | 2 |
| 1.2.3 Specification & general configuration of Welding Transformer at Colombo Dockyard PLC | 3 |
| 1.2.4 Utilization of arc welding transformers in Colombo Dockyard PLC | 4 |
| 1.3 Goals and Scope of present work | 5 |
| 2. Statement of the Problem | 6 |
| 2.1 Preliminaries | 6 |
| 2.2 Problem identification & Thesis statement | 7 |

| | |
|--|----|
| 3. Gathered technical data and its Analysis during execution of design approach | 8 |
| 3.1 CT out put current and voltage measurements which Relevant to each of CT under current sensing design approach | 8 |
| 3.2 Measured parameters during voltage sensing design | 10 |
| 3.3 Following are the measured values of primary and secondary parameters when secondary under load | 11 |
| 3.4 Behavioral study of welding transformer by connecting various types of step down transformers parallel to primary winding of welding transformer | 12 |
| 3.5 Measuring of total idling time and study of operator’s behavioral pattern which relevant to each work location | 14 |
| 3.5.1 Why idling can not eliminate during steel fabrication process | 14 |
| 3.5.2 Instrument used to measure the idling time and to study operator’s work pattern | 15 |
| 3.5.3 Sample screen shots during study of operator’s work pattern from above SCOPE meter | 16 |
| 3.5.4 Data collected which relevant to each work location to measure total idling time for 10 hours of total time period | 17 |
| 3.5.5 Study of operator’s work pattern during general welding operation in order to decide the best timer setting which relevant to voltage sensing approach | 21 |
| 4. Proposed and implemented solutions | 26 |
| 4.1 Design approach and evolution of design concept | 26 |
| 4.2 Design concept – 1 | 27 |
| 4.3 Design concept – 2 (Current sensing approach) | 27 |
| 4.3.1 Why current sensing approach was not feasible | 28 |

| | | |
|-----------|---|-----------|
| 4.4 | Design concept – 3 (Voltage sensing approach No – 1) | 29 |
| 4.4.1 | Operating procedure | 29 |
| 4.5 | Design concept – 4 {Final} , Voltage sensing approach No – 2 | 32 |
| 4.5.1 | Difference between Design concept – 3 & Design concept – 4 | 32 |
| 4.5.2 | Calculation of resister value for Variable resister which has used in control circuit | 34 |
| 4.6 | Operation procedure according to the final design | 35 |
| 4.7 | Functional block diagram according to the final design | 37 |
| 5. | Energy saving calculations and cost benefit analysis | 38 |
| 5.1 | Material used for control circuit and their cost | 38 |
| 5.2 | Measuring of actual active power consumption of welding T/F when idling with out implementing new system | 39 |
| 5.3 | Energy saving calculation | 39 |
| 5.4 | Calculation of simple pay back period | 40 |
| 5.5 | Comparison between active power consumption of welding T/F when idling with & with out implementing new system | 40 |
| 6. | Conclusion | 42 |
| | References | 43 |
| | APPENDIX – A Sample screen shots during study of operator’s work pattern from FLUKE SCOPE meter | 44 |
| | APPENDIX – B Literature about instrument and equipments which were used | 49 |

Acknowledgement

I express my sincere thanks to all the following individuals, those who contributed towards the completion of my final project successfully under my M.Sc/PG Diploma in Industrial Automation 2006/07 course.

At the very beginning my gratitude goes to the project supervisor Dr. Nalin Wickramarachchi, senior lecturer, department of electrical engineering, University of Maratuwa. I am indebted to my project supervisor for his immense guidance and excellent technical advices for success of my project. I would like to extend my sincere thanks to Prof. J. Rohan Lucas, Prof. H.Y. Ranjit Perera, Head department of electrical engineering Prof. J.P. Karunadasa,

Prof.Lanka Udawatta and Dr. Sisil Kumarawadu who gave their valuable advices for success of my project. I would like to take this opportunity to deliver my sincere thank to MD/CEO Mr. Mangala P.B. Yapa and Mr. D.A.P Senasinghe, Assistant Production Manager (Electrical and Automation) for their guidance and opportunity given to me to initiate and execute my project within the yard premises. Again thankful to Mr. D.A.P Senasinghe for his technical advices and immense guidance for the success of my project.

My sincere thanks should also go to the young engineers specially Mr. E. M. M. B Yatiyana and Mr. P. H. K. H Puhulwella in the Electrical and Automation Department. They positively contributed me for the success of my project. Also tanks should also go to electrical workshop engineer Mr. H.R.K.K. Ariyaratne too.

My thanks also go to the instrument technicians from automation workshop who worked under me. Appreciate their work during gathering field data and during execution of project in real situation. I am again thankful to the all of above and success of my project mainly depends upon the help and support given by them.

A.D.M.Jeeth.

April 30, 2009

List of Figures

| Figure | Page No |
|---|---------|
| Figure 1.1 - General configuration of welding transformer | 4 |
| Figure 3.1 - General arrangement of welding transformer | 8 |
| Figure 3.2 – Transformer with external devices during behavioral study | 12 |
| Figure 3.3 – Sample screen shots during study of operator’s work pattern | 16 |
| Figure 3.4 – Graphical representation of measured average idling periods which relevant to each work location | 20 |
| Figure 3.5 – Study of operator’s work pattern during each continuous welding run | 21 |
| Figure 3.6 – Graphical representation of summarized measured average idling periods during each continuous welding run for each work location | 25 |
| Figure 4.1 - Circuit diagram which relevant to Design concept 2 | 28 |
| Figure 4.2 - Circuit diagram which relevant to Design concept 3 | 31 |
| Figure 4.2 - Circuit diagram which relevant to Design concept 4 | 33 |
| Figure 4.4 – Resistor arrangement to maintain required voltage across relay (R_1) | 34 |
| Figure 4.5 - Functional block diagram according to the final design | 37 |

List of Tables

| Table | Page No |
|--|----------------|
| Table 1.1 – Measured power consumption during idling when 400 VAC gets connects with primary | 3 |
| Table 1.2 – Utilization of arc welding transformers in Colombo Dockyard PLC | 4 |
| Table 3.1 - CT out put current and voltage measurements with CT Ration: 100 / 5 A & $V_1 = 24$ VAC | 8 |
| Table 3.2 - CT out put current and voltage measurements with CT Ration: 100 / 5 A & $V_1 = 400$ VAC | 9 |
| Table 3.3 - CT out put current and voltage measurements with CT Ration: 400 / 5 A & $V_1 = 24$ VAC | 9 |
| Table 3.4 - CT out put current and voltage measurements with CT Ration: 400 / 5 A & $V_1 = 400$ VAC | 10 |
| Table 3.5 - Measured values of I_1 & V_2 by varying transformer current setting | 10 |
| Table 3.6 - Measured values of primary and secondary parameters when secondary under load and $V_1 = 400$ VAC | 11 |
| Table 3.7 - Measured values of primary and secondary parameters when secondary under load and $V_1 = 24$ VAC | 11 |
| Table 3.8 - Measured values of primary and secondary parameters when secondary under load and $V_1 = 48$ VAC | 11 |
| Table 3.9 – Readings during behavioral study @ $V_1 = 24$ V AC with 110 VAC / 24 VAC step down transformer | 13 |
| Table 3.10 – Readings during behavioral study @ $V_1 = 48$ V AC with 110 VAC / 24 VAC step down transformer | 13 |
| Table 3.11 – Readings during behavioral study @ $V_1 = 220$ V AC with 110 VAC / 24 VAC step down transformer | 13 |
| Table 3.12 – Readings during behavioral study @ $V_1 = 400$ V AC with 110 VAC / 24 VAC step down transformer | 14 |

| | |
|--|----|
| Table 3.13 – Readings during behavioral study @ $V_1 = 400$ V AC with 80 VAC / 12 VAC step down transformer | 14 |
| Table 3.14 – Measured idling periods at Yard welding pool | 17 |
| Table 3.15 – Measured idling periods at Metal Workshop (MEW) | 17 |
| Table 3.16 – Measured idling periods at Pipe Fabrication workshop (PFS) | 17 |
| Table 3.17 – Measured idling periods at Deck fitting workshop (FIS DEC) | 18 |
| Table 3.18 – Measured idling periods at Steel workshop | 18 |
| Table 3.19 – Measured idling periods at Component workshop (COM) | 18 |
| Table 3.20 – Measured idling periods at Machinery outfitting workshop (MOF) | 19 |
| Table 3.21 – Summary of measured average idling periods which relevant to each work location | 19 |
| Table 3.22 – Measured idling period during each continuous welding run, Location: Yard welding pool | 22 |
| Table 3.23 – Measured idling period during each continuous welding run, Location: Metal Workshop (MEW) | 22 |
| Table 3.24 – Measured idling period during each continuous welding run, Location: Pipe Fabrication workshop (PFS) | 22 |
| Table 3.25 – Measured idling period during each continuous welding run, Location: Deck fitting workshop (FIS DEC) | 23 |
| Table 3.26 – Measured idling period during each continuous welding run, Location: Steel workshop | 23 |
| Table 3.27 – Measured idling period during each continuous welding run, Location: Component workshop (COM) | 23 |
| Table 3.28 – Measured idling period during each continuous welding run, Location: Machinery outfitting workshop (MOF) | 24 |
| Table 3.29 – Summary of measured average idling period during each continuous welding run, For each work location | 24 |

| | |
|---|----|
| Table 4.1 - Measured data by varying V_1 when secondary in open circuit (no load) | 26 |
| Table 5.1 – Material list for one unit with their prices | 38 |
| Table 5.2 - Measured data about active power consumption of welding T/F when idling with out implementing new system | 39 |
| Table 5.3 – Reading observed from energy meter | 40 |
| Table 5.4 – Actual energy consumption after deducting initial meter reading | 41 |



University of Moratuwa, Sri Lanka.
Electronic Theses & Dissertations
www.lib.mrt.ac.lk