References

- "Dispersion compensating fiber," https://www.thorlabs.com/catalogpages/ obsolete/2017/DCF38.pdf, accessed: 2020-10-10.
- [2] "What is zero water peak fiber?" https://www.fiberoptics4sale.com/blogs/ archive-posts/95050054-what-is-zero-water-peak-fiber, accessed: 2020-10-10.
- [3] X. Chen, "Ultra-narrow laser linewidth measurement." Virginia Polytechnic Institute and State University, 2006, pp. 17–27.
- [4] R. U. Weerasuriya, "Data retiming for multi-wavelength regeneration," Ph.D. dissertation, Ireland, 2011.
- [5] J. J. Hamd-Ameen, "Dispersion and intersymbol interference (isi) in optical fibers," *International Conference on Communication, Computer Power* (ICCCP'07), p. 366, February 2007.
- [6] L. V. T. Nguyen, in Distributed feedback (DFB) laser coherence and linewidth broadening. Defence Science and Technology Organization, 2003, pp. 1–44.
- [7] P.Frascella, "Dpsk signal regeneration with a dual-pump non-degenerate phase-sensitive amplifier," *Photonic Technology Letters*, vol. 23, no. 8, pp. 516–518, 2011.
- [8] J. M. Senior, "Optical fiber communications," in Proceedings of the 23rd Annual Conference on Computer Graphics and Interactive Techniques. UK:Pearson Education Limited, 2009.
- [9] R.Slavık, "All-optical phase and amplitude regenerator for next-generation telecommunications systems," *Nature Photonic*, vol. 4, no. 2, pp. 690–695, 2010.

- [10] R.Weerasuriya and et al, "Novel carrier extraction scheme for phase modulated signals using feed-forward based modulation stripping," *Optical Soci*ety of America, pp. 19–23, 2010.
- [11] C. Cheng and et al, "Measurement of the carrier recovery time in soa based on dual pump fwm," in n asia communications and photonics conference and exhibition," Asia Communications and Photonics conference and Exhibition (ACP), Optical Society of America, 2009.
- [12] K.-T. Wu and H. Sun, "Techniques in carrier recovery for optical coherent systems," in OFC/NFOEC. Technical Digest of Optical Society of America, 2012, p. paper OTh4c.3.
- [13] R.Weerasuriya and et al, "Generation of frequency symmetric signal from a bpsk input for phase sensitive amplification," *Optical Society of America*, 2010.
- [14] T. Maiman, "Stimulated optical radiation in ruby," Nature, vol. 187, pp. 493–494, 1960.
- [15] F. P. Kapron and et al, "Radiation losses in glass optical waveguides," Applied Physics Letters, vol. 17, pp. 423–425, 1970.
- [16] G. Agrawal, "Fiber optics communication system," 2002, pp. 1–18.
- [17] S. Tomaru and et al, "Vad single mode fibre with 0 2 db/km loss," *ELEC-TRONICS LETTERS*, vol. 17, no. 02, pp. 92–93, 1981.
- [18] H. Kanamori and et al, "Transmission characteristics and reliability of puresilica-core single- mode-fibers," *Journal of Lightwave technology*, vol. 04, pp. 1144–1150, 1986.
- [19] K. Nagayama and et al, "Ultra low loss (0.151 db/km) fiber and its impact on submarine transmission systems," Optical Fiber communication conference and exhibits, pp. FA10–1– FA10–3, 2002.
- [20] T. Miya and et al, "Ultimate low-loss single-mode fibre at 1.55 μ m," *Electronic Letters*, vol. 15, no. 4, pp. 106–108, 1979.
- [21] R. Linke and A. Gnauck, "High-capacity coherent lightwave system," Journal of Lightwave technology, vol. 06, no. 11, pp. 1750–1769, 1988.

- [22] P. Henry, "Lightwave primer," *IEEE Journal of Quantum Electronics*, vol. 21, no. 12, pp. 1862–1879, 1985.
- [23] N. S. Bergano and et al, "A 9000 km 5 gb/s and 21,000 km 2.4 gb/s feasibility demonstration of transoceanic edfa systems using a circulating loop," *Fiber Optic Communication*, vol. 4, p. PD 13, 1991.
- [24] K. Fukuchi and et al, "10.92-tb/s (273 x 40-gb/s) triple-band/ultra-dense wdm optical-repeatered transmission experiment," Optical Fiber Communication Conference and International Conference on Quantum Information, p. PD 24, 2001.
- [25] G. Vareille and et al, "3 tbit/s (300 x 11.6 gbit/s) transmission over 7380 km using c+l band with 25 ghz channel spacing and nrz format," Optical Fiber Communication Conference and International Conference on Quantum Information, p. PD 22, 2001.
- [26] K. Schuh and et al, "1 t bit/s (10 x 107 gbit/s etdm) serial nrz transmission over 480km ssmf," Optical Fiber Communication Conference and Exposition and The National Fiber Optic Engineers Conference, p. PDP23, 2007.
- [27] G. A. Thomas and et al, "Towards the clarity limit in optical fiber," Nature, vol. 404, pp. 262–264, 2000.
- [28] W. J. Smith, "Modern optical engineering (3rd edn)." McGraw Hill, 2000.
- [29] R. L. Freeman, "Fundamentals of telecommunication." John Wiley and Sons, 1999.
- [30] F. L. Pedrotti and et al, "introduction to optics (3rd edn)." Prentice Hall, 2006.
- [31] E. Hecht and A. Zajac, "Optics (4th edn)." Addison-Wesley, 2003.
- [32] F. Graham and et al, "Optics and photonics: An introduction (2nd edn)." John Wiley and sons publication, 2007.
- [33] G. P. Agrawal, "Lightwave technology." John Wiley and sons publication, 2005.
- [34] G. Agrawal, "Nonlinear fiber optics," 2007.

- [35] R. Ramaswami and K. Sivarajan, "A practical perspective," in Optical Networks, 2002, pp. 43–54.
- [36] K. P. ho, "Phase modulated optical communication systems." Springer, 2005, pp. 1–40, 118–128, 129–137.
- [37] S. Jawla, "Intensity modulation formats in optical communication system," International Journal of Scientific & Engineering Research, vol. 4, no. 4, 2013.
- [38] E. IP and J. M. Kahn, "Power spectra of return-to-zero optical signals," Journal of Lightwave Technology, vol. 24, pp. 1610–1618, 2006.
- [39] P. J. Winzer and R. J. Essiamber, "Advance modulation format for high capacity optical transport network," *Journal of Lightwave Technology*, vol. 24, pp. 4711–4728, 2006.
- [40] R. Singh and S. Jawla, "Different modulation formats used in optical communication," IOSR Journal of Electronics and Communication Engineering (IOSR-JECE), vol. 8, no. 4, 2013.
- [41] "Frequency shift keying," https://www.tutorialspoint.com/digital_ communication/digital_communication_frequency_shift_keying.htm, accessed: 2020-10-06.
- [42] G. Breed, "A tutorial introduction to optical modulation techniques," High Frequency design optical Modulation, Summit Technical Media, 2007.
- [43] A. H. Gnauck and P. J. Winzer, "Optical phase-shift-keyed transmission," Journal of Lightwave Technology, vol. 23, no. 1, pp. 115–130, 2005.
- [44] T. Chikama and et al, "Modulation and demodulation techniques in optical heterodyne psk transmission systems," *Journal of Lightwave Technology*, vol. 8, no. 3, pp. 309–322, 1990.
- [45] "Understanding quadrature phase shift keying (qpsk) modulation," https://www.allaboutcircuits.com/technical-articles/ quadrature-phase-shift-keying-qpsk-modulation/, accessed: 2020-10-28.
- [46] C. H. Henry, "Theory of the linewidth of semiconductor laser," *IEEE Jour*nal of Quantum Electronics, vol. QE-18, no. 02, pp. 259–264, 1982.

- [47] M. Fleming and A. Mooradian, "Fundamental line broadening of singlemode (gaal)as diode lasers," *Applied Physics Letters*, vol. 38, pp. 511–513, 1981.
- [48] M. Lax, "Classical noise. v. noise in self-sustained oscillators," *Physical Review Journals Archive*, vol. 160, pp. 290–307, Aug 1967.
- [49] K. Vahala and A. Yariv, "Semiclassical theory of noise in semiconductor lasers-part i," *IEEE JOURNAL OF QUANTUM ELECTRONICS*, vol. 19, pp. 1096–1101, June 1983.
- [50] M. Lax, "Quantum noise x density-matrix treatment of field and populationdifference fluctuations," *Physical Review Journals Archive*, vol. 157, pp. 213–231, May 1967.
- [51] J. van der Ziel, "Spectral broadening of pulsating alxga1-xas double heterostructure lasers," *IEEE Journal of Quantum Electronics*, vol. 15, no. 11, pp. 1277–1281, 1979.
- [52] B. W. Hakki, "Optical and microwave instabilities in injection lasers," Journal of Applied Physics, vol. 51, no. 1, pp. 68–73, 1980.
- [53] "My laser spectrum," http://mylaserspectrum.com/2018/02/ spectral-purity-laser-assessed/, accessed: 2020-11-10.
- [54] n. y. Voo and et al, "Linewidth and phase noise characteristics of dfb fibre lasers," *Proceedings of SPIE - The International Society for Optical Engineering*, vol. 5620, 12 2004.
- [55] "Laser spectral linewidth," NKT Photonics, no. 09, 2013.
- [56] "Full width half maximum," https://www.schoolsobservatory.org/discover/ projects/clusters/fwhm, accessed: 2020-11-10.
- [57] D. Derickson, in Fiber Optic Test and Measurement. Prentice Hall PTR, 1998, pp. 169–191, 475–486.
- [58] R. Tkach and A. Chraplyvy, "Phase noise and linewidth in an ingaasp dfb laser," *Journal of Lightwave Technology*, vol. 4, no. 11, pp. 1711–1716, 1986.
- [59] H. Qi, W. Wang, G. Guo, and Z. Song, "A practical perspective," in Handbook of Optical Fibers. springer, Singapore, 2018.

- [60] "Ultra-narrow laser linewidth measurement," https://vtechworks.lib.vt. edu/handle/10919/11124, accessed: 2020-10-04.
- [61] O. Ishida, "Delayed-self-heterodyne measurement of laser frequency fluctuations," *Journal of Lightwave Technology*, vol. 9, no. 11, pp. 1528–1533, 1991.
- [62] L. B. Mercer, "1/f frequency noise effects on self-heterodyne linewidth measurements," *Journal of Lightwave Technology*, vol. 9, no. 4, pp. 485–493, 1991.
- [63] I. Blekhman, "Synchronization in science and technology." ASME Press, 1988.
- [64] M. G. Rosenblum, "Phase synchronization of chaotic oscillators," American Physical society, vol. 76, no. 11, pp. 1804–1807, 1996.
- [65] V. Ferrero and S. Camatel, "Optical phase locking techniques: an overview and a novel method based on single side sub-carrier modulation," *Opt. Express*, vol. 16, no. 2, pp. 818–828, Jan 2008.
- [66] T. Xu and et al, "A carrier synchronization method for global synchronous pulse width modulation application using phase-locked-loop," *IEEE Trans*actions on Power Electronics, 02 2019.
- [67] https://www.slideshare.net/FuyunLing/phaselocked-loop-pll-and-carriersynchronization-fuyun lingv13.
- [68] K. Iwashita and K. Nakagawa, "Suppression of mode partition noise by laser diode light injection," *IEEE Journal of Quantum Electronics*, vol. 18, no. 10, pp. 1669–1674, 1982.
- [69] K. K. A. Murakami and K. Atsuki, "Cavity resonance shift and bandwidth enhancement in semiconductor lasers with strong light injection," *IEEE Journal of Quantum Electronics*, vol. 39, no. 10, pp. 1196–1204, 2003.
- [70] C. H. Henry, "Locking range and stability of injection locked 1.54 pm ingaasp semiconductor lasers," *IEEE Journal Of Quantum Electronics*, vol. 21, no. 08, pp. 1152–1157, August 1985.
- [71] L. Winkelmann and et al, "Injection-locked single-frequency laser with an output power," *Applied Physics*, vol. 102, pp. 529–538, February 2011.

- [72] N. Schunk and K. Petermann, "Noise analysis of injection-locked semiconductor injection lasers," *IEEE Journal of Quantum Electronics*, vol. 22, no. 5, pp. 642–650, 1986.
- [73] W. Han and et al, "The optical injection locking technique and its applications for wdm-pon spare function," *Proceedings of SPIE - The International Society for Optical Engineering*, vol. 7278, 2009.
- [74] R. W. Boyd, "Nonlinear optics." Elsevier Publications, 2011, p. Chapter 1.
- [75] E. Ip and J. M. Kahn, "Feedforward carrier recovery for coherent optical communications," *Journal of Lightwave Technology*, vol. 25, no. 9, pp. 2675– 2692, 2007.
- [76] R. Ramaswami and G. H. Sivaragan, "Optical networks (3rd edn)." Elsevier Publications, 2010, pp. 78–95, 314–325.
- [77] M. Hofer and et al, "Mode locking with cross-phase and self-phase modulation," Opt. Lett., vol. 16, no. 7, pp. 502–504, Apr 1991.
- [78] A. Hasegawa and F. Tappert, "Transmission of stationary nonlinear optical pulses in dispersive dielectric fibers. i. anomalous dispersion," *Applied Physics Letters*, vol. 23, no. 3, pp. 142–144, 1973.
- [79] K. Inoue, "Four-wave mixing in an optical fiber in the zero-dispersion wavelength region," *Journal of Lightwave Technology*, vol. 10, no. 11, pp. 1553– 1563, 1992.
- [80] N. Shibata, "Phase-mismatch dependence of efficiency of wave generation through four-wave mixing in a singal mode optical fiber," *IEEE journal of quntum electronics*, vol. 23, no. 07, pp. 1205–1211, 1987.
- [81] K.Inoue, "Wavelength conversion experiment using fiber four-wave mixing," *IEEE Photonic Technology letters*, vol. 4, no. 01, pp. 69–73, 1992.
- [82] M. T. Osamu Aso and S. Namiki, "Four-wave mixing in optical fibers and its applications," *Furukawa Review*, no. 19, pp. 63–68, 2000.
- [83] X. Yang and et al, "Four-wave-mixing-assisted room-temperature fourwavelength erbium-doped fiber lasers," *Optical Engineering - OPT ENG*, vol. 45, 06 2006.

- [84] S. Tomaru and et al, "Vad single mode fibre with 0 2 db/km loss," *Electronics Lwtters*, vol. 17, no. 2, pp. 92–93, 1981.
- [85] K. Nagayama and et a, "ultra low loss (0.151 db/km) fiber and its impact onsubmarine transmission systems," Optical Fiber communication conference and exhibits, pp. FA10–1–FA10–3, 2002.
- [86] A. C. Cokrak and A. Altuncu, "Gain and noise figure performance of erbium doped fiber amplifiers (edfa)," *Journal of Electrical and Electronics Engineering*, vol. 04, no. 2, pp. 1111–1122, 2004.
- [87] S. M. J. Alam and et al, "Bit error rate optimization in fiber optic communications," *International Journal of Machine Learning and Computing*, vol. 01, no. 5, pp. 435–440, 2011.
- [88] R. Application note, HFAN-9.0.2, "Optical signal-to-noise ratio and the qfactor in fiber-optic communication systems." Maxim integrated, 04/08.
- [89] K. Lau, "Signal to noise ratio calculation for fiber optic links." TDA Progress Report, Communication Systems Research Section, Jet Propulsion Laboratory, 1980, pp. 41–48.
- [90] "Dispersion," https://www.daenotes.com/electronics/ communication-system/dispersion, accessed: 2020-11-03.
- [91] P. J. Winzer and R. J. Essiambre, "Advanced optical modulation formats," *Proceedings of the IEEE*, vol. 94, no. 5, pp. 952–985, 2006.
- [92] J. c. Daly and I. D. Aggrawal, "Optical waveguide manufacturing," in *Fiber Optics*, 1984, pp. 22–40.
- [93] "Optical fiber dispersion," https://www.fiberoptics4sale.com/blogs/ archive-posts/95047942-optical-fiber-dispersion, accessed: 2020-11-03.
- [94] R.Weerasuriya and et al, "Chromatic dispersion tolerance of 42.65gbit/s dual gate asynchronous digital optical regenerator," *Photonics Ireland*, 2009.
- [95] P. Pecci and et al, "Tolerance to dispersion compensation parameters of six," *Electronics Letters*, vol. 39, no. 25, pp. 1844–1846, 2003.

- [96] B. Clesca and et al, "The wdm answer to line-rate increase within the terrestrial fiber-based networks," in *Proceedings of GLOBECOM'96. 1996 IEEE Global Telecommunications Conference*, vol. 3, 1996, pp. 1925–1929.
- [97] I. S. Amiri and M. Ghasemi, "Design and development of optical dispersion characterization systems." Springer, 2019, p. 9.
- [98] S. Ramachandran, "Fiber based dispersion compensation." Springer, 2007, pp. 154–155.
- [99] "Intermodal dispersion," https://www.rp-photonics.com/intermodal_ dispersion.html, accessed: 2020-11-03.
- [100] M. O. R. Hui, "Fiber optic measurement techniques." Academic press, 2009, pp. 394–397.
- [101] S. K. Ibrahim and et al, "Novel carrier extraction scheme for phase modulated signals using feed-forward based modulation stripping," *ECOC*, pp. 19–23, 2010.
- [102] K. Wu and H. Sun, "Techniques in carrier recovery for optical coherent systems," OFC/NFOEC Technical Digest of Optical Society of America, p. OTh4c.3.pdf, 2012.
- [103] W. Imajuku and A. Takada, "In-line optical phase-sensitive amplifier with pump light source controlled by optical phase-lock loop," *Journal of Light*wave Technology, vol. 17, no. 4, pp. 637–646, 1999.
- [104] "Method and apparatus for use in carrier recovery in a communications system," https://patents.google.com/patent/US7894333B2/en, accessed: 2020-12-15.
- [105] S. Norimatsu, "Optimum optical power splitting ratio of decision driven phase-locked loop in bpsk optical homodyne receiver," *Journal of Lightwave Technology*, vol. 13, no. 11, pp. 2183–2190, 1995.
- [106] "Complexity reduced feed forward carrier recovery methods for m-qam modulation formats," https://patents.google.com/patent/US8908809B2/en, accessed: 2020-12-15.

- [107] I. Kim and et al, "All-optical carrier synchronization using a phase-sensitive oscillator," *IEEE PHOTONICS TECHNOLOGY LETTERS*, vol. 19, p. 13, 2007.
- [108] K. Croussore and G. Li, "Phase and amplitude regeneration of differential phase-shift keyed signals using phase-sensitive amplification," *IEEE Journal* of Selected Topics in Quantum Electronics, vol. 14, no. 3, pp. 648–658, 2008.
- [109] M. Qiu and et al, "Simple and efficient frequency offset tracking and carrier phase recovery algorithms in single carrier transmission systems," *Optical Express*, vol. 21, pp. 8157–8165, 2013.
- [110] X. Zhou, "Hardware efficient carrier recovery algorithms for single-carrier qam systems," Advanced Photonics Congress, OSA, 2012.
- [111] S.-L. Lee and et al, "Performance enhancement on soa-based four-wavemixing wavelength conversion using an assisted beam," *IEEE Photonics Technology Letters*, vol. 14, no. 12, pp. 1713–1715, 2002.
- [112] G. Lu and et al, "Format conversion of optical multilevel signals using fwmbased optical phase erasure," *Journal of Lightwave Technology*, vol. 29, no. 16, pp. 2460–2466, 2011.
- [113] R. Weerasuriya and et al, "Generation of frequency symmetric signals from a bpsk input for phase sensitive amplification," in 2010 Conference on Optical Fiber Communication (OFC/NFOEC), collocated National Fiber Optic Engineers Conference, 2010, pp. 1–3.
- [114] J. Knab and et al, "Ultrafast carrier dynamics and optical properties of nanoporous silicon at terahertz frequencies," *Optical Materials Express*, vol. 4, no. 2, pp. 300–307, February 2014.
- [115] R. Weerasuriya and et al, "Generation of frequency symetric signals from a bpsk input for phase sensitive amplification," OSA/OFC/NFOEC, 2010.
- [116] J. W. Goodman, "Delta function and fourier transform theorems," in Introduction to Fourier Optics. Viva Books Private Limited, 2007, pp. 433–435.
- [117] I. J. Nagrath and et al, "Discrete fourier transformation and fast fourier transformation," in *Signals and Systems*. McGraw- Hill, 2003, pp. 260– 273.

- [118] C. T. Chen, in Signals and Systems, Third Edition. Oxford University Press, 2004, pp. 116–190.
- [119] L. .Richter and et al, "Linewidth determination from self-heterodyne measurements with subcoherence delay time," *IEEE Journal of Quantum Electronics*, vol. QE-22, no. 11, pp. 2070–2074, November 1986.
- [120] A. Altuncu and A. Cokrak, "Gain and noise figure performance of erbium doped fiber amplifiers(edfa)," *Journal of Electrical and Electronics Engineering*, vol. 04, no. 02, pp. 1111–1122, 2004.
- [121] "Erbium-doped fiber amplifiers," https://www.rp-photonics.com/erbium_ doped_fiber_amplifiers.html, accessed: 2020-11-05.
- [122] R. Hui, "Optical amplifiers," in Introduction to Fiber Optic Communication. Elsevier, 2019, pp. 179–190.
- [123] E. Desurvire, in *Erbium Doped Fiber Amplifiers:Principles and Application*. Wiley Publication, 2002.
- [124] A. Ghatak and K. Thyagarajan, "Optical fiber amplifiers," in *Introduction to Fiber Optics*. Cambridge University Press, 1998, pp. 281–315.
- [125] S. Ryu, "Signal linewidth broadening due to nonlinear kerr effect in longhaul coherent system using cascaded optical amplifier," *Journal of Light*wave technology, no. 10, pp. 1450 – 1457, 1992.
- [126] J. P. Gordon and L. F. Mollenauer, "Phase noise in photonic communications systems using linear amplifiers," *Optics Letters*, vol. 15, no. 23, pp. 1351–1353, 1990.
- [127] G. J. Cowle and et al, "Spectral broadening due to fibre amplifier phase noise," *Electronics Letters*, vol. 26, no. 7, pp. 424–425, 1990.
- [128] E. Desurvire, "Erbium doped fiber amplifiers." A John Wiley & Sons, Inc., New York, 1993, pp. 399–404.
- [129] A. Yariv, in Optical Electronics (3rd edn). Reinhart and Winston, New York, 1985.
- [130] B. Wang and et al, "Millimeter-resolution long-range ofdr using ultralinearly 100 ghz-swept optical source realized by injection-locking technique and cascaded fwm process," *Optics Express*, February 2017.

[131] R.Weerasuriya and et al, "Comparison of frequency symmetric signal generation from a bpsk input using fiber and semiconductor-based nonlinear elements," *IEEE Photonics Technology Letters*, vol. 23, no. 10, pp. 651–653, 2011.