

REFERENCE LIST

- [1] H.K. Ekanayake, “Methodology to limit inrush current of toroidal transformers”, Charted Engineering IESL Sri Lanka, 2012
- [2] Rasim Dogan, Saeed Jazebi, ”Investigation of Transformer-Based Solutions for the Reduction of Inrush and Phase-Hop Currents”, IEEE Transactions on Power Electronics, Vol. 31, Iss 5, pp 3506 – 3516, July 2015
- [3] Francisco de L, Brian G, “Transformer Based Solutions to Power Quality Problems”, Plitron Manufacturing Inc. Canada, 2001
- [4] KAWASAKI STEEL CORPORATION, “PLASMA CORE RGHPJ RGH AND RG CORE”, Grain-Oriented Magnetic Steel Strip, Japan: 1991.
- [5] Colonel MW, T. Mclyman, “Transformer and inductor design handbook”, Third Edition, Kg Magnetics, Inc. California, USA, 2004, pp. 96-100
- [6] Saeed Jazebi, Nicholas Wu, “Enhanced analytical method for the calculation of the maximum inrush current of single phase power transformer”, IEEE Transactions on Power Delivery, Vol. 30, Iss 6, pp 2590 - 2599, June 2015
- [7] Yunfei Wang, Sami G., “Analytical formula to estimate the maximum inrush current”, IEEE Translations on Power Delivery, Vol. 23, No 2, pp 1266 - 1268, April 2008