

## REFERENCES

- [1] A. Ölander, “An Electrochemical Investigation of Solid Cadmium-Gold Alloys,” *J. Am. Chem. Soc.*, vol. 54, no. 10, pp. 3819–3833, Oct. 1932, doi: 10.1021/ja01349a004.
- [2] G. V. Kurdyumov and L. G. Khandros, “On the ‘Thermoelastic’ Equilibrium on Martensitic Transformations,” *Ukr J Phys 2008*, vol. 53, no. Special Issue, pp. 211–214, 1949.
- [3] W. J. Buehler, J. V. Gilfrich, and R. C. Wiley, “Effect of Low-Temperature Phase Changes on the Mechanical Properties of Alloys near Composition TiNi,” *J. Appl. Phys.*, vol. 34, no. 5, pp. 1475–1477, May 1963, doi: 10.1063/1.1729603.
- [4] G. B. Kauffman and I. Mayo, “The Story of Nitinol: The Serendipitous Discovery of the Memory Metal and Its Applications,” *Chem. Educ.*, vol. 2, no. 2, pp. 1–21, Jun. 1997, doi: 10.1007/s00897970111a.
- [5] W. J. Buehler and F. E. Wang, “A summary of recent research on the nitinol alloys and their potential application in ocean engineering,” *Ocean Eng.*, vol. 1, no. 1, pp. 105–120, Jul. 1968, doi: 10.1016/0029-8018(68)90019-X.
- [6] J. Mohd Jani, M. Leary, A. Subic, and M. A. Gibson, “A review of shape memory alloy research, applications and opportunities,” *Mater. Des. 1980-2015*, vol. 56, pp. 1078–1113, Apr. 2014, doi: 10.1016/j.matdes.2013.11.084.
- [7] Y. Liu and Z. Xie, “Detwinning of Shape Memory Alloy,” in *Progress in Smart Materials and Structures*, Nova Publishers, 2007, pp. 29–65.
- [8] B. Amin-Ahmadi, R. D. Noebe, and A. P. Stebner, “Crack propagation mechanisms of an aged nickel-titanium-hafnium shape memory alloy,” *Scr. Mater.*, vol. 159, pp. 85–88, Jan. 2019, doi: 10.1016/j.scriptamat.2018.09.019.
- [9] D. T.W., M. K.N., S. D, and W. C.M., *Engineering Aspects of Shape Memory Alloys*. Butterworth-Heinemann, 1990. doi: 10.1016/C2013-0-04566-5.
- [10] D. C. Lagoudas, Ed., *Shape Memory Alloys: Modeling and Engineering Applications*, 1st ed. Springer US, 2008. Accessed: May 07, 2019. [Online]. Available: <https://www.springer.com/gp/book/9780387476841>
- [11] Y. Liu, Z. Xie, J. Van Humbeeck, and L. Delaey, “Asymmetry of stress-strain curves under tension and compression for NiTi shape memory alloys,” *Acta*

- Mater.*, vol. 46, no. 12, pp. 4325–4338, Jul. 1998, doi: 10.1016/S1359-6454(98)00112-8.
- [12] J. A. Shaw, “A thermomechanical model for a 1-D shape memory alloy wire with propagating instabilities,” 2002. doi: 10.1016/s0020-7683(01)00242-6.
- [13] “Shape Memory Alloys/Nitinol Melting and Materials.” <https://www.saesgetters.com/products-functions/products/shape-memory-alloys/shape-memory-alloys-melting-and-materials> (accessed Oct. 24, 2019).
- [14] M. H. Wu, “Fabrication of Nitinol Materials and Components,” 2002. doi: 10.4028/www.scientific.net/MSF.394-395.285.
- [15] G. S. Mammano and E. Dragoni, “Functional fatigue of NiTi Shape Memory wires for a range of end loadings and constraints,” *Frat. Ed Integrità Strutt.*, vol. 7, no. 23, Art. no. 23, 2013, doi: 10.3221/IGF-ESIS.23.03.
- [16] G. Eggeler, E. Hornbogen, A. Yawny, A. Heckmann, and M. Wagner, “Structural and functional fatigue of NiTi shape memory alloys,” *Mater. Sci. Eng. A*, vol. 378, 2004, [Online]. Available: <http://linkinghub.elsevier.com/retrieve/pii/S0921509303015144>
- [17] T. W. Duerig, “Applications of Shape Memory,” *Mater. Sci. Forum*, vol. 56–58, pp. 679–692, 1990.
- [18] M. Sreekumar, T. Nagarajan, M. Singaperumal, M. Zoppi, and R. Molfino, “Critical review of current trends in shape memory alloy actuators for intelligent robots,” *Ind Robot*, 2007, doi: 10.1108/01439910710749609.
- [19] J. Colorado, A. Barrientos, C. Rossi, and K. S. Breuer, “Biomechanics of smart wings in a bat robot: morphing wings using SMA actuators,” *Bioinspir. Biomim.*, vol. 7, no. 3, p. 036006, Apr. 2012, doi: 10.1088/1748-3182/7/3/036006.
- [20] T. Duerig, A. Pelton, and D. Stöckel, “An overview of nitinol medical applications,” *Mater. Sci. Eng. A*, vol. 273–275, pp. 149–160, Dec. 1999, doi: 10.1016/S0921-5093(99)00294-4.
- [21] N. B. Morgan and M. Broadley, “Taking the Art out of Smart! - Forming Processes and Durability Issues for the Application of Niti Shape Memory Alloys in Medical Devices - International Metallographic Society,” Anaheim, California, Sep. 2003, vol. 2004. Accessed: May 17, 2020. [Online]. Available:

[https://www.asminternational.org/web/ims/news/amp/-/journal\\_content/56/10192/CP2003MPMD247/CONFERENCE-PAPER](https://www.asminternational.org/web/ims/news/amp/-/journal_content/56/10192/CP2003MPMD247/CONFERENCE-PAPER)

- [22] F04 Committee, “Standard Test Method for Transformation Temperature of Nickel-Titanium Alloys by Thermal Analysis,” ASTM International. doi: 10.1520/F2004-05R10.
- [23] TA Instruments, “Differential Scanning Calorimetry (DSC) Basic Theory & Applications Training,” presented at the DSC Training Course, 2009.
- [24] “Differential Scanning Calorimeters,” TA Instruments.  
<https://www.tainstruments.com/products/thermal-analysis/differential-scanning-calorimeters/> (accessed May 20, 2020).
- [25] E. Abel, H. Luo, M. Pridham, and A. Slade, “Issues concerning the measurement of transformation temperatures of NiTi alloys,” *Smart Mater. Struct.*, vol. 13, no. 5, p. 1110, 2004, doi: 10.1088/0964-1726/13/5/016.
- [26] N. Ma, G. Song, and H.-J. Lee, “Position control of shape memory alloy actuators with internal electrical resistance feedback using neural networks,” *Smart Mater. Struct.*, vol. 13, no. 4, pp. 777–783, 2004, doi: 10.1088/0964-1726/13/4/015.
- [27] G. Song, V. Chaudhry, and C. Batur, “Precision tracking control of shape memory alloy actuators using neural networks and a sliding-mode based robust controller,” *Smart Mater. Struct.*, vol. 12, no. 2, pp. 223–231, 2003, doi: 10.1088/0964-1726/12/2/310.
- [28] K. Ikuta, M. Tsukamoto, and S. Hirose, “Shape memory alloy servo actuator system with electric resistance feedback and application for active endoscope,” in *1988 IEEE International Conference on Robotics and Automation Proceedings*, Apr. 1988, pp. 427–430 vol.1. doi: 10.1109/ROBOT.1988.12085.
- [29] S. Yan, X. Liu, F. Xu, and J. Wang, “A Gripper Actuated by a Pair of Differential SMA Springs;,” *J. Intell. Mater. Syst. Struct.*, Dec. 2006, doi: 10.1177/1045389X06067110.
- [30] G. Stiff, M. Rhodes, A. Kelly, K. Telford, C. P. Armstrong, and B. I. Rees, “Long-term pain: Less common after laparoscopic than open cholecystectomy,” *Br. J. Surg.*, vol. 81, no. 9, pp. 1368–1370, Sep. 1994, doi: 10.1002/bjs.1800810939.

- [31] “Minimally invasive Cardiac surgery(MICS) | Dr Manoj Pradhan.” <http://drmanojpradhan.com/minimally-invasive-cardiac-surgerymics> (accessed May 16, 2017).
- [32] “Minimally Invasive Neurosurgery.” <https://www.beaumont.org/treatments/minimally-invasive-neurosurgery> (accessed May 16, 2017).
- [33] F. Tendick, S. S. Sastry, R. S. Fearing, and M. Cohn, “Applications of micromechatronics in minimally invasive surgery,” *IEEEASME Trans. Mechatron.*, vol. 3, no. 1, pp. 34–42, Mar. 1998, doi: 10.1109/3516.662866.
- [34] R. H. Petersen, “Video-assisted thoracoscopic thymectomy using 5-mm ports and carbon dioxide insufflation,” *Ann. Cardiothorac. Surg.*, vol. 5, no. 1, pp. 51–55, Jan. 2016, doi: 10.3978/9055.
- [35] “Minimally Invasive Neurosurgery.” [https://safemedtrip.com/wp-content/uploads/2013/04/Minimally\\_Invasive\\_Neurosurgery.jpg](https://safemedtrip.com/wp-content/uploads/2013/04/Minimally_Invasive_Neurosurgery.jpg) (accessed Dec. 07, 2021).
- [36] “Surgeons Performing Functional Endoscopic Sinus Surgery.” <https://c8.alamy.com/comp/H238P1/sinus-surgery-surgeons-performing-functional-endoscopic-sinus-surgery-H238P1.jpg> (accessed Dec. 07, 2021).
- [37] M. C. Carrozza, P. Dario, and L. P. S. Jay, “Micromechatronics in surgery,” *Trans. Inst. Meas. Control*, Jul. 2016, doi: 10.1191/0142331203tm089oa.
- [38] T. G. Frank, G. B. Hanna, and A. Cuschieri, “Technological aspects of minimal access surgery,” *Proc. Inst. Mech. Eng. [H]*, vol. 211, no. 2, pp. 129–144, 1997, doi: 10.1243/0954411971534250.
- [39] J. Catherine, C. Rotinat-Libersa, and A. Micaelli, “Comparative review of endoscopic devices articulations technologies developed for minimally invasive medical procedures,” *Appl. Bionics Biomech.*, vol. 8, no. 2, pp. 151–171, 2011, doi: 10.3233/ABB-2011-0018.
- [40] J. Ryhänen *et al.*, “Biocompatibility of nickel-titanium shape memory metal and its corrosion behavior in human cell cultures,” *J. Biomed. Mater. Res.*, vol. 35, no. 4, pp. 451–457, Jun. 1997, doi: 10.1002/(sici)1097-4636(19970615)35:4<451::aid-jbm5>3.0.co;2-g.

- [41] F04 Committee, “Standard Specification for Wrought Nickel-Titanium Shape Memory Alloys for Medical Devices and Surgical Implants,” ASTM International. doi: 10.1520/F2063-05.
- [42] P. Mucksavage, D. C. Kerbl, D. L. Pick, J. Y. Lee, E. M. McDougall, and M. K. Louie, “Differences in grip forces among various robotic instruments and da vinci surgical platforms,” *J. Endourol.*, vol. 25, no. 3, pp. 523–528, 2011, doi: 10.1089/end.2010.0306.
- [43] A. K. Morimoto *et al.*, “Force sensor for laparoscopic Babcock,” *Stud. Health Technol. Inform.*, vol. 39, pp. 354–361, 1997.
- [44] I. Brouwer, J. Ustin, L. Bentley, A. Sherman, N. Dhruv, and F. Tendick, “Measuring in vivo animal soft tissue properties for haptic modeling in surgical simulation,” *Stud. Health Technol. Inform.*, vol. 81, pp. 69–74, 2001.
- [45] S. Greenish, V. Hayward, V. Chial, A. Okamura, and T. Steffen, “Measurement, Analysis, and Display of Haptic Signals During Surgical Cutting,” *Presence Teleoper Virtual Env.*, vol. 11, no. 6, pp. 626–651, Dec. 2002, doi: 10.1162/105474602321050749.
- [46] S. P. Rodrigues, T. Horeman, J. Dankelman, J. J. van den Dobbelsteen, and F.-W. Jansen, “Suturing intraabdominal organs: when do we cause tissue damage?,” *Surg. Endosc.*, vol. 26, no. 4, pp. 1005–1009, Apr. 2012, doi: 10.1007/s00464-011-1986-5.
- [47] J. J. van den Dobbelsteen, A. Schooleman, and J. Dankelman, “Friction dynamics of trocars,” *Surg. Endosc.*, vol. 21, no. 8, pp. 1338–1343, Aug. 2007, doi: 10.1007/s00464-006-9105-8.
- [48] P. Puangmali, K. Althoefer, L. D. Seneviratne, D. Murphy, and P. Dasgupta, “State-of-the-Art in Force and Tactile Sensing for Minimally Invasive Surgery,” *IEEE Sens. J.*, vol. 8, no. 4, pp. 371–381, Apr. 2008, doi: 10.1109/JSEN.2008.917481.
- [49] D. Mantovani, “Shape memory alloys: Properties and biomedical applications,” *JOM*, vol. 52, no. 10, pp. 36–44, Oct. 2000, doi: 10.1007/s11837-000-0082-4.
- [50] “Memry, a SAES Group Company | From Melt to Market.” <http://memry.com/> (accessed May 28, 2017).

- [51] J. J. B. Lim and A. G. Erdman, “A review of mechanism used in laparoscopic surgical instruments,” *Mech. Mach. Theory*, vol. 38, no. 11, pp. 1133–1147, Nov. 2003, doi: 10.1016/S0094-114X(03)00063-6.
- [52] C. Song, “History and Current Situation of Shape Memory Alloys Devices for Minimally Invasive Surgery,” *Open Med. Devices J.*, vol. 2, no. 1, Jan. 2010, Accessed: May 28, 2017. [Online]. Available: <https://benthamopen.com/ABSTRACT/TOMDJ-2-24>
- [53] S. J. Phee *et al.*, “Robot-assisted endoscopic submucosal dissection is effective in treating patients with early-stage gastric neoplasia,” *Clin. Gastroenterol. Hepatol. Off. Clin. Pract. J. Am. Gastroenterol. Assoc.*, vol. 10, no. 10, pp. 1117–1121, Oct. 2012, doi: 10.1016/j.cgh.2012.05.019.
- [54] S. Akbari and H. R. Shea, “An array of  $100 \mu\text{m} \times 100 \mu\text{m}$  dielectric elastomer actuators with 80% strain for tissue engineering applications,” *Sens. Actuators Phys.*, vol. 186, pp. 236–241, Oct. 2012, doi: 10.1016/j.sna.2012.01.030.
- [55] R. Pelrine, R. Kornbluh, Q. Pei, and J. Joseph, “High-Speed Electrically Actuated Elastomers with Strain Greater Than 100%,” *Science*, vol. 287, no. 5454, pp. 836–839, Feb. 2000, doi: 10.1126/science.287.5454.836.
- [56] P. Garstecki, P. Tierno, D. B. Weibel, F. Sagués, and G. M. Whitesides, “Propulsion of flexible polymer structures in a rotating magnetic field,” *J. Phys. Condens. Matter*, vol. 21, no. 20, p. 204110, 2009, doi: 10.1088/0953-8984/21/20/204110.
- [57] J. Paek, I. Cho, and J. Kim, “Microrobotic tentacles with spiral bending capability based on shape-engineered elastomeric microtubes,” *Sci. Rep.*, vol. 5, Jun. 2015, doi: 10.1038/srep10768.
- [58] A. AbuZaiter and M. S. M. Ali, “Analysis of Thermomechanical Behavior of Shape-Memory-Alloy Bimorph Microactuator,” in *Modelling and Simulation 2014 5th International Conference on Intelligent Systems*, Jan. 2014, pp. 390–393. doi: 10.1109/ISMS.2014.72.
- [59] A. D. Donno, L. Zorn, P. Zanne, F. Nageotte, and M. de Mathelin, “Introducing STRAS: A new flexible robotic system for minimally invasive surgery,” in *2013 IEEE International Conference on Robotics and Automation*, May 2013, pp. 1213–1220. doi: 10.1109/ICRA.2013.6630726.

- [60] P. Berkelman and J. Ma, “A Compact Modular Teleoperated Robotic System for Laparoscopic Surgery,” *Int. J. Robot. Res.*, vol. 28, no. 9, pp. 1198–1215, Sep. 2009, doi: 10.1177/0278364909104276.
- [61] J. H. Crews and G. D. Buckner, “Design optimization of a shape memory alloy–actuated robotic catheter,” *J. Intell. Mater. Syst. Struct.*, vol. 23, no. 5, pp. 545–562, Mar. 2012, doi: 10.1177/1045389X12436738.
- [62] T. G. Frank, W. Xu, and A. Cuschieri, “Instruments based on shape-memory alloy properties for minimal access surgery, interventional radiology and flexible endoscopy,” *Minim. Invasive Ther. Allied Technol.*, vol. 9, no. 2, pp. 89–98, Jan. 2000, doi: 10.3109/13645700009063055.
- [63] L. Petrini and F. Migliavacca, “Biomedical Applications of Shape Memory Alloys,” *J. Metall.*, vol. 2011, p. e501483, May 2011, doi: 10.1155/2011/501483.
- [64] T. Bradly, W. Brantley, and B. Culbertson, “Differential scanning calorimetry (DSC) analyses of superelastic and nonsuperelastic nickel-titanium orthodontic wires.,” *Am. J. Orthod. Dentofac. Orthop. Off. Publ. Am. Assoc. Orthod. Its Const. Soc. Am. Board Orthod.*, vol. 109, no. 6, pp. 589–97, Jun. 1996.
- [65] J. A. Shaw, C. B. Churchill, and M. A. Iadicola, “Tips and Tricks for Characterizing Shape Memory Alloy Wire: Part 1—Differential Scanning Calorimetry and Basic Phenomena,” *Exp. Tech.*, vol. 32, no. 5, pp. 55–62, 2008, doi: 10.1111/j.1747-1567.2008.00410.x.
- [66] M. F.-X. Wagner, S. R. Dey, H. Gugel, J. Frenzel, Ch. Somsen, and G. Eggeler, “Effect of low-temperature precipitation on the transformation characteristics of Ni-rich NiTi shape memory alloys during thermal cycling,” *Intermetallics*, vol. 18, no. 6, pp. 1172–1179, Jun. 2010, doi: 10.1016/j.intermet.2010.02.048.
- [67] T. Duerig, “The metallurgy of Nitinol as it pertains to medical devices - ScienceDirect,” in *Titanium in Medical and Dental Applications*, Woodhead Publishing, 2018, pp. 555–570. Accessed: Feb. 17, 2019. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/B9780128124567000251>
- [68] R. J. Wasilewski, S. R. Butler, J. E. Hanlon, and D. Worden, “Homogeneity range and the martensitic transformation in TiNi,” *Metall. Mater. Trans.*, vol. 2, no. 1, pp. 229–238, Dec. 1971.

- [69] M. R. da Silva *et al.*, “Microstructural Characterization of a Laser Surface Remelted Cu-Based Shape Memory Alloy,” *Mater. Res.*, vol. 21, no. 3, 2018, doi: 10.1590/1980-5373-mr-2017-1044.
- [70] Y. Zheng, F. Jiang, L. J. Li, X. Yang, and Y. Liu, “Effect of ageing treatment on the transformation behaviour of Ti50.9 at.% Ni alloy,” 2008. doi: 10.1016/j.actamat.2007.10.020.
- [71] W. Huang, “On the selection of shape memory alloys for actuators,” *Mater. Des.*, vol. 23, no. 1, pp. 11–19, Feb. 2002, doi: 10.1016/S0261-3069(01)00039-5.
- [72] “Printinciple, Types and Structure of Strain Gage | KYOWA.” [https://www.kyowa-ei.com/eng/technical/strain\\_gages/principles.html](https://www.kyowa-ei.com/eng/technical/strain_gages/principles.html) (accessed May 28, 2020).
- [73] E. rite, “Strain Gauge: Principle, Types, Features and Applications,” *Medium*, Jul. 04, 2019. <https://medium.com/@encardio/strain-gauge-principle-types-features-and-applications-357f6fed86a5> (accessed May 28, 2020).
- [74] K. H. Ang, G. Chong, and Y. Li, “PID control system analysis, design, and technology,” *IEEE Trans. Control Syst. Technol.*, vol. 13, no. 4, pp. 559–576, Jul. 2005, doi: 10.1109/TCST.2005.847331.
- [75] A. Spaggiari, I. Spinella, and E. Dragoni, “Design equations for binary shape memory actuators under arbitrary external forces,” *J. Intell. Mater. Syst. Struct.*, vol. 24, no. 6, pp. 682–694, Apr. 2013, doi: 10.1177/1045389X12444491.
- [76] “SimMechanics 2 User’s Guide.” MathWorks, Inc., 2007.