

REFERENCES

- [1] "Statics World Production and Consumption of Ceramic Tiles.", Association of Italian Manufactures of Machinery and Equipment for ceramic, 2015.
- [2] E. V. Romera, F. Xavier and M. Morales, "CURRENT AND FUTURE CHALLENGES OF THE CERAMIC TILE FIRMS (The case of the INKJET technological innovation) Final Year Project (6 credits)".
- [3] Hassanein A. Refaey , E. Specht , M.R.Salem, 'Influence of fuel distribution and heat transfer on energy consumption in tunnel kilns' , *International Journal of Advances in Engineering & Technology*, June, 2015
- [4] S.H. Jazayeri, A. salem, G. timellini, E. rastelli, 'A kinetic study on the development of porosity in porcelain stoneware tile sintering' , *Bol. Soc. Esp. Ceram*, V., 46 [1] 1-6 (2007)
- [5] M. Romero and J. M. Pérez, "Relation between the microstructure and technological properties of porcelain stoneware. A review," *Materiales de Construcción*, vol. 65, no. 320, p. e065, Oct. 2015, doi: <https://doi.org/10.3989/mc.2015.05915>.
- [6] J. Martín-Márquez, J. Ma. Rincón, and M. Romero, "Effect of firing temperature on sintering of porcelain stoneware tiles," *Ceramics International*, vol. 34, no. 8, pp. 1867–1873, Dec. 2008, doi: <https://doi.org/10.1016/j.ceramint.2007.06.006>.
- [7] J. L. Amorós, M. J. Orts, J. García-Ten, A. Gozalbo, and E. Sánchez, "Effect of the green porous texture on porcelain tile properties," *Journal of the European Ceramic Society*, vol. 27, no. 5, pp. 2295–2301, Jan. 2007, doi: <https://doi.org/10.1016/j.jeurceramsoc.2006.07.005>.
- [8] J. M. Pérez and M. Romero, "Microstructure and technological properties of porcelain stoneware tiles moulded at different pressures and thicknesses," *Ceramics International*, vol. 40, no. 1, pp. 1365–1377, Jan. 2014, doi: <https://doi.org/10.1016/j.ceramint.2013.07.018>.
- [9] K. E. Atcholi, E. Padayodi, J. C. Sagot, T. Beda, O. Samah, and J. Vantomme, "Thermo-mechanical behaviour of the structures of tropical clays from Togo (West Africa) fired at 500 °c, 850 °c and 1060 °c," *Construction and Building Materials*, vol. 27, no. 1, pp. 141–148, Feb. 2012, doi: [10.1016/j.conbuildmat.2011.08.009](https://doi.org/10.1016/j.conbuildmat.2011.08.009).
- [10] G. C. Stangle and I. A. Aksay, "Simultaneous momentum, heat and mass transfer with chemical reaction in a disordered porous medium: application to binder removal from a ceramic green body," *Chemical Engineering Science*, vol. 45, no. 7, pp. 1719–1731, Jan. 1990, doi: [https://doi.org/10.1016/0009-2509\(90\)87050-3](https://doi.org/10.1016/0009-2509(90)87050-3).
- [11] K. Murugesan, K. N. Seetharamu, and A. Narayana, "A one dimensional analysis of convective drying of porous materials," *Heat and mass transfer*, vol. 32, no. 1–2, pp. 81–88, Nov. 1996, doi: <https://doi.org/10.1007/s002310050095>.
- [12] S. Messai, J. Sghaier, D. Lecomte, and A. Belghith, "Drying Kinetics of a Porous Spherical Particle and the Inversion Temperature," *Drying Technology*, vol. 26, no. 2, pp. 157–167, Jan. 2008, doi: <https://doi.org/10.1080/07373930701831127>.
- [13] H. Suresh, K. Murugesan, P. Narayana, and K. Seetharamu, "DRYING OF POROUS MATERIAL USING FINITE ELEMENT METHOD," presented at the Second International Conference on CFD in the Minerals and process Industries, 1999. Accessed: Jun. 08, 2024. [Online]. Available: https://www.cfd.com.au/cfd_conf99/Conf99_Papers/008SURE.PDF
- [14] K. Khalili, M. Bagherian, and S. Khisheh, "Numerical Simulation of Drying Ceramic Using Finite Element and Machine Vision," *Procedia technology*, vol. 12, pp. 388–393, Jan. 2014, doi: <https://doi.org/10.1016/j.protcy.2013.12.504>.
- [15] J. C. Jarque, C. Segarra, V. Cantavella, and R. Mondragón, "Non-isothermal modeling of drying kinetics of ceramic tiles," *Drying Technology*, vol. 34, no. 7, pp. 761–772, Aug. 2015, doi: <https://doi.org/10.1080/07373937.2015.1076837>.
- [16] A.-D. la, A.M. Guzmán, C. Gómez-Rodríguez, D.I. Martínez, and N. Elizondo, "Influence of Al₂O₃ and SiO₂ nanoparticles addition on the microstructure and mechano-physical properties of ceramic tiles," *Ceramics International*, vol. 48, no. 9, pp. 12712–12720, May 2022, doi: <https://doi.org/10.1016/j.ceramint.2022.01.140>.

- [17] F. Güngör and N. Ay, "The effect of particle size of body components on the processing parameters of semi transparent porcelain," *Ceramics International*, vol. 44, no. 9, pp. 10611–10620, Jun. 2018, doi: <https://doi.org/10.1016/j.ceramint.2018.03.086>.
- [18] A. J. Souza, A. Pinheiro, and F. Hol, "Sintering Behavior of Vitrified Ceramic Tiles Incorporated with Petroleum Waste," *InTech eBooks*, Feb. 2013, doi: <https://doi.org/10.5772/53256>.
- [19] D. Antal, Tomáš Hulan, Igor Štubňa, M. Záleská, and A. Trník, "The influence of texture on elastic and thermophysical properties of kaolin- and illite-based ceramic bodies," *Ceramics International*, vol. 43, no. 2, pp. 2730–2736, Feb. 2017, doi: <https://doi.org/10.1016/j.ceramint.2016.11.100>.
- [20] Kornelia Wiśniewska, Waldemar Pichór, and E. Kłosek-Wawrzyn, "Impact of the addition of dolomite to cream-firing clays on the technological and color properties of sintered ceramics," *International Journal of Applied Ceramic Technology*, vol. 18, no. 3, pp. 1063–1073, Feb. 2021, doi: <https://doi.org/10.1111/ijac.13719>.
- [21] M. Dal Bó, L. Dominguni, A. Zimmer, S. R. Grando, P. Kaspari, and D. Hotza, "Chemical tempering of porcelain tiles," *Ceramics International*, vol. 42, no. 14, pp. 15199–15202, Nov. 2016, doi: <https://doi.org/10.1016/j.ceramint.2016.06.138>.
- [22] J. García Ten, M. J. Orts, A. Saburit, and G. Silva, "Thermal conductivity of traditional ceramics. Part I: Influence of bulk density and firing temperature," *Ceramics International*, vol. 36, no. 6, pp. 1951–1959, Aug. 2010, doi: <https://doi.org/10.1016/j.ceramint.2010.05.012>.
- [23] C. Zanelli, M. Raimondo, G. Guarini, and M. Dondi, "The vitreous phase of porcelain stoneware: Composition, evolution during sintering and physical properties," *Journal of Non-Crystalline Solids*, vol. 357, no. 16–17, pp. 3251–3260, Aug. 2011, doi: [10.1016/j.jnoncrysol.2011.05.020](https://doi.org/10.1016/j.jnoncrysol.2011.05.020).
- [24] E. Garzón, L. Pérez-Villarejo, D. Eliche-Quesada, S. Martínez-Martínez, and P. J. Sánchez-Soto, "Vitrification rate and estimation of the optimum firing conditions of ceramic materials from raw clays: A review," *Ceramics International*, vol. 48, no. 11, pp. 15889–15898, Jun. 2022, doi: [10.1016/j.ceramint.2022.02.129](https://doi.org/10.1016/j.ceramint.2022.02.129).
- [25] Abdelaziz Elgamouz, Najib Tijani, I. Shehadi, Md. Kamrul Hasan, and Mohamad Al-Farooq Kawam, "Characterization of the firing behaviour of an illite-kaolinite clay mineral and its potential use as membrane support," *Heliyon*, vol. 5, no. 8, pp. e02281–e02281, Aug. 2019, doi: <https://doi.org/10.1016/j.heliyon.2019.e02281>.
- [26] S. A. T. Redfern, "The kinetics of dehydroxylation of kaolinite," *Clay Minerals*, vol. 22, no. 4, pp. 447–456, Dec. 1987, doi: <https://doi.org/10.1180/claymin.1987.022.4.08>.
- [27] D. V. Andreev and A. I. Zakharov, "Ceramic item deformation during firing: effects of composition and microstructure (review)," *Refract Ind Ceram*, vol. 50, no. 4, pp. 298–303, Jul. 2009, doi: [10.1007/s11148-009-9191-y](https://doi.org/10.1007/s11148-009-9191-y).
- [28] M. J. Orts, J.L. Amorós, A. Escardino, A. Gozalbo, and C. Feliu, "Kinetic model for the isothermal sintering of low porosity floor tiles," *Applied Clay Science*, vol. 8, no. 2–3, pp. 231–245, Aug. 1993, doi: [https://doi.org/10.1016/0169-1317\(93\)90040-8](https://doi.org/10.1016/0169-1317(93)90040-8).
- [29] M. J. Orts, A. Escardino, J. L. Amorós, and F. Negre, "Microstructural changes during the firing of stoneware floor tiles," *Applied Clay Science*, vol. 8, no. 2–3, pp. 193–205, Aug. 1993, doi: [https://doi.org/10.1016/0169-1317\(93\)90037-2](https://doi.org/10.1016/0169-1317(93)90037-2).
- [30] W. Zeng, L. Gao, L. Gui, and J. Guo, "Sintering kinetics of α -Al₂O₃ powder," *Ceramics International*, vol. 25, no. 8, pp. 723–726, Dec. 1999, doi: [https://doi.org/10.1016/S0272-8842\(99\)00008-5](https://doi.org/10.1016/S0272-8842(99)00008-5).
- [31] S. Yürüyen and H. Ö. Toplan, "The sintering kinetics of porcelain bodies made from waste glass and fly ash," *Ceramics International*, vol. 35, no. 6, pp. 2427–2433, Aug. 2009, doi: <https://doi.org/10.1016/j.ceramint.2009.02.005>.
- [32] A. Salem, S. H. Jazayeri, E. Rastelli, and G. Timellini, "Dilatometric study of shrinkage during sintering process for porcelain stoneware body in presence of nepheline syenite," *Journal of Materials Processing Technology*, vol. 209, no. 3, pp. 1240–1246, Feb. 2009, doi: <https://doi.org/10.1016/j.jmatprotec.2008.03.033>.

- [33] A. Salem, S. H. Jazayeri, E. Rastelli, and G. Timellini, "Kinetic model for isothermal sintering of porcelain stoneware body in presence of nepheline syenite," *Thermochimica Acta*, vol. 503–504, pp. 1–7, May 2010, doi: <https://doi.org/10.1016/j.tca.2010.01.024>.
- [34] M. Cargnin, S. M. A. G. Ulson de Souza, A. A. Ulson de Souza, and A. De Noni Jr., "MODELING AND SIMULATION OF THE EFFECT OF THE FIRING CURVE ON THE LINEAR SHRINKAGE OF CERAMIC MATERIALS: LABORATORY SCALE AND INDUSTRIAL SCALE," *Brazilian Journal of Chemical Engineering*, vol. 32, no. 2, pp. 433–443, Jun. 2015, doi: 10.1590/0104-6632.20150322s00002876.
- [35] S. Conte, C. Zanelli, M. Ardit, G. Cruciani, and M. Dondi, "Predicting Viscosity and Surface Tension at High Temperature of Porcelain Stoneware Bodies: A Methodological Approach," *Materials*, vol. 11, no. 12, p. 2475, Dec. 2018, doi: <https://doi.org/10.3390/ma11122475>.
- [36] Igor Stubna, A. Trnik, F. Chmelik, and L. Vozar, "Mechanical Properties of Kaolin-Base Ceramics During Firing," *InTech eBooks*, Aug. 2011, doi: <https://doi.org/10.5772/19199>.
- [37] J. M. N. Jayaweera, M. Narayana, and S. U. Adikary, "Numerical Modeling of Drying Behavior of Ceramic Tiles with High Silica Content of Kaolin," in *2023 Moratuwa Engineering Research Conference (MERCon)*, Moratuwa, Sri Lanka: IEEE, Nov. 2023, pp. 592–597. doi: <https://doi.org/10.1109/mercon60487.2023.10355459>.
- [38] J. M. N. Jayaweera, M. Narayana, and S. U. Adikary, "Effects of Kaolin with High Silica Content on Properties of Ceramic Tiles," in *2022 Moratuwa Engineering Research Conference (MERCon)*, Moratuwa, Sri Lanka: IEEE, Jul. 2022, pp. 1–6. doi: 10.1109/MERCon55799.2022.9906261.
- [39] H. A. Refaey, E. Specht, and M. R. Salem, "INFLUENCE OF FUEL DISTRIBUTION AND HEAT TRANSFER ON ENERGY CONSUMPTION IN TUNNEL KILNS," *International Journal of Advances in Engineering & Technology*, vol. 8, no. 3, Jun. 2015.
- [40] S. Ferrer, A. Mezquita, M. P. Gomez-Tena, C. Machi, and E. Monfort, "Estimation of the heat of reaction in traditional ceramic compositions," *Applied Clay Science*, vol. 108, pp. 28–39, May 2015, doi: <https://doi.org/10.1016/j.clay.2015.02.019>.
- [41] H. K. Versteeg and W. Malalasekera, *An introduction to computational fluid dynamics : the finite volume method*. Harlow: Pearson Education, 2011.
- [42] F. Moukalled, L. Mangani, and M. Darwish, *The Finite Volume Method in Computational Fluid Dynamics An Advanced Introduction with OpenFOAM® and Matlab*. Cham: Springer International Publishing, 2016.
- [43] V. D. Thi, M. Li, M. Khelifa, M. El Ganaoui, and Y. Rogaume, "Finite Element Modeling of Heat and Moisture Transfer in Porous Material," *International Journal of Materials and Metallurgical Engineering*, vol. 11, no. 4, 2017.
- [44] Ante Sikirica, Luka Grbčić, M. Alvir, and Lado Kranjčević, "Computational Efficiency Assessment of Adaptive Mesh Refinement for Turbulent Jets in Crossflow," *Mathematics*, vol. 10, no. 4, pp. 620–620, Feb. 2022, doi: <https://doi.org/10.3390/math10040620>.
- [45] R. Mondragón, J. E. Juliá, L. Hernández, and J. C. Jarque, "Modeling of Drying Curves of Silica Nanofluid Droplets Dried in an Acoustic Levitator Using the Reaction Engineering Approach (REA) Model," *Drying Technology*, vol. 31, no. 4, pp. 439–451, Mar. 2013, doi: <https://doi.org/10.1080/07373937.2012.738753>.
- [46] C. Jung, J.-R. Kim, and S. Yi, "Two-dimensional simulation of silica gel drying using computational fluid dynamics," *Journal of Ceramic Processing Research*, vol. 9, no. 2, pp. 184–188, Apr. 2008, doi: <https://doi.org/10.36410/jcpr.2008.9.2.184>.
- [47] S. Mahmoudi, E. Srasra, and F. Zargouni, "SIMULTANEOUS OPTIMISATION OF DRYING PARAMETERS OF CERAMIC BODIES," *American Journal of Geoscience*, vol. 4, no. 1, pp. 1–7, Jan. 2014, doi: 10.3844/ajgsp.2014.1.7.
- [48] Lauro, N., Oummadi, S., Alzina, A., Nait-Ali, B., & Smith, D. S. (2021). Computer model of drying behaviour of ceramic green bodies with particular reference to moisture content dependent properties. *Journal of the European Ceramic Society*, 41(14), 7321–7329. doi:10.1016/j.jeurceramsoc.2021.0

- [49] G. MUSIELAK, T. SLIWA, and M. STASIAK, "NUMERICAL MODELLING OF EFFECTS OF THE DRYING RATE ON KAOLIN FRACTURING," CERAMIC MATERIALS, vol. 65, pp. 61–64, 2013.
- [50] J. Barbosa da Silva, G. S. Almeida, W. C. P. Barbosa de Lima, G. A. Neves, and A. G. B. de Lima, "Heat and Mass Diffusion Including Shrinkage and Hygrothermal Stress during Drying of Holed Ceramics Bricks," Defect and Diffusion Forum, vol. 312–315, pp. 971–976, Apr. 2011, doi: 10.4028/www.scientific.net/ddf.312-315.971.
- [51] M. Hassanein, A. Mohsen, and H. Refaey, "Mathematical Model to Analyze the Heat Transfer in Tunnel Kilns for Burning of Ceramics," 1978. Accessed: Dec. 14, 2023. [Online]. Available: <https://core.ac.uk/download/pdf/51448507.pdf>
- [52] H. Refaey, M. Karali, A. Al-Hasnawi, and E. Specht, "MATHEMATICAL MODEL TO SIMULATE THE HEAT TRANSFER IN VITRIFIED CLAY PIPES KILN," The International Conference on Applied Mechanics and Mechanical Engineering, vol. 18, no. 18, pp. 1–12, Apr. 2018, doi: 10.21608/amme.2018.34989.
- [53] S. Salem and A. Salem, "Mechanisms of Momentum Transport in Viscous Flow Sintering," Sintering Applications, Feb. 2013, doi: <https://doi.org/10.5772/53259>.
- [54] C. Zanelli, M. Raimondo?, M. Dondi, G. Guarini?, and P. Cavalcante", "SINTERING MECHANISMS OF PORCELAIN STONEWARE TILES," 2004. Accessed: Dec. 16, 2023. [Online]. Available: <https://www.qualicer.org/recopilatorio/ponencias/pdfs/0413191e.pdf>
- [55] Muhammad Shoaib Anwar, "Heat transfer in MHD convective stagnation point flow over a stretching surface with thermal radiations," Numerical heat transfer. Part A. Applications/Numerical heat transfer. Part A, Applications, pp. 1–16, Jan. 2024, doi: <https://doi.org/10.1080/10407782.2023.2299289>.
- [56] H. S. Ko, Y. H. Bae, and I. H. Cho, "DYNAMIC ANALYSIS OF A FLOATING STRUCTURE USING OPENFOAM," Journal of Computational Fluids Engineering, vol. 23, no. 1, pp. 101–112, Mar. 2018, doi: <https://doi.org/10.6112/ksce.2018.23.1.101>.
- [57] M. Gómez-Tena, J. Gilabert, J. Toledo, E. Zumaquero, and C. Machí, "CASTELLÓN (ESPAÑA) RELATIONSHIP BETWEEN THE SPECIFIC SURFACE AREA PARAMETERS DETERMINED USING DIFFERENT ANALYTICAL TECHNIQUES." Available: <https://www.qualicer.org/recopilatorio/ponencias/pdfs/56%20POSTER%20ING.pdf>
- [58] D. Llorens, "temperature Distribution inside a ceramic tile During industrial firing," 2006. Accessed: Dec. 14, 2022. [Online]. Available: <https://www.qualicer.org/recopilatorio/ponencias/pdfs/0062312e.pdf>
- [59] Ján Ondruška et al., "Thermophysical Properties of Kaolin–Zeolite Blends up to 1100 °C," Crystals, vol. 11, no. 2, pp. 165–165, Feb. 2021, doi: <https://doi.org/10.3390/cryst11020165>.
- [60] R.B. Bird, W.E. Stewart, E.N. Lightfoot, Transport Phenomena, second ed., 2002, <https://doi.org/10.1002/aic.690070245>.
- [61] S. Salem and A. Salem, "Mechanisms of Momentum Transport in Viscous Flow Sintering," Sintering Applications, Feb. 2013, doi: <https://doi.org/10.5772/53259>.
- [62] T. Húlan et al., "Young's Modulus of Different Illitic Clays during Heating and Cooling Stage of Firing," Materials, vol. 13, no. 21, p. 4968, Nov. 2020, doi: <https://doi.org/10.3390/ma13214968>.
- [63] S. L. Correia, K. A. S. Curto, D. Hotza, and A. M. Segadães, "Using Experiments Design to Model Linear Firing Shrinkage of Triaxial Ceramic Bodies," Materials Science Forum, vol. 498–499, pp. 430–435, Nov. 2005, doi: <https://doi.org/10.4028/www.scientific.net/msf.498-499.430>.
- [64] A. Elimbi, J. M. Dika, and C. N. Djangang, "Effects of Alkaline Additives on the Thermal Behavior and Properties of Cameroonian Poorly Fluxing Clay Ceramics," Journal of Minerals and Materials Characterization and Engineering, vol. 02, no. 05, pp. 484–501, Jan. 2014, doi: <https://doi.org/10.4236/jmmce.2014.25049>.

- [65] V.-G. Lee and T.-H. Yeh, "Sintering effects on the development of mechanical properties of fired clay ceramics," *Materials Science and Engineering: A*, vol. 485, no. 1–2, pp. 5–13, Jun. 2008, doi: [10.1016/j.msea.2007.07.068](https://doi.org/10.1016/j.msea.2007.07.068).
- [66] I. Stubna, A. Trník, F. Chmelik, and L. Vozar, "Mechanical Properties of Kaolin-Base Ceramics During Firing," in *Advances in Ceramics - Characterization, Raw Materials, Processing, Properties, Degradation and Healing*, C. Sikalidis, Ed., InTech, 2011. doi: [10.5772/19199](https://doi.org/10.5772/19199).
- [67] P. Šín, R. Podoba, I. Štubňa, and A. Trník, "Mechanical properties of alumina porcelain during heating," presented at the TIM 2013 PHYSICS CONFERENCE, Timisoara, Romania, 2014, pp. 76–80. doi: [10.1063/1.4903017](https://doi.org/10.1063/1.4903017).
- [68] A. Elimbi, J. M. Dika, and C. N. Djangang, "Effects of Alkaline Additives on the Thermal Behavior and Properties of Cameroonian Poorly Fluxing Clay Ceramics," *Journal of Minerals and Materials Characterization and Engineering*, vol. 02, no. 05, pp. 484–501, Jan. 2014, doi: <https://doi.org/10.4236/jmmce.2014.25049>.
- [69] P. P. Parlevliet, H. E. N. Bersee, and A. Beukers, "Residual stresses in thermoplastic composites—A study of the literature—Part II: Experimental techniques," *Composites Part A: Applied Science and Manufacturing*, vol. 38, no. 3, pp. 651–665, Mar. 2007, doi: <https://doi.org/10.1016/j.compositesa.2006.07.002>.
- [70] "The TCNA Handbook for Ceramic, Glass and Stone Tile Installation," www.ceramictilefoundation.org, Sep. 01, 2020. <https://www.ceramictilefoundation.org/blog/tcna-handbook>
- [71] P. K. Panda, T. S. Kannan, J. Dubois, C. Olagnon, and G. Fantozzi, "Thermal shock and thermal fatigue study of ceramic materials on a newly developed ascending thermal shock test equipment," *Science and Technology of Advanced Materials*, vol. 3, no. 4, pp. 327–334, Jan. 2002, doi: [https://doi.org/10.1016/s1468-6996\(02\)00029-3](https://doi.org/10.1016/s1468-6996(02)00029-3).
- [72] S. Jazayeri, A. Salem, Timellini, and Rastelli, "Cerámica y Vidrio A kinetic study on the development of porosity in porcelain stoneware tile sintering," Feb. 2007. Accessed: Feb. 28, 2024. [Online]. Available: <https://boletines.secv.es/upload/20070113132809.46%5B1%5D1-6.pdf>
- [73] V.-G. Lee and T.-H. Yeh, "Sintering effects on the development of mechanical properties of fired clay ceramics," *Materials Science and Engineering: A*, vol. 485, no. 1–2, pp. 5–13, Jun. 2008, doi: <https://doi.org/10.1016/j.msea.2007.07.068>.
- [74] P. Šín, R. Podoba, Igor Štubňa, and A. Trník, "Mechanical properties of alumina porcelain during heating," *Nucleation and Atmospheric Aerosols*, Jan. 2014, doi: <https://doi.org/10.1063/1.4903017>.
- [75] T. Húlan et al., "Young's Modulus of Different Illitic Clays during Heating and Cooling Stage of Firing," *Materials*, vol. 13, no. 21, p. 4968, Nov. 2020, doi: <https://doi.org/10.3390/ma13214968>.
- [76] A. Vojtko, P. Šín, and I. Štubňa, "POISSON'S RATIO OF KAOLIN CERAMICS AS A FUNCTION OF FIRING TEMPERATURE," in *Material – Acoustics*, 2011.
- [77] E. Eren Gültekin, "The effect of heating rate and sintering temperature on the elastic modulus of porcelain tiles," *Ultrasonics*, vol. 83, pp. 120–125, Feb. 2018, doi: <https://doi.org/10.1016/j.ultras.2017.06.005>.
- [78] A. Elimbi, J. M. Dika, and C. N. Djangang, "Effects of Alkaline Additives on the Thermal Behavior and Properties of Cameroonian Poorly Fluxing Clay Ceramics," *Journal of Minerals and Materials Characterization and Engineering*, vol. 02, no. 05, pp. 484–501, Jan. 2014, doi: <https://doi.org/10.4236/jmmce.2014.25049>.
- [79] Martín-Márquez, J. Ma. Rincón, and M. Romero, "Mullite development on firing in porcelain stoneware bodies," *Journal of the European Ceramic Society*, vol. 30, no. 7, pp. 1599–1607, May 2010, doi: <https://doi.org/10.1016/j.jeurceramsoc.2010.01.002>.
- [80] A. D. Pekdemir, Y. Sarıkaya, and M. Önal, "Thermal transformation kinetics of a kaolinitic clay," *Journal of Thermal Analysis and Calorimetry*, vol. 123, no. 1, pp. 767–772, Jul. 2015, doi: <https://doi.org/10.1007/s10973-015-4866-8>.

- [81] B. F. Rangel, M. M. Viana, M. V. A. Fonseca, J. Dweck, and L. M. Tavares, "Thermal characterization of a new green ceramic material by heating microscopy, thermogravimetry and differential thermal analysis," *Journal of Thermal Analysis and Calorimetry*, vol. 121, no. 1, pp. 115–125, Jul. 2015, doi: 10.1007/s10973-015-4496-1.
- [82] M. S. Conconi, M. Morosi, J. Maggi, P. E. Zalba, F. Cravero, and N. M. Rendtorff, "Thermal behavior (TG-DTA-TMA), sintering and properties of a kaolinitic clay from Buenos Aires Province, Argentina," *Ceramica*, vol. 65, no. 374, pp. 227–235, 2019, doi: 10.1590/0366-69132019653742621.
- [83] S. A. T. Redfern, "The kinetics of dehydroxylation of kaolinite," *Clay Minerals*, vol. 22, no. 4, pp. 447–456, Dec. 1987, doi: <https://doi.org/10.1180/claymin.1987.022.4.08>.
- [84] I. Hammouda and D. Mihoubi, "Thermodynamic and mechanical characterisation of kaolin clay," *Polish Journal of Chemical Technology*, vol. 16, no. 1, pp. 28–35, 2014, doi: 10.2478/pjct-2014-0005.
- [85] O. Castelein, B. Soulestin, J. P. Bonnet, and Philippe Blanchart, "The influence of heating rate on the thermal behaviour and mullite formation from a kaolin raw material," *Ceramics International*, vol. 27, no. 5, pp. 517–522, Jan. 2001, doi: [https://doi.org/10.1016/s0272-8842\(00\)00110-3](https://doi.org/10.1016/s0272-8842(00)00110-3).
- [86] Hayward and A. Arbor, "Hysteresis upon Repeated Cycling through the Beta-Alpha Cristobalite Transformation," *Journal of Ceramic Science and Technology*, vol. 6, no. 1, pp. 55–62, Jan. 2014, doi: <https://doi.org/10.4416/jcst2014-00048>.
- [87] A. I. Rat'ko, A. I. Ivanets, A. I. Kulak, Y. Morozov, and I. O. Sakhar, "Thermal decomposition of natural dolomite," vol. 47, no. 12, pp. 1372–1377, Nov. 2011, doi: <https://doi.org/10.1134/s002016851120156>.
- [88] S. Ke, X. Cheng, Y. Wang, Q. Wang, and H. Wang, "Dolomite, wollastonite and calcite as different CaO sources in anorthite-based porcelain," *Ceramics International*, vol. 39, no. 5, pp. 4953–4960, Jul. 2013, doi: <https://doi.org/10.1016/j.ceramint.2012.11.091>.
- [89] M. JANKULA et al., "The influence of heat on elastic properties of illitic clay Radobica," *Journal of the Ceramic Society of Japan*, vol. 123, no. 1441, pp. 874–879, 2015, doi: <https://doi.org/10.2109/jcersj2.123.874>.
- [90] H. Cengizler, "Effect of calcination temperature on use of high-boron-content waste for low-temperature wall tile production," *Ceramics International*, vol. 48, no. 5, pp. 6024–6036, Nov. 2021, doi: <https://doi.org/10.1016/j.ceramint.2021.11.138>.
- [91] S. L. Correia, K. A. S. Curto, D. Hotza, and A. M. Segadães, "Using Experiments Design to Model Linear Firing Shrinkage of Triaxial Ceramic Bodies," *Materials Science Forum*, vol. 498–499, pp. 430–435, Nov. 2005, doi: <https://doi.org/10.4028/www.scientific.net/msf.498-499.430>.
- [92] S. OUMMADI, "Drying behaviour of ceramic green bodies: experimental characterization and numerical modeling," Dec. 2019. Available: <https://theses.hal.science/tel-02495750>
- [93] Y. Cheng et al., "Dehydroxylation and Structural Distortion of Kaolinite as a High-Temperature Sorbent in the Furnace," vol. 9, no. 10, pp. 587–587, Sep. 2019, doi: <https://doi.org/10.3390/min9100587>.
- [94] Pagliari, L., Dapiaggi, M., Pavese, A., & Francescon, F. (2013). A kinetic study of the quartz–cristobalite phase transition. *Journal of the European Ceramic Society*, 33(15-16), 3403–3410. doi:10.1016/j.jeurceramsoc.2013.06.014
- [95] Ptáček, P., Šoukal, F., Opravil, T., Havlica, J., & Brandštet, J. (2013). Crystallization of spinel phase from metakaoline: The nonisothermal thermogravimetric CRH study. *Powder Technology*, 243, 40–45. doi:10.1016/j.powtec.2013.03.031
- [96] M. Romero; J. Martín-Márquez; J.Ma. Rincón (2006). Kinetic of mullite formation from a porcelain stoneware body for tiles production. , 26(9), 1647–1652. doi:10.1016/j.jeurceramsoc.2005.03.235
- [97] M. Olszak-Humienik and M. Jablonski, "Thermal behavior of natural dolomite," *Journal of Thermal Analysis and Calorimetry*, vol. 119, no. 3, pp. 2239–2248, Dec. 2014, doi: <https://doi.org/10.1007/s10973-014-4301-6>.

- [98] Ptáček, P., Opravil, T., & Šoukal, F. (2016). Introduction of novel kinetic approach to calculation of activation energy and its application to the sinter-crystallization of strontian feldspar. *Ceramics International*, 42(15), 16969–16980. doi:10.1016/j.ceramint.2016.07.203
- [99] Amor³s, J.L.; Blasco, E.; Moreno, A.; Marⁿ, N.; Feliu, C. (2020). Sinter-crystallisation kinetics of a SiO²–Al²O³–CaO–MgO–SrO glass-ceramic glaze. *Journal of Non-Crystalline Solids*, 532(), 119900–. doi:10.1016/j.jnoncrysol.2020.119900
- [100] Amor³s, J.L.; Blasco, E.; Moreno, A.; Marⁿ, N.; Feliu, C. (2020). Sinter-crystallisation kinetics of a SiO²–Al²O³–CaO–MgO–SrO glass-ceramic glaze. *Journal of Non-Crystalline Solids*, 532(), 119900–. doi:10.1016/j.jnoncrysol.2020.119900
- [101] W.-C.R. Chan, Kelbon Marica, B.B. Krieger, Modeling and experimental verification of physical and chemical process during pyrolysis of a large biomass particle, *Fuel* 64 (1985) 1505e1513
- [102] Y. Kobayashi, H. Maekawa, W. Okuno, T. Mizuno, T. Sugimura, and A. Negawa, “Effect of quartz grain size on elastic and thermal expansion properties of porcelain,” *Journal of the Ceramic Society of Japan*, vol. 131, no. 8, pp. 451–457, Aug. 2023, doi: <https://doi.org/10.2109/jcersj2.23050>.
- [103] Igor Štubňa, Marek Mánik, Tomáš Húlan, and A. Trník, “Development of stress on quartz grain in illite ceramics during cooling stage of firing,” *Journal of the Ceramic Society of Japan*, vol. 128, no. 3, pp. 117–123, Mar. 2020, doi: <https://doi.org/10.2109/jcersj2.19169>.
- [104] Alves and João Baptista Baldo, “The Threshold Percolation Volume Fraction of Vitreous Silica on the Thermal Expansion Behavior of Quartz,” *Journal of Materials Science and Chemical Engineering*, vol. 07, no. 06, pp. 1–6, Jan. 2019, doi: <https://doi.org/10.4236/msce.2019.76001>.
- [105] H. S. Houldsworth and J. W. Cobb, “THE REVERSIBLE THERMAL EXPANSION OF REFRACTORY MATERIALS,” *Journal of the American Ceramic Society*, vol. 6, no. 5, pp. 645–662, May 1923, doi: <https://doi.org/10.1111/j.1151-2916.1923.tb18141.x>.
- [106] “Volume Changes in Porcelain Bodies During the Cooling Phase After Firing.” Accessed: Aug. 22, 2024. [Online]. Available: <https://www.tainstruments.com/pdf/literature/DIL002.pdf>
- [107] E. Sánchez et al., “Residual stresses in porcelain tiles. Measurement and process variables assessment,” *Journal of the European Ceramic Society*, vol. 39, no. 11, pp. 3364–3372, Sep. 2019, doi: <https://doi.org/10.1016/j.jeurceramsoc.2019.04.038>.
- [108] Ludmila Mahnicka-Goremikina, Ruta Svinka, Visvaldis Svinka, Liga Grase, and Vadims Goremikins, “The formation of phases with low or negative linear thermal expansion coefficient in porous mullite ceramics,” *Epitoanyag-Journal of Silicate Based and Composite Materials*, vol. 72, no. 3, pp. 91–98, Jan. 2020, doi: <https://doi.org/10.14382/epitoanyag-jsbcm.2020.15>.
- [109] Mechanical and Thermal Properties of Ceramics Proceedings of a Symposium Held at Gaithersburg, Maryland chrome-extension://efaidnbmnnnibpcajpcglclefindmkaj/https://nvlpubs.nist.gov/nistpubs/Legacy/SP/nbsspecialpublication303.pdf <https://www.expertlabservice.it/en/publication/the-effect-of-cooling-rate-on-the-specific-volume-of-glassy-phases/>
- [110] J. E. K. Schawe and J. F. Löffler, “Existence of multiple critical cooling rates which generate different types of monolithic metallic glass,” *Nature Communications*, vol. 10, no. 1, Mar. 2019, doi: <https://doi.org/10.1038/s41467-018-07930-3>.
- [111] Johnson, J. S., Clark, J., Miller-Antonio, S., Robins, D., Schiffer, M. B., & Skibo, J. M. (1988). Effects of firing temperature on the fate of naturally occurring organic matter in clays. *Journal of Archaeological*
- [112] Leinweber, P., & Schulten, H.-R. (1992). Differential thermal analysis, thermogravimetry and in-source pyrolysis-mass spectrometry studies on the formation of soil organic matter. *Thermochimica Acta*,
- [113] J. M. N. Jayaweera, M. Narayana, and S. U. Adikary, “Numerical Modeling of Drying Behavior of Sri Lankan Kaolin,” in 2021 Moratuwa Engineering Research Conference

- (MERCon), Moratuwa, Sri Lanka: IEEE, Jul. 2021, pp. 48–53. doi: 10.1109/MERCon52712.2021.9525774.
- [114] P. Niedoba, L. Čermák, and M. Jicha, “Meshfree methods for computational fluid dynamics,” EPJ Web of Conferences, vol. 45, p. 01068, 2013, doi: <https://doi.org/10.1051/epjconf/20134501068>.
- [115] J. J. Monaghan, “Smoothed particle hydrodynamics.” Reports on Progress in Physics, Institute of Physics Publishing, Jul. 2005, vol. 68(8), pp.1703–1759. doi:10.1088/0034-4885/68/8/r01
- [116] W. A. M. K. P. Wickramaarachchi and M. Narayana, “Pyrolysis of single biomass particle using three-dimensional Computational Fluid Dynamics modelling,” Renewable Energy, vol. 146, pp. 1153–1165, Feb. 2020, doi: <https://doi.org/10.1016/j.renene.2019.07.001>.
- [117] Montorfano, F. Piscaglia, and A. Onorati, “An Extension of the Dynamic Mesh Handling with Topological Changes for LES of ICE in OpenFOAM®,” SAE technical papers on CD-ROM/SAE technical paper series, Apr. 2015, doi: <https://doi.org/10.4271/2015-01-0384>.
- [118] H. Jasak, “Dynamic Mesh Handling in OpenFOAM,” in 47th AIAA Aerospace Sciences Meeting including The New Horizons Forum and Aerospace Exposition, Reston, Virginia: American Institute of Aeronautics and Astronautics, Jan. 2009, doi: <http://dx.doi.org/10.2514/6.2009-341>