

REFERENCES

- [1] J. Y. Koh, H.G. Lee, John, 'System Performance with Variation of Outdoor Unit Layouts at Building Re-entrants', *International Journal of Air-Conditioning and Refrigeration*, vol. 16, no. 1, 2008, pp. 15-21.
- [2] 'World Air Conditioner Demand by Region', *The Japan Refrigeration and Air-Conditioning Industry Association*, 2019.
- [3] H. Xue, B. Xu, J. Wu, Y. Wei, 'Prediction of temperature rise near condensing units', *Building and Environment*, vol. 42, 2007, pp. 2480–2487.
- [4] T. T. Chow, Z. Lin, and X. Y. Yang, 'Placement of condensing units of split-type air-conditioners at low-rise residences', *Applied Thermal Engineering*, vol. 22, no. 13, pp., 2002, 1431–1444.
- [5] T. T. Chow, J. P. Liu, and Q. W. Wang, 'Evaluating group performance of residential air- conditioners', *International Journal on Architectural Science*, vol. 3, 2002, pp. 11.
- [6] D. Geekiyanage and T. Ramachandra, 'A model for estimating cooling energy demand at early design stage of condominiums', *Journal of Building Engineering*, vol. 17, 2018, pp. 43–51.
- [7] D. R. Yau, D. V. Cheng, S. Lee, O. Arup, and H. Kong, 'Planning and design tools for sustainable housing development for healthy living', 2004, pp. 8.
- [8] B. K. Gupta, A. Patil, and P. Dharkar, 'Application of CFD simulations for locating outdoor units on high rise tower', *14th Conference of International Building Performance Simulation Association*, 2015, pp. 2448-2452.
- [9] G. Wang, Y. Hu, and S. Hu, 'Thermal environment of outdoor units of vrv system in high- rise building', *Building Simulation*, 2007, pp. 1109-1114.
- [10] K. Prasath, S. Thavanees, A. Prakalathan, and M. A. Wijewardane, 'Analysis of the heat column formation in a 10 storey building', *110th Annual Sessions The Institution of Engineers*, 2016, p. 6.
- [11] A. Avara and E. Daneshgar, 'Optimum placement of condensing units of split-type air-conditioners by numerical simulation', *Energy and Buildings*, vol. 40, no. 7, 2008, pp. 1268–1272.
- [12] M. Bruelisauer, F. Meggers, E. Saber, C. Li, and H. Leibundgut, 'Stuck in a stack—Temperature measurements of the microclimate around split type condensing units in a high rise building in Singapore', *Energy and Buildings*, vol. 71, 2014, pp. 28–37.
- [13] P. N. Ananthanarayanan, " Basic Refrigeration and Air Conditioning", 3rd Edition, Tata McGraw-Hill Education Publisher Limited, 2015, pp. 262-271, 280-285.

- [14] Azridjal Aziz, Arya Bhima Satria, Rahmat Iman Mainil, 'Experimental study of split air conditioner with and without trombone coil condenser as air conditioning water heater', *International Journal of Automotive and Mechanical Engineering (IJAME)*, Vol. 12, pp. 3043-3057, 2015
- [15] Bashab Jyoti Phukan, S.K. Deb, 'Performance improvement of split air conditioner using evaporative cooling method in the climatic condition of Guwahati, Assam', *International Research Journal of Engineering and Technology (IRJET)*, Vol. 5, pp. 321-328, 2018
- [16] M. Bojic, S. Savic, and D. Nikolic, 'Application of Computational Fluid Dynamics to flow next to high-rise buildings in Hong Kong due to air-conditioner heat rejection', *International Journal of Energy Technology and Policy*, vol. 6, no. 1/2, 2008, pp. 159.
- [17] T. T. Chow, Z. Lin, and Q. W. Wang, 'Effect of building re-entrant shape on performance of air-cooled condensing units', 2000, pp. 10.
- [18] N. Ba Chien, N. Viet Dung, T. Quoc Dung, N. Tien Cuong, and K. Hiep Le, 'CFD Simulation of Multi-Outdoor Unit Configuration Design for a Building', *IOP Conference Series: Earth and Environmental Science*, vol. 505, 2020, pp. 012007.
- [19] T. T. Chow and Z. Lin, 'Prediction of on-coil temperature of condensers installed at tall building re-entrant', *Applied Thermal Engineering*, vol. 19, no. 2, 1999, pp. 117–132.
- [20] T. T. Chow, Z. Lin, Q. W. Wang, and J. W. Z. Lu, 'Studying thermal performance of split-type air-conditioners at building re-entrant via computer simulation', *Energy and Buildings*, vol. 34., no. 3, 2002, pp. 237-244.
- [21] B. Blocken, 'Computational Fluid Dynamics for urban physics: Importance, scales, possibilities, limitations and ten tips and tricks towards accurate and reliable simulations', *Building & Environment*, vol. 91, 2015, pp. 219-245.
- [22] ANSI/ASHRAE/IES Addenda ce and cp to ANSI/ASHRAE/IESNA Standard 90.1-2007', p. 16.
- [23] A. O. Elsayed and T. S. Kayed, 'Dynamic performance analysis of inverter-driven split air conditioner', *International Journal of Refrigeration*, vol. 118, 2020, pp. 443–452.
- [24] T. T. Chow, Z. Lin, and J. P. Liu, 'Effect of condensing unit layout at building re-entrant on split-type air-conditioner performance', *Energy and Buildings*, vol. 34, no. 3, pp. 237–244, 200.
- [25] Climate of Sri Lanka, Available at: <http://www.meteo.gov.lk/> (Accessed: 30 September 2021)

- [26] Jae-Yoon Koh, Hyun-Gu Lee, John Zhai, ‘System performance with variation of outdoor unit layouts at Building re-entrants’, *International Journal of Air-Conditioning and Refrigeration*, Vol. 16, No. 1, pp. 15-21, 2008.
- [27] Garratt, J. R., *The Atmospheric Boundary Layer*. Cambridge University Press. (1992).
- [28] Bert Blocken, Ted Stathopoulos, Jan Carmeliet, Jan Hensen, ‘Application of CFD in Building performance simulation for the outdoor environment’, *Eleventh International IBPSA Conference*, 2009, pp. 489-496.
- [29] M. A. Nelson, M. D. Williams, D. Zajic, E. R. Pardyjak, and M. J. Brown, “Evaluation of an urban vegetative canopy scheme and impact on plume dispersion,” in Proc. 89th AMS Annu. Meeting, Phoenix, AZ, Jan. 2009, Poster JP6.4.
- [30] Electricity Bill Calculator, Ceylon Electricity Board, 2025. [Online]. Available: <https://cebcare.ceb.lk/Incognito/BillCalculator>
- [31] Tareq Gaber Farea, Dilshan Remaz Ossen, Saqaff Alkaff, Hisashikotani, ‘CFD modeling for natural ventilation in a lightwell connected to outdoor through horizontal voids’, *Energy and Buildings*, vol. 86, 2015, pp. 502-513
- [32] Nestoras Antoniou, Hamid Montazeri, Hans Wigo, Marina K.-A. Neophytou, Bert Blocken, Mats Sandberg, ‘CFD and wind-tunnel analysis of outdoor ventilation in a real compact heterogeneous urban area: Evaluation using air delay’, *Building and Environment*. vol. 126, 2017, pp. 355-372.
- [33] F. R. Menter, "Two-equation eddy-viscosity turbulence models for engineering applications," *AIAA J.*, Aug. 1994, vol. 32, no. 8, pp. 1598–1605