

References

- [1] S. L. E. D. Board, "Sri Lanka Export Development Board," [Online]. Available: <https://www.srilankabusiness.com/rubber/non-tyre-sector.html>. [Accessed 25 06 2024].
- [2] Britannica, "Britannica," [Online]. Available: <https://www.britannica.com/technology/tire#ref117797>. [Accessed 26 06 2024].
- [3] V. Empire, "Vehicle Empire," [Online]. Available: <https://vehicleempire.com/tire-manufacturing-process/>. [Accessed 10 06 2024].
- [4] J. E. Mark, B. Erman and F. R. Eirich (Eds.), "Reinforcement of elastomers by particulate fillers," *Science and technology of rubber (2nd ed)*, Academic Press, San Diego, pp. 387-418, 1994.
- [5] S. Barathan and B. Gobinath, "Evaluation of wood ash as a partial replacement to cement," *International Journal of science, engineering and technology research*, no. 2, pp. 2009-2013, 2013.
- [6] B. Olanders and B. Steenari, "Characterization of ashes from wood and straw," *Biomass Bioenergy*, no. 8, pp. 105-115, 1995.
- [7] M. Sharma, A. A. Khan, S. K. Puri and D. K. Tuli, "Wood ash as a potential heterogeneous catalyst," *Biomass Bioenergy*, no. 41, pp. 94-106, 2012.
- [8] A. L. Ulery, R. C. Graham and C. Amrhein, "Wood-ash composition and soil pH following intense burning," *Soil Sci*, no. 156, p. 358–364, 1993.
- [9] A. Demeyer, W. J. C. Nkana and M. Verloo, "Characteristics of wood ash and influence on," *An overview Biores. Technol*, no. 77, p. 287–295, 2001.

- [10] S. Bülbül, N. Akçakale, M. Yasar and H. Gökmese, "The effect of wood ash on the mechanical properties of rubber compounds," *Materials and technology*, no. 53, p. 333–339, 2012.
- [11] S. Bülbül, M. Yasar and N. Akçakale, "Effect of changing of filling materials in NR-SBR type elastomer based rubber materials on mechanical properties," *Polymer (Korea)*, no. 38, pp. 664-670, 2014.
- [12] L. Jean L, "Rubber–filler interactions and rheological properties in filled compounds," *Progress in Polymer Science*, vol. 27, no. 4, pp. 627-687, 2002.
- [13] J. B. Donnet and A. Voet, "Carbon black physics, chemistry and elastomer reinforcement," *Marcel Dekker*, 1976.
- [14] J. B. Donnet, Carbon black, New York: Marcel Dekker, 1993.
- [15] J. B. Donnet and E. Custodero, "Ordered structures observed by scanning tunnelling macroscopy at atomic scale on carbon black surfaces," *Carbon*, no. 30, pp. 813-817, 1992.
- [16] J. B. Donnet, "Black and white fillers and tire compound," *Rubber Chem Technol*, no. 71, pp. 323-348, 1998.
- [17] T. C. Gruber and C. R. Herd, "Anisometry measurements in carbon black aggregate populations," *Rubber Chem Technol*, no. 70, pp. 727-746, 2000.
- [18] J. L. Leblanc and C. Barrès, "Bound rubber," in *a key factor in understanding the rheological properties of carbon black filled rubber compounds*, Illinois, Rub Div Mtg, Am Chem Soc Chicago, 1999, p. 13–16.
- [19] G. R. Cotten, "Mixing of carbon black with rubber I. Measurement of dispersion rate by changes in mixing torque," *Rubber Chem Technol*, no. 57, pp. 118-133, 1984.

- [20] G. R. Cotten, "Mixing of carbon black with rubber: IV. Effect of carbon black characteristics," *Plast Rubber Proc Applic*, no. 7 (3), pp. 173-178, 1987.
- [21] J. L. Leblan, "Insight into elastomer-filler interactions and their role in the processing behaviour of rubber compounds," *Plast Rubber Proc Technol*, no. 10 (2), pp. 110-129, 1994.
- [22] A. R. Payne and R. E. Whittaker, "Low strain dynamic properties of filled rubber," *Rubber Chem Technol*, no. 44, pp. 440-478, 1971.
- [23] A. Feriancová, M. Pajtášová, K. Moricová and B. Pecušová, "Using of wood ash as the alternative filler for preparation of rubber mixtures," in *IOP Conference Series Materials Science and Engineering*, San Francisco Canada, 2020.
- [24] B. Saban , A. Nurettin, Y. Mustafa and G. Hakan, "The Effect of wood Ash on the Mechanical Properties of Rubber Compounds," *Materials and technology*, no. 53, p. 333–339, 2019.
- [25] Y. Niu, H. Tan and S. Hui, "Prog. Energy Combust. Sci," *Ash-related issues during biomass combustion: alkali-induced slagging, silicate melt-induced slagging (ash fusion), agglomeration, corrosion, ash utilization, and related countermeasures*, no. 52, pp. 1-61, 2016.
- [26] R. P. Brown, Rubber Product Failure, Shawbury: RAPRA Technology, 2002.
- [27] J. Maláč, Rubber technology (Electronic Materials), Czech: Univerzity of Tomáš Baťa, 2005.
- [28] N. Sombatsompop, S. Thongsang, T. Markpin and E. Wimolmala, "Fly ash an precipitated silica as rubber fillers," *J. Appl. Polym. Sci*, no. 93, p. 2119–2130, 2004.

- [29] R. Rakdee, C. Rakdee and P. Thanmathorn, "Use of rice husk ash as filler in natural rubber vulcanizates in comparison with other commercial fillers," *J. Appl. Polym. Sci.*, no. 83, p. 2485–2493, 2002.
- [30] S. Debnath, S. K. De and D. Khastgir, "Effect of silane coupling agent on vulcanization, network structure, polymer-filler interaction, physical properties and failure mode of mica-filled styrene-butadiene rubber," *J. Mater. Sci.*, no. 22, p. 4453–4459, 1987.
- [31] R. Manshaie, S. K. Khorasani, S. J. Veshare and M. R. Abadchi, "Effect of electron beam irradiation on the properties of Natural Rubber (NR)/Styrene–Butadiene Rubber (SBR) blend," *Radiation Physics and Chemistry*, p. 100–106, 2011.
- [32] K. Sengloyluan, K. Sahakaro, W. K. Dierkes and J. W. M. Noordermeer, "Silica-reinforced tire tread compounds compatibilized by using epoxidized natural rubber," *European Polymer Journal*, no. 51, p. 69–79, 2014.