

REFERENCES

- [1] E. Sariyildiz, "A stability analysis for the reaction torque observer-based sensorless force control systems," in *2023 IEEE International Conference on Mechatronics (ICM)*. IEEE, 2023, pp. 1–5.
- [2] Y. Ohba, M. Sazawa, K. Ohishi, T. Asai, K. Majima, Y. Yoshizawa, and K. Kageyama, "Sensorless force control for injection molding machine using reaction torque observer considering torsion phenomenon," *IEEE Transactions on Industrial Electronics*, vol. 56, no. 8, pp. 2955–2960, 2009.
- [3] E. Sariyildiz and K. Ohnishi, "A comparison study for force sensor and reaction force observer based robust force control systems," in *2014 IEEE 23rd International Symposium on Industrial Electronics (ISIE)*. IEEE, 2014, pp. 1156–1161.
- [4] Z. Qian and Z. Bi, "Recent development of rehabilitation robots," *Advances in Mechanical Engineering*, vol. 7, no. 2, p. 563062, 2015.
- [5] G. . L. R. of Stroke Collaborators, "Global, regional, and country-specific lifetime risks of stroke, 1990 and 2016," *New England Journal of Medicine*, vol. 379, no. 25, pp. 2429–2437, 2018.
- [6] D. Shi, W. Zhang, W. Zhang, and X. Ding, "A review on lower limb rehabilitation exoskeleton robots," *Chinese Journal of Mechanical Engineering*, vol. 32, no. 1, pp. 1–11, 2019.
- [7] S. K. Banala, S. H. Kim, S. K. Agrawal, and J. P. Scholz, "Robot assisted gait training with active leg exoskeleton (alex)," *IEEE transactions on neural systems and rehabilitation engineering*, vol. 17, no. 1, pp. 2–8, 2008.
- [8] F. J. Ruiz-Ruiz, J. M. Gandarias, F. Pastor, and J. M. Gomez-De-Gabriel, "Upperlimb kinematic parameter estimation and localization using a compliant robotic manipulator," *IEEE Access*, vol. 9, pp. 48 313–48 324, 2021.
- [9] P. Song, Y. Yu, and X. Zhang, "A tutorial survey and comparison of impedance control on robotic manipulation," *Robotica*, vol. 37, no. 5, pp. 801–836, 2019.
- [10] M. M. Fateh and R. Babaghasabha, "Impedance control of robots using voltage control strategy," *Nonlinear Dynamics*, vol. 74, pp. 277–286, 2013.
- [11] Trisha, G. Gupta, and S. Shiva Kumar, "Review of the parameter estimation and transient analysis of three-phase induction motor," in *Advances in Smart Grid Automation and Industry 4.0: Select Proceedings of ICETSGAI4. 0*. Springer, 2021, pp. 223–232.

- [12] S. Katsura, Y. Matsumoto, and K. Ohnishi, "Modeling of force sensing and validation of disturbance observer for force control," *IEEE Transactions on industrial electronics*, vol. 54, no. 1, pp. 530–538, 2007.
- [13] B. Ugurlu, M. Nishimura, K. Hyodo, M. Kawanishi, and T. Narikiyo, "Proof of concept for robot-aided upper limb rehabilitation using disturbance observers," *IEEE Transactions on Human-Machine Systems*, vol. 45, no. 1, pp. 110–118, 2014.
- [14] R. Ruwanthika and A. H. S. Abeykoon, "3d environmental force: Position impedance variation for different motion parameters," in *2015 Moratuwa Engineering Research Conference (MERCCon)*. IEEE, 2015, pp. 112–117.
- [15] J. K. Salisbury, "Active stiffness control of a manipulator in cartesian coordinates," in *1980 19th IEEE conference on decision and control including the symposium on adaptive processes*. IEEE, 1980, pp. 95–100.
- [16] M. H. Raibert and J. J. Craig, "Hybrid position/force control of manipulators," 1981.
- [17] W. Xu, J. Han, and S. Tso, "Experimental study of contact transition control incorporating joint acceleration feedback," *IEEE/ASME transactions on mechatronics*, vol. 5, no. 3, pp. 292–301, 2000.
- [18] K. Kim, M. Kang, Y. Choi, H. Jang, J. Han, and C. Han, "Development of the exoskeleton knee rehabilitation robot using the linear actuator," *International Journal of Precision Engineering and Manufacturing*, vol. 13, no. 10, pp. 1889–1895, 2012.
- [19] E. Schrijver and J. Van Dijk, "Disturbance observers for rigid mechanical systems: equivalence, stability, and design," *J. Dyn. Sys., Meas., Control*, vol. 124, no. 4, pp. 539–548, 2002.
- [20] A. Kato and K. Ohnishi, "Robust force sensorless control in motion control system," in *9th IEEE International Workshop on Advanced Motion Control, 2006*. IEEE, 2006, pp. 165–170.
- [21] E. Sariyildiz and K. Ohnishi, "A guide to design disturbance observer," *Journal of Dynamic Systems, Measurement, and Control*, vol. 136, no. 2, p. 021011, 2014.
- [22] A. Mohammadi and H. Dallali, "Disturbance observer applications in rehabilitation robotics: an overview," *Powered prostheses*, pp. 113–133, 2020.

- [23] P. D. Harischandra and A. H. S. Abeykoon, “Upper-limb tele-rehabilitation system with force sensorless dynamic gravity compensation,” *International Journal of Social Robotics*, vol. 11, pp. 621–630, 2019.
- [24] X. Su, X. Yan, and C.-L. Tsai, “Linear regression,” *Wiley Interdisciplinary Reviews: Computational Statistics*, vol. 4, no. 3, pp. 275–294, 2012.
- [25] W. T. G. Wijewardhana, E. H. Senevirathne, and A. H. S. Abeykoon, “Iterative approach for parameter estimation in dc motor based motion systems,” in *2020 IEEE 29th International Symposium on Industrial Electronics (ISIE)*. IEEE, 2020, pp. 134–141.
- [26] M. Kino, T. Goden, T. Murakami, and K. Ohnishi, “Reaction torque feedback based vibration control in multi-degrees of freedom motion system,” in *IECON’98. Proceedings of the 24th Annual Conference of the IEEE Industrial Electronics Society (Cat. No. 98CH36200)*, vol. 3. IEEE, 1998, pp. 1807–1811.
- [27] Y. Ali, S. Noor, S. Bashi, and M. Hassan, “Microcontroller performance for dc motor speed control system,” in *Proceedings. National Power Engineering Conference, 2003. PECon 2003*. IEEE, 2003, pp. 104–109.
- [28] E. Sariyildiz and K. Ohnishi, “Analysis the robustness of control systems based on disturbance observer,” *International Journal of Control*, vol. 86, no. 10, pp. 1733–1743, 2013.
- [29] —, “Stability and robustness of disturbance-observer-based motion control systems,” *IEEE Transactions on Industrial Electronics*, vol. 62, no. 1, pp. 414–422, 2014.