

7 REFERENCES

- [1] S. W. M. A. I. Senevirathne, H. K. G. Punchihewa, K. N. M. D. S. K. Kosgahakumbura, D. M. P. P. Dissanayake, and T. Sahathevan, "Tool wear in machining AISI D2 steel with minimum quantity lubrication using alternative cutting fluids," *2016 Manuf. Ind. Eng. Symp. Innov. Appl. Ind. MIES 2016*, no. October, 2016, doi: 10.1109/MIES.2016.7780253.
- [2] R. Katna, M. Suhaib, and N. Agrawal, "Nonedible vegetable oil-based cutting fluids for machining processes—a review," *Mater. Manuf. Process.*, vol. 35, no. 1, pp. 1–32, 2020, doi: 10.1080/10426914.2019.1697446.
- [3] S. W. M. A. I. Senevirathne and H. K. G. Punchihewa, "Effect of minimum quantity lubrication aerosol temperature on tool life in machining AISI P20 and D2 steels using coated tungsten carbide tool inserts," *2nd Int. Moratuwa Eng. Res. Conf. MERCon 2016*, no. October 2017, pp. 186–191, 2016, doi: 10.1109/MERCon.2016.7480137.
- [4] "Fortune business insights," 1390. <https://www.fortunebusinessinsights.com/industry-reports/metalworking-fluids-market-101391>.
- [5] E. Benedicto, D. Carou, and E. M. Rubio, "Technical, Economic and Environmental Review of the Lubrication/Cooling Systems Used in Machining Processes," *Procedia Eng.*, vol. 184, pp. 99–116, 2017, doi: 10.1016/j.proeng.2017.04.075.
- [6] A. H. Abdelrazek, I. A. Choudhury, Y. Nukman, and S. N. Kazi, "Metal cutting lubricants and cutting tools: a review on the performance improvement and sustainability assessment," *Int. J. Adv. Manuf. Technol.*, vol. 106, no. 9–10, pp. 4221–4245, 2020, doi: 10.1007/s00170-019-04890-w.
- [7] M. N. Derani and M. M. Ratnam, "The use of tool flank wear and average roughness in assessing effectiveness of vegetable oils as cutting fluids during turning—a critical review," *Int. J. Adv. Manuf. Technol.*, vol. 112, no. 7–8, pp. 1841–1871, 2021, doi: 10.1007/s00170-020-06490-5.
- [8] S. A. Lawal, I. A. Choudhury, and Y. Nukman, "Application of vegetable oil-based metalworking fluids in machining ferrous metals - A review," *Int. J. Mach. Tools Manuf.*, vol. 52, no. 1, pp. 1–12, 2012, doi: 10.1016/j.ijmachtools.2011.09.003.
- [9] M. A. Xavier and M. Adithan, "Determining the influence of cutting fluids on tool wear and surface roughness during turning of AISI 304 austenitic stainless steel," *J. Mater. Process. Technol.*, vol. 209, no. 2, pp. 900–909, 2009, doi: 10.1016/j.jmatprotec.2008.02.068.
- [10] S. A. Lawal, I. A. Choudhury, and Y. Nukman, "Evaluation of vegetable and mineral oil-in-water emulsion cutting fluids in turning AISI 4340 steel with coated carbide tools," *J. Clean. Prod.*, vol. 66, pp. 610–618, 2014, doi: 10.1016/j.jclepro.2013.11.066.
- [11] S. A. Lawal, I. A. Choudhury, and Y. Nukman, "Developments in the formulation and application of vegetable oil-based metalworking fluids in turning process," *Int. J. Adv. Manuf. Technol.*, vol. 67, no. 5–8, pp. 1765–1776, 2013, doi: 10.1007/s00170-012-4607-0.
- [12] O. O. Fasina and Z. Colley, "Viscosity and specific heat of vegetable oils as a

- function of temperature: 35°C to 180°C,” *Int. J. Food Prop.*, vol. 11, no. 4, pp. 738–746, 2008, doi: 10.1080/10942910701586273.
- [13] A. O. Silalahi, N. Sukmawati, I. M. Sutjahja, D. Kurnia, and S. Wonorahardjo, “Thermophysical Parameters of Organic PCM Coconut Oil from T-History Method and Its Potential as Thermal Energy Storage in Indonesia,” *IOP Conf. Ser. Mater. Sci. Eng.*, vol. 214, no. 1, 2017, doi: 10.1088/1757-899X/214/1/012034.
- [14] E. E. G. Rojas, J. S. R. Coimbra, and J. Telis-Romero, “Thermophysical properties of cotton, canola, sunflower and soybean oils as a function of temperature,” *Int. J. Food Prop.*, vol. 16, no. 7, pp. 1620–1629, 2013, doi: 10.1080/10942912.2011.604889.
- [15] V. R. Patel, G. G. Dumancas, L. C. K. Viswanath, R. Maples, and B. J. J. Subong, “Castor oil: Properties, uses, and optimization of processing parameters in commercial production,” *Lipid Insights*, vol. 9, no. 1, pp. 1–12, 2016, doi: 10.4137/LPI.S40233.
- [16] H. Mamat, I. Nor Aini, M. Said, and R. Jamaludin, “Physicochemical characteristics of palm oil and sunflower oil blends fractionated at different temperatures,” *Food Chem.*, vol. 91, no. 4, pp. 731–736, 2005, doi: 10.1016/j.foodchem.2004.06.045.
- [17] C. B. of S. Lanka, “of the Monetary Board To the,” vol. I, no. Volume I, 2012.
- [18] G. I. P. Perera, H. M. C. M. Herath, I. M. S. J. Perera, and M. G. H. M. M. P. Medagoda, “Investigation on white coconut oil to use as a metal working fluid during turning,” *Proc. Inst. Mech. Eng. Part B J. Eng. Manuf.*, vol. 229, no. 1, pp. 38–44, 2015, doi: 10.1177/0954405414525610.
- [19] A. S. Abdul Sani, E. A. Rahim, S. Sharif, and H. Sasahara, “The influence of modified vegetable oils on tool failure mode and wear mechanisms when turning AISI 1045,” *Tribol. Int.*, vol. 129, pp. 347–362, 2019, doi: 10.1016/j.triboint.2018.08.038.
- [20] A. H. Tazehkandi, M. Shabgard, and F. Pilehvarian, “SC,” *J. Clean. Prod.*, 2015, doi: 10.1016/j.jclepro.2015.05.039.
- [21] V. K. Mamidi and M. A. Xavior, “A Review on Selection of Cutting Fluids,” *J. Res. Sci. Technol.*, vol. 1, no. 5, pp. 3–19, 2012, [Online]. Available: https://www.researchgate.net/profile/Vamsi_Mamidi/publication/268684157_A_REVIEW_ON_SELECTION_OF_CUTTING_FLUIDS/links/547317820cf24bc8ea19b1f8/A-REVIEW-ON-SELECTION-OF-CUTTING-FLUIDS.pdf.
- [22] B. Ozcelik, E. Kuram, M. Huseyin Cetin, and E. Demirbas, “Experimental investigations of vegetable based cutting fluids with extreme pressure during turning of AISI 304L,” *Tribol. Int.*, vol. 44, no. 12, pp. 1864–1871, 2011, doi: 10.1016/j.triboint.2011.07.012.
- [23] B. S. Kumar, G. Padmanabhan, and P. V. Krishna, “Experimental Investigations of Vegetable Oil Based Cutting Fluids with Extreme Pressure Additive in Machining of AISI 1040 Steel,” *Manuf. Sci. Technol.*, vol. 3, no. 1, pp. 1–9, 2015, doi: 10.13189/mst.2015.030101.
- [24] S. Shankar, T. Mohanraj, and K. Ponappa, “Influence of vegetable based cutting fluids on cutting force and vibration signature during milling of aluminium metal matrix composites,” *J. Tribol.*, vol. 12, no. June, pp. 1–17, 2017.

- [25] A. K. Sharma, A. K. Tiwari, and A. R. Dixit, "Effects of Minimum Quantity Lubrication (MQL) in machining processes using conventional and nanofluid based cutting fluids: A comprehensive review," *J. Clean. Prod.*, vol. 127, pp. 1–18, 2016, doi: 10.1016/j.jclepro.2016.03.146.
- [26] S. A. Lawal, I. A. Choudhury, and Y. Nukman, "A critical assessment of lubrication techniques in machining processes: A case for minimum quantity lubrication using vegetable oil-based lubricant," *J. Clean. Prod.*, vol. 41, pp. 210–221, 2013, doi: 10.1016/j.jclepro.2012.10.016.
- [27] S. Ravi, P. Gurusamy, and V. Mohanavel, "A review and assessment of effect of cutting fluids," *Mater. Today Proc.*, vol. 37, no. Part 2, pp. 220–222, 2020, doi: 10.1016/j.matpr.2020.05.054.
- [28] Z. Said *et al.*, "A comprehensive review on minimum quantity lubrication (MQL) in machining processes using nano-cutting fluids," *Int. J. Adv. Manuf. Technol.*, vol. 105, no. 5–6, pp. 2057–2086, 2019, doi: 10.1007/s00170-019-04382-x.
- [29] S. Islam, N. Khandoker, M. Izham, T. Azizi, and S. Debnath, "Development of a Low Cost MQL Setup for Turning Operations," *MATEC Web Conf.*, vol. 95, 2017, doi: 10.1051/mateconf/20179510004.
- [30] N. R. Dhar, M. Kamruzzaman, and M. Ahmed, "Effect of minimum quantity lubrication (MQL) on tool wear and surface roughness in turning AISI-4340 steel," *J. Mater. Process. Technol.*, vol. 172, no. 2, pp. 299–304, 2006, doi: 10.1016/j.jmatprotec.2005.09.022.
- [31] M. Hadad and B. Sadeghi, "Minimum quantity lubrication-MQL turning of AISI 4140 steel alloy," *J. Clean. Prod.*, vol. 54, pp. 332–343, 2013, doi: 10.1016/j.jclepro.2013.05.011.
- [32] L. D.V, "Performance Evaluation of Minimum Quantity Lubrication (MQL) using CBN Tool during Hard Turning of AISI 4340 and its Comparison with Dry and Wet Turning," *Bonfring Int. J. Ind. Eng. Manag. Sci.*, vol. 3, no. 3, pp. 102–106, 2013, doi: 10.9756/bijiems.4392.
- [33] Y. S. Liao, H. M. Lin, and Y. C. Chen, "Feasibility study of the minimum quantity lubrication in high-speed end milling of NAK80 hardened steel by coated carbide tool," *Int. J. Mach. Tools Manuf.*, vol. 47, no. 11, pp. 1667–1676, 2007, doi: 10.1016/j.ijmachtools.2007.01.005.
- [34] B. Kumaragurubaran, P. Gopal, T. Senthil Kumar, M. P. Mugunthan, and M. Ibrahim, "Optimization of Turning Parameters of En-9 Steel Using Design of Experiments Concepts," *Int. J. Mech. Eng. Rob. Res. 2013 B Kumaragurubaran al*, vol. 2, no. 3, pp. 182–190, 2013, [Online]. Available: <http://www.ijmerr.com/uploadfile/2015/0409/20150409050623750.pdf>.
- [35] F. Itoigawa, T. H. C. Childs, T. Nakamura, and W. Belluco, "Effects and mechanisms in minimal quantity lubrication machining of an aluminum alloy," *Wear*, vol. 260, no. 3, pp. 339–344, 2006, doi: 10.1016/j.wear.2005.03.035.
- [36] M. M. A. Khan, M. A. H. Mithu, and N. R. Dhar, "Effects of minimum quantity lubrication on turning AISI 9310 alloy steel using vegetable oil-based cutting fluid," *J. Mater. Process. Technol.*, vol. 209, no. 15–16, pp. 5573–5583, 2009, doi: 10.1016/j.jmatprotec.2009.05.014.
- [37] S. Safian *et al.*, "Feasibility Study of Using Vegetable Oil As A Cutting

- Lubricant Through The Use Of Minimum Quantity Lubrication During Machining,” *Univ. Teknol. Malaysia*, pp. 1–37, 2009.
- [38] S. Pervaiz, A. Rashid, I. Deiab, and C. M. Nicolescu, “An experimental investigation on effect of minimum quantity cooling lubrication (MQCL) in machining titanium alloy (Ti6Al4V),” *Int. J. Adv. Manuf. Technol.*, vol. 87, no. 5–8, pp. 1371–1386, 2016, doi: 10.1007/s00170-016-8969-6.
- [39] E. A. Rahim and H. Sasahara, “A study of the effect of palm oil as MQL lubricant on high speed drilling of titanium alloys,” *Tribol. Int.*, vol. 44, no. 3, pp. 309–317, 2011, doi: 10.1016/j.triboint.2010.10.032.
- [40] C. Bruni, A. Forcellese, F. Gabrielli, and M. Simoncini, “Effect of the lubrication-cooling technique, insert technology and machine bed material on the workpart surface finish and tool wear in finish turning of AISI 420B,” *Int. J. Mach. Tools Manuf.*, vol. 46, no. 12–13, pp. 1547–1554, 2006, doi: 10.1016/j.ijmachtools.2005.09.007.
- [41] S. W. M. A. I. Senevirathne and H. K. G. Punchihewa, “Reducing surface roughness by varying aerosol temperature with minimum quantity lubrication in machining AISI P20 and D2 steels,” *Int. J. Adv. Manuf. Technol.*, vol. 94, no. 1–4, pp. 1009–1019, 2018, doi: 10.1007/s00170-017-0951-4.
- [42] F. Puh, Z. Jurkovic, M. Perinic, M. Brezocnik, and S. Buljan, “Optimizacija parametara obrade tokarenja s više kriterija kvalitete uporabom Grey relacijske analize,” *Teh. Vjesn.*, vol. 23, no. 2, pp. 377–382, 2016, doi: 10.17559/TV-20150526131717.
- [43] S. Madhavi, D. Sreeramulu, and M. Venkatesh, “Optimization of turning process parameters by using grey-Taguchi,” *Int. J. Eng. Sci. Technol.*, vol. 7, no. 4, p. 1, 2016, doi: 10.4314/ijest.v7i4.1.
- [44] I. Ramu, P. Srinivas, and K. Vekatesh, “Taguchi based grey relational analysis for optimization of machining parameters of CNC turning steel 316,” *IOP Conf. Ser. Mater. Sci. Eng.*, vol. 377, no. 1, 2018, doi: 10.1088/1757-899X/377/1/012078.
- [45] M. Sree, P. Chowdary, S. K. Waseem Sohail, S. K. Sajidh, and K. Sai Krishna, “Ijesrt International Journal of Engineering Sciences & Research Technology Optimisation of Surface Roughness and Material Removal Rate in Turning Operation of Mild Steel Using Taguchi Method,” © *Int. J. Eng. Sci. Res. Technol.*, vol. 7, no. 2, pp. 477–484, 2018, [Online]. Available: <http://www.ijesrt.com>.
- [46] K. Krishnaiah and P. Shahabudeen, *Applied Experimental Design and Taguchi Method*. 2012.
- [47] N. Ramesh, D. Lokanadham, and N. T. Rao, “Optimization of MRR and surface roughness for turning of AA6061 using Taguchi method and PSO,” pp. 225–228, 2016.
- [48] U. K. Yadav, “Experimental Investigation And Optimization Of Machining Parameters For Surface Roughness In CNC Turning By Taguchi Method,” *Int. J. Eng. Res. Appl.*, vol. 2, no. August, pp. 2060–2065, 2012, [Online]. Available: www.ijera.com.
- [49] M. Gupta and S. Kumar, “Multi-objective optimization of cutting parameters in turning using grey relational analysis,” *Int. J. Ind. Eng. Comput.*, vol. 4, no. 4,

- pp. 547–558, 2013, doi: 10.5267/j.ijiec.2013.06.001.
- [50] C. Lin and Z. Shan, “Grid research in China: Origins and directions,” *Proc. - 10th IEEE Int. Work. Futur. Trends Distrib. Comput. Syst.*, no. September 2013, pp. 209–212, 2004, doi: 10.1081/AMP-120029852.
- [51] M. Nalbant, H. Gökkaya, and G. Sur, “Application of Taguchi method in the optimization of cutting parameters for surface roughness in turning,” *Mater. Des.*, vol. 28, no. 4, pp. 1379–1385, 2007, doi: 10.1016/j.matdes.2006.01.008.
- [52] P. J. Liew, A. Shaaroni, J. A. Razak, M. S. Kasim, and M. A. Sulaiman, “Optimization of cutting condition in the turning of AISI D2 steel by using carbon nanofiber nanofluid,” *Int. J. Appl. Eng. Res.*, vol. 12, no. 10, pp. 2243–2252, 2017.
- [53] G. Gul, R. Kumar Mittal, and P. G. Scholar, “Optimization of Turning Process Parameters for Surface Roughness of EN-31 Steel using Taguchi Robust Method,” *Int. J. Creat. Res. Thoughts*, vol. 9, no. 1, pp. 2320–2882, 2021, [Online]. Available: www.ijcrt.org.
- [54] Canyon Hydro *et al.*, “We are IntechOpen , the world ’ s leading publisher of Open Access books Built by scientists , for scientists TOP 1 %,” *Intech*, vol. 32, no. July, pp. 137–144, 2013, [Online]. Available: <http://www.intechopen.com/books/trends-in-telecommunications-technologies/gps-total-electron-content-tec-prediction-at-ionosphere-layer-over-the-equatorial-region%0AInTec%0Ahttp://www.asociatiamhc.ro/wp-content/uploads/2013/11/Guide-to-Hydropower.pdf>.
- [55] A. H. A. Shah, A. I. Azmi, and A. N. M. Khalil, “Grey Relational Analyses for Multi-Objective Optimization of Turning S45C Carbon Steel,” *IOP Conf. Ser. Mater. Sci. Eng.*, vol. 114, no. 1, 2016, doi: 10.1088/1757-899X/114/1/012023.
- [56] E. Nas and N. Altan Özbek, “OPTIMIZATION of the MACHINING PARAMETERS in TURNING of HARDENED HOT WORK TOOL STEEL USING CRYOGENICALLY TREATED TOOLS,” *Surf. Rev. Lett.*, vol. 27, no. 5, 2020, doi: 10.1142/S0218625X19501774.
- [57] R. Fernando, J. Gamage, and H. Karunathilake, “Sustainable machining: environmental performance analysis of turning,” *Int. J. Sustain. Eng.*, vol. 15, no. 1, pp. 15–34, 2022, doi: 10.1080/19397038.2021.1995524.
- [58] M. O. F. Finance, “INDEX OF INDUSTRIAL PRODUCTION es of IIP es of IIP Uses of the IIP The IIP is a key indicator of economic,” pp. 2–5.
- [59] T. News, “UE6110 Excellent stability over a wide range of applications ! UE6110,” 2013.
- [60] ISO 3685, “Norma ISO 3685:1993.” p. 48, 1993.
- [61] S. W. M. A. I. Senevirathne and H. K. G. Punchihewa, “Comparison of tool life and surface roughness with MQL, flood cooling, and dry cutting conditions with P20 and D2 steel,” *IOP Conf. Ser. Mater. Sci. Eng.*, vol. 244, p. 012006, 2017, doi: 10.1088/1757-899x/244/1/012006.
- [62] H. Suresh, B. Rao, B. Venkatesh, T. V. Rao, and K. H. Chandra, “Experimental Investigation on Engine Performance of Diesel Engine Operating on Peanut Seed Oil Biodiesel Blends,” no. May 2014, 2013.

- [63] P. J. Liew, A. Shaaroni, N. A. C. Sidik, and J. Yan, “An overview of current status of cutting fluids and cooling techniques of turning hard steel,” *Int. J. Heat Mass Transf.*, vol. 114, pp. 380–394, 2017, doi: 10.1016/j.ijheatmasstransfer.2017.06.077.
- [64] R. Suresh, S. Basavarajappa, and V. N. Gaitonde, “Experimental studies on the performance of multilayer coated carbide tool in hard turning of high strength low alloy steel,” *J. Mater. Res.*, vol. 30, no. 20, pp. 3056–3064, 2015, doi: 10.1557/jmr.2015.236.
- [65] I. P. Okokpujie, O. S. Ohunakin, C. A. Bolu, and K. O. Okokpujie, “Experimental data-set for prediction of tool wear during turning of Al-1061 alloy by high speed steel cutting tools,” *Data Br.*, vol. 18, no. April, pp. 1196–1203, 2018, doi: 10.1016/j.dib.2018.04.003.
- [66] J. Francis Xavier, B. Ravi, D. Jayabalakrishnan, C. Ezilarasan, V. Jayaseelan, and G. Elias, “Experimental Study on Surface Roughness and Flank Wear in Turning of Nimonic C263 under Dry Cutting Conditions,” *J. Nanomater.*, vol. 2021, pp. 1–12, 2021, doi: 10.1155/2021/2054399.
- [67] M. Kaladhar, K. Venkata Subbaiah, and C. H. Srinivasa Rao, “Optimization of surface roughness and tool flank wear in turning of AISI 304 austenitic stainless steel with CVD coated tool,” *J. Eng. Sci. Technol.*, vol. 8, no. 2, pp. 165–176, 2013.
- [68] S. Debnath, M. M. Reddy, and Q. S. Yi, “Environmental friendly cutting fluids and cooling techniques in machining: A review,” *J. Clean. Prod.*, vol. 83, pp. 33–47, 2014, doi: 10.1016/j.jclepro.2014.07.071.
- [69] R. R. Srikant and V. S. N. V. Ramana, “Performance evaluation of vegetable emulsifier based green cutting fluid in turning of American Iron and Steel Institute (AISI) 1040 steel – an initiative towards sustainable manufacturing,” *J. Clean. Prod.*, vol. 108, pp. 104–109, 2015, doi: 10.1016/j.jclepro.2015.07.031.
- [70] S. Pervaiz, S. Kannan, and H. A. Kishawy, “An extensive review of the water consumption and cutting fluid based sustainability concerns in the metal cutting sector,” *J. Clean. Prod.*, vol. 197, pp. 134–153, 2018, doi: 10.1016/j.jclepro.2018.06.190.
- [71] R. Padmini, P. Vamsi Krishna, and G. Krishna Mohana Rao, “Effectiveness of vegetable oil based nanofluids as potential cutting fluids in turning AISI 1040 steel,” *Tribol. Int.*, vol. 94, pp. 490–501, 2016, doi: 10.1016/j.triboint.2015.10.006.
- [72] P. Akademia Baru, B. S. Kumar, G. Padmanabhan, and P. V. Krishna, “Performance Assessment of Vegetable Oil based Cutting Fluids with Extreme Pressure Additive in Machining,” *J. Adv. Res. Mater. Sci. ISSN*, vol. 19, no. 1, pp. 1–13, 2016.
- [73] T. Y. Woma, S. A. Lawal, A. S. Abdulrahman, M. A. Olutoye, and M. M. Ojapah, “Vegetable oil based lubricants: Challenges and prospects,” *Tribol. Online*, vol. 14, no. 2, pp. 60–70, 2019, doi: 10.2474/trol.14.60.
- [74] A. Astrid, E. Cubillos, and A. E. Delgado-tobón, “Comparative study of the thermal properties of Sesame oil and two mineral oils of different viscosity Estudio comparativo de las propiedades térmicas del aceite de ajonjolí y dos

- aceites minerales de diferente viscosidad,” vol. 15, no. 2, pp. 99–109, 2019.
- [75] R. S. Revuru, N. R. Posinasetti, V. R. Vsn, and M. Amrita, “Application of cutting fluids in machining of titanium alloys—a review,” *Int. J. Adv. Manuf. Technol.*, vol. 91, no. 5–8, pp. 2477–2498, 2017, doi: 10.1007/s00170-016-9883-7.
- [76] W. K. Shafi and M. S. Charoo, “Rheological properties of sesame oil mixed with H-Bn nanoparticles as industrial lubricant,” *Mater. Today Proc.*, vol. 18, pp. 4963–4967, 2019, doi: 10.1016/j.matpr.2019.07.488.
- [77] M. A. Mujtaba *et al.*, “Critical review on sesame seed oil and its methyl ester on cold flow and oxidation stability Critical review on sesame seed oil and its methyl ester on cold flow and oxidation stability,” *Energy Reports*, vol. 6, no. December 2019, pp. 40–54, 2020, doi: 10.1016/j.egy.2019.11.160.
- [78] O. Of, C. For, and B. Millet, “Plant Archives,” vol. 21, no. 1, pp. 1676–1680, 2021.
- [79] A. Resources, “Evaluation of physicochemical , thermal and tribological properties of sesame oil (*Sesamum indicum* L .): a potential agricultural crop base stock for eco-friendly industrial lubricants Sabarinath Sankaran Nair *, Kumarapillai Prabhakaran Nair and Perikin,” vol. 13, no. 1, pp. 77–90, 2017.
- [80] A. T. Hoang and V. T. Nguyen, “Emission characteristics of a diesel engine fuelled with preheated vegetable oil and biodiesel,” *Philipp. J. Sci.*, vol. 146, no. 4, pp. 475–482, 2017.
- [81] J. C. Ahiekpor and K. Polytechnic, “Optimization of factors affecting the production of biodiesel from crude palm kernel oil and ethanol,” *Int. J. Energy Environ.*, vol. 1, no. 4, pp. 675–682, 2010.
- [82] B. Arsene, C. Gheorghe, F. A. Sarbu, M. Barbu, L. I. Cioca, and G. Calefariu, “MQL-assisted hard turning of AISI D2 steel with corn oil: Analysis of surface roughness, tool wear, and manufacturing costs,” *Metals (Basel)*, vol. 11, no. 12, pp. 1–22, 2021, doi: 10.3390/met11122058.
- [83] R. Mallick, R. Kumar, A. Panda, and A. K. Sahoo, “Hard Turning Performance Investigation of AISI D2 Steel under a Dual Nozzle MQL Environment,” *Lubricants*, vol. 11, no. 1, 2023, doi: 10.3390/lubricants11010016.
- [84] A. Radhika, S. R. A, and K. B. Yogesh, “Evaluating machining performance of AISI 1014 steel using gingelly oil as cutting fluid,” *Aust. J. Mech. Eng.*, vol. 00, no. 00, pp. 1–12, 2019, doi: 10.1080/14484846.2019.1636517.
- [85] J. Ni, Z. Cui, C. Wu, J. Sun, and J. Zhou, “Evaluation of MQL broaching AISI 1045 steel with sesame oil containing nano-particles under best concentration,” *J. Clean. Prod.*, vol. 320, no. August, p. 128888, 2021, doi: 10.1016/j.jclepro.2021.128888.
- [86] M. Nalbant, H. Gökkaya, I. Toktaş, and G. Sur, “The experimental investigation of the effects of uncoated, PVD- and CVD-coated cemented carbide inserts and cutting parameters on surface roughness in CNC turning and its prediction using artificial neural networks,” *Robot. Comput. Integr. Manuf.*, vol. 25, no. 1, pp. 211–223, 2009, doi: 10.1016/j.rcim.2007.11.004.
- [87] W. H. Yang and Y. S. Tarn, “Design optimization of cutting parameters for turning operations based on the Taguchi method,” *J. Mater. Process. Technol.*,

- vol. 84, no. 1–3, pp. 122–129, 1998, doi: 10.1016/S0924-0136(98)00079-X.
- [88] H. Akkuş and H. Yaka, “Optimization of Cutting Parameters in Turning of Titanium Alloy (Grade 5) by Analysing Surface Roughness, Tool Wear and Energy Consumption,” *Exp. Tech.*, vol. 46, no. 6, pp. 945–956, 2022, doi: 10.1007/s40799-021-00525-6.
- [89] C. Camposeco-Negrete, “Optimization of cutting parameters for minimizing energy consumption in turning of AISI 6061 T6 using Taguchi methodology and ANOVA,” *J. Clean. Prod.*, vol. 53, pp. 195–203, 2013, doi: 10.1016/j.jclepro.2013.03.049.
- [90] I. Deiab, S. W. Raza, and S. Pervaiz, “Analysis of lubrication strategies for sustainable machining during turning of titanium ti-6al-4v alloy,” *Procedia CIRP*, vol. 17, pp. 766–771, 2014, doi: 10.1016/j.procir.2014.01.112.
- [91] R. R. Srikant and V. S. N. V. Ramana, “Performance evaluation of vegetable emulsifier based green cutting fluid in turning of American Iron and Steel Institute (AISI) 1040 steel – an initiative towards sustainable manufacturing,” *J. Clean. Prod.*, vol. 108, no. May, pp. 104–109, 2015, doi: 10.1016/j.jclepro.2015.07.031.
- [92] D. D. Trung *et al.*, “Optimization Study on Turning Process by Using Taguchicopras Method,” *E3S Web Conf.*, vol. 309, 2021, doi: 10.1051/e3sconf/202130901010.
- [93] H. K. Dave, L. S. Patel, and H. K. Raval, “Effect of machining conditions on MRR and surface roughness during CNC turning of different materials using TiN coated cutting tools - A taguchi approach,” *Int. J. Ind. Eng. Comput.*, vol. 3, no. 5, pp. 925–930, 2012, doi: 10.5267/j.ijiec.2012.04.005.
- [94] R. Aryan, F. John, S. Kumar, and A. Kumar, “Optimization of Turning Parameters of AL-Alloy 6082 using Taguchi Method,” *Int. J. Adv. Res. Innov.*, vol. 5, no. 2, pp. 193–206, 2017, doi: 10.51976/ijari.521733.
- [95] M. S. Siddique, M. N. Akhtar, M. W. Iqbal, N. Beg, and M. Z. Haq, “TURNING PARAMETER OPTIMIZATION FOR MATERIAL REMOVAL RATE OF AISI 4140Alloy STEEL BY TAGUCHI METHOD,” *Int. Res. J. Eng. Technol.*, vol. 4, no. 6, pp. 848–854, 2017, [Online]. Available: <https://irjet.net/archives/V4/i6/IRJET-V4I6155.pdf>.
- [96] S. Kumar, B. S. Pabla, and J. Madan, “Optimization of Machining Parameters in Turning EN-45 Steel Using Plain Carbide Tools,” *Int. J. Sci. Res. Sci. Technol.*, vol. 3, no. 6, pp. 37–43, 2017.