



**PREDICTING THE END BEARING CAPACITY OF
ROCK-SOCKETED BORED AND CAST IN-SITU PILES
IN SRI LANKAN METAMORPHIC ROCK USING
ROCK MASS PROPERTIES**

Roshan Sameera Ruwanpathirana

198353F

Thesis submitted in partial fulfillment of the requirements for the degree
Master of Science in Geotechnical Engineering

Department of Civil Engineering
Faculty of Engineering



April 2024

TH 5600
+

CD ROM

624 "2024"

624-13(043)

TH 5600

DECLARATION

I declare that this is my own work and this thesis does not incorporate without acknowledgement any material previously submitted for a degree or diploma in any other University or Institute of higher learning and to the best of my knowledge and belief it does not contain any material previously published or written by another person except where the acknowledgement is made in the text. I retain the right to use this content in whole or part in future works (such as articles or books).

Signature:

UOM Verified Signature

Date: 07/05/2024

The above candidate has carried out research for the Masters thesis under my supervision. I confirm that the declaration made above by the student is true and correct.

Name of Supervisor: Prof. U G A Puswewala

Signature of the Supervisor

UOM Verified Signature

Date: 07/05/2024

DEDICATION

I dedicate this research project report to,

My research project supervisor, Prof. U G A Puswewala

Senior Lecturer and former Head of the Department of Civil Engineering, Open University of Sri Lanka, Eng. M.N.C. Samarawickrama

Former Head of the Department of Civil Engineering, Prof. S A S Kulathilaka,

MSc. research project coordinator, Prof. L.I.N. de Silva and other staff members of the Civil Engineering Department, University of Moratuwa.

To all the students, authorities and researchers who are interested in the field of geotechnical engineering and who are benefited from this research finding

ACKNOWLEDGEMENT

I would like to acknowledge and extend my heartfelt gratitude to the following personnel who helped me in various ways to complete this research project;

Project supervisor Prof. U G A Puswewala, for the constant reminders, much needed motivation, vital encouragement and support provided throughout the period.

Senior Lecturer and former Head of the Department of Civil Engineering, Open University of Sri Lanka, Eng. M.N.C. Samarawickrama for the support provided, motivation and encouragement given throughout the period.

Former Head of the Department of Civil Engineering, Prof. S A S Kulathilaka for his guidance extended.

MSc. research project coordinator, Prof. L.I.N. de Silva and other staff members of the Department of Civil Engineering, University of Moratuwa. for their guidance.

Officials of Library, University of Moratuwa for their support when purchasing related research papers.

Academic and Nonacademic staff of the Department of Civil Engineering for the support given.

ABSTRACT

Rock socketed end bearing cast in situ bored (CIB) piles are currently among the most widely used types of deep foundations in Sri Lanka to transfer the superstructure load into the competent bedrock. However, deliberations are going on whether the pile designers maximize the advantage on locally available higher-strength-less deformable metamorphic rock characteristics during the design of CIB piles. In this study, appropriateness of commonly used end bearing capacity estimation methods in the design of rock socketed CIB piles are briefly reviewed and then the results obtained through these methods are compared against the actual end bearing capacity levels obtained from pile static load test data. Locally available static pile load test data do not facilitate direct estimation of actual ultimate end bearing capacity values due to non-continuation of pile load tests beyond the required pile capacity limits caused by practical and economic reasons. Therefore, load-settlement curve extrapolation methods proposed by Chin- Kondner (1978), Brinch Hansen (1963) and Decourt (1999), were used in this study to determine the ultimate carrying capacities of piles. It is found that the ultimate carrying capacity values obtained from Chin- Kondner (1978) and Decourt (1999) methods are in a similar range while values obtained from Brinch Hansen (1963) are far below from other two methods. Moreover, the Hong Kong Guidelines (HKG) method which has been developed based on Rock Mass Rating (RMR), seems reasonable to estimate of the allowable end bearing capacity of the bedrock corresponding to a settlement of less than 0.5% of the pile diameter. However, HKG method can be used only in instances where RMR value of rock strata is exceeds 40. In order to facilitate locally available high-strength rock terrain conditions, a more appropriate new empirical relationship between RMR and allowable end bearing capacity of rock socketed pile was introduced and the accuracy of the relationship was verified using limited available instrumented pile load test data. It was further noted that this relationship performs well in rock masses with RMR greater than 20.

Keywords: Cast in situ bored piles, load-settlement curve extrapolation, End bearing capacity, RMR

TABLE OF CONTENTS

Declaration	i
Dedication	ii
Acknowledgement.....	iii
Abstract	iv
Table of Contents	v
List of Figures	viii
List of Tables.....	ix
List of Abbreviations.....	xii
List of Appendices	xiii
Chapter 1	1
Introduction.....	1
1.1 General Introduction.....	1
1.2 Significance of the research.....	2
1.3 Objectives of the research	2
Chapter 2	3
LITERATURE REVIEW.....	3
2.1 Introduction	3
2.2 Load transfer mechanisms of piles.....	4
2.3 Estimation of geotechnical carrying capacity of rock socketed end bearing piles with established equations and codes of practice	5
2.3.1 Estimation of ultimate skin friction of soil	6
2.3.2 Estimation of ultimate skin friction of rock	7
2.3.3 Estimation of the allowable and ultimate end bearing capacity in rock	10
2.3.4 Estimation of settlement of a single pile at working load.....	16
2.4 Estimation of geotechnical carrying capacity of rock socketed end bearing piles using pile load test data	17
2.4.1 Pile load tests	17
2.4.2 Interpretation of Static Load Test Results.....	20
2.5 Engineering properties of intact and rock mass	25
2.5.1 Difference between intact rock and rock mass	25

2.5.2	Engineering properties of intact rock	26
2.5.3	Engineering properties of rock mass	32
Chapter 3	40
METHODOLOGY	40
3.1	Collect pile static load test results and relevant geotechnical investigation data	41
3.2	Estimate the ultimate and allowable carrying capacities of piles by established equations and codes of practice methods	41
3.2.1	Estimation of the ultimate skin friction in soil	41
3.2.2	Estimation of the ultimate skin friction in rock socket	43
3.2.3	Estimation of the allowable and ultimate end bearing capacity in rock by established equations and codes of practice methods	45
3.3	Estimate the ultimate carrying capacities of piles using load-settlement test results	47
3.3.1	Estimation of ultimate skin friction of piles using load-settlement relationship	47
3.3.2	Estimation of ultimate carrying capacity of piles by extrapolation of load-settlement curves	49
3.3.3	Estimation of ultimate end bearing capacity of piles based on pile load test data	53
3.3.4	Estimation of allowable end bearing capacity of piles based on pile load test data	54
3.4	Engineering Rock Mass Classifications	56
Chapter 4	59
RESULTS AND DISCUSSION	59
4.1	Appropriateness of the extrapolation methods used in end bearing capacity estimation of piles	59
4.2	Appropriateness of the existing established equations and codes of practice used in end bearing capacity estimation of piles	60
4.3	Development of a new relationship between allowable end bearing capacity of piles and RMR value of rock strata for metamorphic rock sockets	63
4.4	Verification of the developed solutions through instrumented pile load test results	64
4.4.1	Estimation of RMR value for case 14	64

4.4.2 Estimation of allowable end bearing pressure using proposed relationship	66
4.4.3 Estimation of pile bottom settlement corresponding to the calculated allowable bearing pressure under section 4.4.2	67
4.4.4 Comparison of calculated end bearing pressure with instrumented pile load test data of case 14	68
Chapter 5	69
CONCLUSIONS AND RECOMMENDATIONS	69
5.1 Conclusions	69
5.2 Recommendations	70
References	71
Appendix - A	73
Appendix - B	79
Appendix - C	1
Appendix - D	15



LIST OF FIGURES

Figure	Description	Page
Fig. 2.1	Load Transfer Mechanism of Axially Loaded Piles [3]	3
Fig. 2.2	Load-transfer curves of single pile. [4]	4
Fig. 2.3	Relationship between the adhesion factor a and undrained shear strength [2]	6
Fig. 2.4	Relationship between Z_{cd} and ϕ_0 for piles in sand [6]	7
Fig. 2.5	UCS vs modified shaft resistance in rock socket proposed by HKG [8]	8
Fig. 2.6	Reduction factors for rock socket shaft friction [10]	9
Fig. 2.7	Reduction factors for discontinuities in rock mass [10]	10
Fig. 2.8	Allowable end bearing capacity for igneous and metamorphic rock proposed by BS 8004 [12] and quoted by [7]	11
Fig. 2.9	Relationship between RMR and allowable bearing pressure given by HKG [08]	12
Fig. 2.10	Relationship between RQD and allowable bearing capacity on a jointed rock mass. [8]	13
Fig. 2.11	Analysis of bearing capacity on rock by Goodman [15]	14
Fig. 2.12	Wedge bearing capacity factors for foundation on rock, quoted by Tomlinson [10]	15
Fig. 2.13	Linear Relationship between SP vs s	21
Fig. 2.14	Distinct segments in the load-settlement curve proposed by Van Weele in 1957 [2]	22
Fig. 2.15	Shape of load vs settlement curve assumed as hyperbolic	23
Fig. 2.16	Obtained straight line by plotting S vs \sqrt{SP}	24
Fig. 2.17	Linear Relationship between PS vs P	25
Fig. 2.18	Transition from intact rock to jointed rock mass with increasing sample size [24]	26
Fig. 2.19	Procedure for measurement and calculation of RQD [28]	33
Fig. 2.20	Relationship between Deformation Modulus and RMR for a Jointed Rock Mass [31]	39
Fig. 3.1	The flow diagram of the methodology	40
Fig. 3.2	Plotted graph SP vs S	47
Fig. 3.3	Estimation of P_{su} , Van Weele using S vs P graph	48

Fig. 3.4	Plotted graph the SP ratio vs S for ultimate carrying capacity (P_u , chin)	49
Fig. 3.5	Plotted graph for the \sqrt{SP} ratio vs S	50
Fig. 3.6	Plotted graph PS ratio vs P	51
Fig. 3.7	Ultimate carrying capacity obtained from pile load test results	52
Fig. 3.8	Comparison of ultimate skin friction values	53
Fig. 4.1	Comparison of results of ICTAD, HKG and Peck et al (1974) methods with the allowable bearing pressure values obtained from pile load test data.	60
Fig. 4.2	Comparison of results of Goodman (1980) and Kulhawy & Goodman (1987) methods with the allowable bearing pressure values obtained from pile load test data.	61
Fig. 4.3	Proposed relationship between RMR and allowable bearing pressure of rock strata	63

LIST OF TABLES

Table	Description	Page
Table 2.1	Estimation of Mass factor (J) from RQD and fracture frequency (FI)	9
Table 2.2	Recommended allowable bearing pressure based on RMR value by HKG[8]	12
Table 2.3	Relationship between ultimate bearing pressure of piles, UCS of the intact rock and the RQD of the rock mass	15
Table 2.4	Minimum global safety factors used in rock socketed piles [8]	16
Table 2.5	Table 2.5: Load Increment and load maintain time period (for working piles) [17]	18
Table 2.6	Load Increment and load maintain time period (for non-working piles) [17]	19
Table 2.7	Bulk density and porosity for different weathered grades of metamorphic rocks in Sri Lanka [25]	26
Table 2.8	Typical range of unconfined compressive strength of intact rocks [23]	27
Table 2.9	Correlations between unconfined compressive strength σ_c and point load index Is_{50} (Quoted from Zhang [23])	28
Table 2.10	Typical values of elastic modulus of intact rocks [23]	30
Table 2.11	Empirical correlation between Elastic Modulus (E) and Unconfined Compressive Strength (σ_c) (Quoted from Zhang [23])	30
Table 2.12	Typical values of Poisson's ratio of intact rocks [23]	31

Table 2.13	Engineering classification of intact rock based on strength (as quoted by Zhang [23] from ISRM, 1978c)	31
Table 2.14	Major rock mass classification systems (Quoted from Cosar [27])	32
Table 2.15	Correlation between RQD and rock mass quality [28]	34
Table 2.16	RMR classification parameters and their rating as quoted by HKG [8], from Bieniawski [13]	35
Table 2.17	Relationship between the RMR and the rock mass quality	36
Table 2.18	Empirical correlations for estimating rock mass unconfined compressive strength (σ_{cm}) (As quoted by [23])	36
Table 2.19	Empirical relationships to estimate rock mass deformation modulus (E_m) [23]	37
Table 3.1	Data Collection Projects and locations	41
Table 3.3	Calculation of ultimate unit skin friction (overburden soil) of the case 04	42
Table 3.4	Adjacent borehole data (Rock) of the case 04	43
Table 3.5	Calculation of ultimate skin frictional resistance (Rock) of the case 04	44
Table 3.6	Summary of theoretically estimated ultimate frictional resistance of piles	44
Table 3.7	Estimation of the theoretical allowable end bearing capacity in rock	45
Table 3.8	Estimation of the theoretical ultimate end bearing capacity in rock	45
Table 3.9	Weighted average of allowable and ultimate pressure of bearing strata	46
Table 3.10	Summary of theoretically estimated allowable and ultimate bearing capacities	46
Table 3.11	Estimated ultimate carrying capacity of piles based on different extrapolation methods.	52
Table 3.12	Estimated ultimate end bearing capacity of rock based on pile load test results	54
Table 3.13	Estimated stress to give a settlement correspond to 0.5% of the pile diameter	55
Table 3.14	Estimated FOS to $q_{b,0.5s}$	55
Table 3.15	Parameters for Rock Mass Classification	56
Table 3.16	RMR estimation for layer 04	56
Table 3.17	RMR estimation for layer 05	57
Table 3.18	RMR estimation for layer 06	57
Table 3.19	RMR Estimation for bearing strata of case 04	58

Table 3.20 RMR Estimation for bearing strata of all cases	58
Table 4.1 Estimated allowable bearing pressure (q_a)	59
Table 4.2 Comparison of allowable bearing pressure with IMLT test results	60
Table 4.3 Estimated allowable bearing capacities from Goodman (1980) and Kulhawy and Goodman (1987)	61
Table 4.4 RMSE estimated from allowable end bearing from rational equations against the allowable end bearing estimated from pile load test data.	62
Table 4.5 Parameters for Rock Mass Classification (Case 14)	64
Table 4.6 RMR estimation for layer 05	64
Table 4.7 RMR estimation for layer 06	65
Table 4.8 RMR estimation for layer 07	65
Table 4.9 RMR Estimation for bearing strata of case 14	66
Table 4.10 Comparison of calculated end bearing pressure with instrumented pile load test data of case 14	68

LIST OF ABBREVIATIONS

Abbreviation	Description
CIB	Cast In situ Bored
HKG	Hong Kong Guidelines
RMR	Rock Mass Rating
ICTAD	Institute for Construction Training and Development
UCS	Uniaxial Compressive Strength
RQD	Rock Quality Designation
CR	Core Recovery
PDA	Pile Driving Analyzer
CRP	Constant Rate of Penetration
ML	Maintained Load
DVL	Design Verification Load
SWL	Specified Working Load
RMSE	Root mean Square Error

LIST OF APPENDICES

Appendix	Description	Page
Appendix - A	Summary of Site Investigation Data	73
Appendix - B	Estimation of the Ultimate Skin Friction in Soil and Rock Socket	79
Appendix - C	Estimation of The Ultimate Carrying Capacity of Piles	98
Appendix - D	Unit End Bearing Vs Pile Toe Settlement (Instrument load test result-Case No 14)	112