

REFERENCES

- [1] J. Vivancos, C. J. Luis, L. Costa, and J. A. Ortíz, “Optimal machining parameters selection in high speed milling of hardened steels for injection moulds,” *J. Mater. Process. Technol.*, vol. 155–156, pp. 1505–1512, Nov. 2004, doi: 10.1016/j.jmatprotec.2004.04.260.
- [2] G. M. Kim, B. H. Kim, and C. N. Chu, “Estimation of cutter deflection and form error in ball-end milling processes,” *Int. J. Mach. Tools Manuf.*, vol. 43, no. 9, pp. 917–924, Jul. 2003, doi: 10.1016/S0890-6955(03)00056-7.
- [3] A. Lamikiz, L. N. López de Lacalle, J. A. Sánchez, and M. A. Salgado, “Cutting force estimation in sculptured surface milling,” *Int. J. Mach. Tools Manuf.*, vol. 44, no. 14, pp. 1511–1526, Nov. 2004, doi: 10.1016/j.ijmachtools.2004.05.004.
- [4] A. J. de Oliveira and A. E. Diniz, “Tool life and tool wear in the semi-finish milling of inclined surfaces,” *J. Mater. Process. Technol.*, vol. 209, no. 14, pp. 5448–5455, Jul. 2009, doi: 10.1016/j.jmatprotec.2009.04.022.
- [5] S. Wojciechowski, M. Wiackiewicz, and G. M. Krolczyk, “Study on metrological relations between instant tool displacements and surface roughness during precise ball end milling,” *Measurement*, vol. 129, pp. 686–694, Dec. 2018, doi: 10.1016/j.measurement.2018.07.058.
- [6] D. Przystacki, T. Chwalczuk, and S. Wojciechowski, “The study on minimum uncut chip thickness and cutting forces during laser-assisted turning of WC/NiCr clad layers,” *Int. J. Adv. Manuf. Technol.*, vol. 91, no. 9–12, pp. 3887–3898, Aug. 2017, doi: 10.1007/s00170-017-0035-5.
- [7] D. Ulutan and T. Özel, “Determination of tool friction in presence of flank wear and stress distribution based validation using finite element simulations in machining of titanium and nickel based alloys,” *J. Mater. Process. Technol.*, vol. 213, no. 12, pp. 2217–2237, Dec. 2013, doi: 10.1016/j.jmatprotec.2013.05.019.
- [8] R. Kumar, S. Chattopadhyaya, S. Hloch, G. Krolczyk, and S. Legutko, “Wear characteristics and defects analysis of friction stir welded joint of aluminium alloy 6061-T6,” *Ekspolatacja Niezawodn. - Maint. Reliab.*, vol. 18, no. 1, pp. 128–135, Jan. 2016, doi: 10.17531/ein.2016.1.17.
- [9] B. Kecelj, J. Kopač, Z. Kampuš, and K. Kuzman, “Speciality of HSC in manufacturing of forging dies,” *J. Mater. Process. Technol.*, vol. 157–158, pp. 536–542, Dec. 2004, doi: 10.1016/j.jmatprotec.2004.07.112.
- [10] L. N. López de Lacalle, A. Lamikiz, J. A. Sánchez, and M. A. Salgado, “Effects of tool deflection in the high-speed milling of inclined surfaces,” *Int. J. Adv. Manuf. Technol.*, vol. 24, no. 9–10, pp. 621–631, Nov. 2004, doi: 10.1007/s00170-003-1723-x.
- [11] L. N. L. De Lacalle, A. Lamikiz, M. A. Salgado, S. Herranz, and A. Rivero, “Process planning for reliable high-speed machining of moulds,” *Int. J. Prod. Res.*, vol. 40, no. 12, pp. 2789–2809, Jan. 2002, doi: 10.1080/00207540210140068.

- [12] S.-H. Suh, J.-H. Cho, and J.-Y. Hascoet, “Incorporation of tool deflection in tool path computation: Simulation and analysis,” *J. Manuf. Syst.*, vol. 15, no. 3, pp. 190–199, Jan. 1996, doi: 10.1016/0278-6125(96)89571-9.
- [13] M. A. Salgado, L. N. López de Lacalle, A. Lamikiz, J. Muñoa, and J. A. Sánchez, “Evaluation of the stiffness chain on the deflection of end-mills under cutting forces,” *Int. J. Mach. Tools Manuf.*, vol. 45, no. 6, pp. 727–739, May 2005, doi: 10.1016/j.ijmachtools.2004.08.023.
- [14] L. N. López de Lacalle, A. Lamikiz, J. A. Sánchez, and J. L. Arana, “Improving the surface finish in high speed milling of stamping dies,” *J. Mater. Process. Technol.*, vol. 123, no. 2, pp. 292–302, Apr. 2002, doi: 10.1016/S0924-0136(02)00102-4.
- [15] Á. R. Machado and A. E. Diniz, “Tool wear analysis in the machining of hardened steels,” *Int. J. Adv. Manuf. Technol.*, vol. 92, no. 9–12, pp. 4095–4109, Oct. 2017, doi: 10.1007/s00170-017-0455-2.
- [16] D. A. Stephenson, “Metal Cutting Theory and Practice”.
- [17] M. L. Polli, “para a obtenção do grau de”.
- [18] Y. Altintas, *Manufacturing automation: metal cutting mechanics, machine tool vibrations, and CNC design*, 2nd ed. Cambridge ; New York: Cambridge University Press, 2012.
- [19] Y. Gao, R. Sun, and J. Leopold, “Analysis of Cutting Stability in Vibration Assisted Machining Using Ananalytical Predictive Force Model,” *Procedia CIRP*, vol. 31, pp. 515–520, 2015, doi: 10.1016/j.procir.2015.03.014.
- [20] J. Fleischer *et al.*, “The Influence of Tool Holder Technologies on Milling Performance,” *Procedia CIRP*, vol. 46, pp. 226–229, 2016, doi: 10.1016/j.procir.2016.03.183.
- [21] G. S. Duncan, M. F. Tummond, and T. L. Schmitz, “An investigation of the dynamic absorber effect in high-speed machining,” *Int. J. Mach. Tools Manuf.*, vol. 45, no. 4–5, pp. 497–507, Apr. 2005, doi: 10.1016/j.ijmachtools.2004.09.005.
- [22] P. Fallböhmer, C. A. Rodríguez, T. Özel, and T. Altan, “High-speed machining of cast iron and alloy steels for die and mold manufacturing,” *J. Mater. Process. Technol.*, vol. 98, no. 1, pp. 104–115, Jan. 2000, doi: 10.1016/S0924-0136(99)00311-8.
- [23] J.-S. By Chen, Y.-K. Huang, and M.-S. Chen, “Feedrate optimization and tool profile modification for the high-efficiency ball-end milling process,” *Int. J. Mach. Tools Manuf.*, vol. 45, no. 9, pp. 1070–1076, Jul. 2005, doi: 10.1016/j.ijmachtools.2004.11.020.
- [24] P. G. Benardos and G.-C. Vosniakos, “Predicting surface roughness in machining: a review,” *Int. J. Mach. Tools Manuf.*, vol. 43, no. 8, pp. 833–844, Jun. 2003, doi: 10.1016/S0890-6955(03)00059-2.

- [25] A. E. Diniz, J. R. Ferreira, and J. F. Silveira, "Toroidal milling of hardened SAE H13 steel," *J. Braz. Soc. Mech. Sci. Eng.*, vol. 26, no. 1, pp. 17–21, Mar. 2004, doi: 10.1590/S1678-58782004000100003.
- [26] A. Joshi and P. Kothiyal, "Investigating Effect of Machining Parameters of CNC Milling on Surface Finish by Taguchi Method," vol. 1, no. 2.
- [27] N. S. Kumar, A. Shetty, A. Shetty, A. K., and H. Shetty, "Effect of Spindle Speed and Feed Rate on Surface Roughness of Carbon Steels in CNC Turning," *Procedia Eng.*, vol. 38, pp. 691–697, 2012, doi: 10.1016/j.proeng.2012.06.087.
- [28] F. Dweiri, M. Al-Jarrah, and H. Al-Wedyan, "Fuzzy surface roughness modeling of CNC down milling of Aluminic-79," *J. Mater. Process. Technol.*, vol. 133, no. 3, pp. 266–275, Feb. 2003, doi: 10.1016/S0924-0136(02)00847-6.
- [29] "Mathematical Modeling to Predict Surface Roughness in CNC Milling," vol. 3, no. 5, 2009.
- [30] M. M. de Aguiar, A. E. Diniz, and R. Pederiva, "Correlating surface roughness, tool wear and tool vibration in the milling process of hardened steel using long slender tools," *Int. J. Mach. Tools Manuf.*, vol. 68, pp. 1–10, May 2013, doi: 10.1016/j.ijmachtools.2013.01.002.
- [31] P.G. Benardos, G.C. Vosniakos, "Prediction of surface roughness in CNC face milling using neural networks and Taguchi's design of experiments," 2002
- [32] A. Mahyar Khorasani, M. Reza Soleymani Yazdi, Mir Saeed Safizadeh "Analysis of machining parameters effects on surface roughness: a review" *Int. J. Computational Materials Science and Surface Engineering*, Vol. 5, No. 1, 2012
- [33] S. Luo, "Toolpath and Cutter Orientation Optimization in 5-Axis CNC Machining of Free-form Surfaces Using Flat-end Mills," 2015.
- [34] Sh.Shajari, "Influence of machining strategies on surface roughness in ball end," *Advanced Materials Research*, pp. 836-840, 2012.