

LB/TH/44/2025

TH6022

**HEADWAY DISTRIBUTION ON URBAN ROADS
UNDER HETEROGENEOUS TRAFFIC CONDITION**

Yahampath Arachchige Pasan Madura

189282J

Degree of Master of Engineering

Department of Civil Engineering

University of Moratuwa

Sri Lanka

December 2023

HEADWAY DISTRIBUTION ON URBAN ROADS UNDER HETEROGENEOUS TRAFFIC CONDITION

Yahampath Arachchige Pasan Madura

189282J

Dissertation submitted in partial fulfillment of the requirements for the
degree Master of Science/ Master of Engineering in Highway and Traffic
Engineering

Department of Civil Engineering

University of Moratuwa
Sri Lanka

December 2023

DECLARATION OF THE CANDIDATE AND SUPERVISOR

“I declare that this is my own work and this thesis/dissertation does not incorporate without acknowledgement any material previously submitted for a degree or Diploma in any other University or institute of higher learning and to the best of my knowledge and belief it does not contain any material previously published or written by another person except where the acknowledgement is made in the text.

Also, I hereby grant to University of Moratuwa the non-exclusive right to reproduce and distribute my thesis/dissertation, in whole or in part in print, electronic or other medium. I retain the right to use this content in whole or part in future works (such as articles or books).

Signature:

Date: December 2023

The above candidate has carried out research for the Masters/MPhil/PhD thesis/
Dissertation under my supervision.

Name of the supervisor: Prof. J.M.S Bandara

Signature of the supervisor:

Date: Dcember 2023

ABSTRACT

This study examines time headway distributions on urban roads in Sri Lanka, emphasizing the impact of heterogeneous traffic conditions. Headway, which refers to the temporal gaps or spacing between consecutive vehicles on the road, plays a pivotal role in shaping traffic flow behaviors level of service, and safety standards, making its understanding critical for effective traffic management and urban planning as a microscopic parameter offering insights into macroscopic traffic behaviors. This parameter finds application in capacity analysis, safety evaluations, accident investigations, car-following behavior models, and lane-change propensity studies.

The problem lies in the lack of comprehensive research on headway distribution in urban traffic settings marked by significant heterogeneity. The prevailing focus on homogeneous traffic conditions in conventional traffic research, often limited to low and medium flow situations within lane-based vehicle flow scenarios. However, urban road networks in Sri Lanka frequently encounter highly diverse traffic conditions due to the presence of diverse vehicle types like three-wheelers, motorbikes, mini-lorries, buses, and heavy vehicles, each with varying physical attributes, axle configurations, weight distributions, power ratios, varying driver behaviors, and multitude road users. Moreover, road discipline issues and truncated inter-vehicle distances due to aggressive driving further complicate traffic analysis.

The primary aim is to determine appropriate distribution models for various traffic flow ranges and leader-follower pairs on different road segments and rigorously evaluate their statistical validity through a range of goodness-of-fit tests.

The data collection involves videographic surveys to capture headway data from selected road sections. The selection process for these road sections involves considering several crucial factors, such as the absence of side hindrances (e.g., parking lots, gradients, bus stops, intersections), the straight and flat nature of the road, the availability of ample shoulder space, favorable weather conditions, good visibility, Optimal driving surface, geometric and functional homogeneity for at least 1 kilometer upstream and downstream. Selected road sections are A004 road at Pannipitiya, A001 road at Kegalla, Marine Drive at Wellawatta and AB -042 road at Hirasagala. For each road section videographic surveys were carried out at three peaks periods during the day, namely from 7.00-9.00 am, from 12.00-2.00 pm and from 4.00-6.00 pm, which were identified during the initial observations of the road sections and also based on the findings of the literature review. Each time interval was sub divided into 15 min intervals in order to identify the variation of flow and calculate the flow rates. Sub-time intervals were defined in such a manner that sample size (number of headways) was large enough for all flow ranges. Time stamps during the entry of the front bumper, vehicle type and speed of each vehicle were extracted from video recordings manually by image processing using software “Traffic Extractor” developed by IIT Bombay to compute time headways. Accordingly, headways between subsequent vehicles were established by the time gap between the entry times of front bumpers of successive vehicles. A total of 24,201 time headways were collected through the data collection.

The analytical framework encompasses two scenarios: studying headway variations across diverse traffic flow conditions and exploring headway data for different leader-follower pairs. The data is categorized into three flow ranges—below 400 veh/hr. indicating free-flowing conditions (Level of Service A and B), 400 to 1200 veh/hr. representing moderate flow with some restrictions (Level C), and above 1200 veh/hr. denoting highly congested conditions with reduced speeds and potential stoppages (Level D and E) based on computed flow rates. Frequency and cumulative frequency distributions are constructed for each flow range and road section.

Distribution model selection relies on established empirical models, with goodness-of-fit assessments carried out using the Anderson-Darling test, Kolmogorov-Smirnov (K-S) test and chi-square test. Statistical tools such as Easy Fit, NCSS, and SPSS aid in these evaluations. The K-S and Anderson-Darling tests assess the fitness of theoretical distribution models to observed data by comparing cumulative distribution functions, with the chosen model yielding the least discrepancy as the best fit.

Easy Fit software aids in conducting these tests, and rejection of the null hypothesis occurs if calculated statistics surpass critical values at a chosen significance level. The study examines various flow ranges across different road sections and tests the goodness-of-fit of several distributions, including Generalized Extreme Value, Johnson SU, Pearson, Generalized Gamma, Beta, and Burr.

In conclusion, the research findings suggest that the "General Extreme Value" distribution consistently emerges as a strong and versatile candidate for describing traffic flow behavior in the flow range below 400 veh/h. For flow rates between 400 and 1200 veh/h, the Gen. Gamma (4P) distribution proves to be the most suitable choice. In the flow range above 1200 veh/h, the Gen. Gamma distribution also performs well. Moreover, the study reveals varying degrees of variability, skewness, and kurtosis in leader-follower relationships across different vehicle classes, indicating the need for tailored approaches to traffic management and safety analysis.

The research contributes to a deeper understanding of headway behavior in diverse traffic scenarios, offering practical implications for transportation engineering and management, safety analysis, and infrastructure planning. It underscores the importance of tailoring headway distribution models to specific traffic conditions and vehicle relationships, providing valuable insights for traffic management and infrastructure planning in Sri Lanka and similar urban environments.

ACKNOWLEDGEMENTS

I deeply appreciate the Transport Engineering Division of Department of Civil Engineering, University of Moratuwa for granting me the opportunity to carry out my research and for their invaluable support, which played a pivotal role in the successful completion of my research.

Moreover, I wish to convey my heartfelt gratitude to Professor. J.M.S.J. Bandara for his continuous guidance, invaluable advice and his willingness for insightful discussions that greatly enriched the journey of my research. Furthermore, I wish to extend my sincere gratitude to Professor. H.R. Pasindu for his guidance and support throughout the research.

I gratefully acknowledge all the helpful technical suggestions and advices provided by the panel of examiners at the progress reviews.

I wish to thank other lecturers of the transport engineering division for their advices, guidance and support during the research time period.

Also support given by fellow research assistants, technical officers and non-academic staff of the transport division is greatly appreciated.

CONTENT

DECLARATION OF THE CANDIDATE AND SUPERVISOR.....	i
ABSTRACT.....	ii
ACKNOWLEDGEMENTS	iv
CONTENT	v
LIST OF FIGURES	ix
LIST OF TABLES	xii
LIST OF ABBREVIATIONS	xv
LIST OF APPENDICES	xvi
1. CHAPTER.....	1
INTRODUCTION.....	1
1.1. Background	1
1.2. Problem Statement	2
1.3. Objectives	3
1.4. Research Approach.....	4
2. CHAPTER	5
LITERATURE SURVEY	5
2.1. Introduction to Headway	5
2.2. History of Headway Analysis.....	5
3. CHAPTER	15
METHODOLOGY.....	15
3.1. Data Collection.....	15
3.1.1. Factors considered for selecting suitable location for data collection .	15
3.1.2. Assumptions and Considerations for Data Collections.....	15
3.1.3. Identified locations for data collection.....	15
3.1.4. Nature of identified road sections	15

3.1.5.	Nature of vehicular traffic at selected road sections	16
3.1.6.	Observations at road sections.....	17
3.1.7.	Duration and Frequency of Data collection	17
3.1.8.	Data collection using Video graphic technique	17
3.1.9.	Extraction of video recordings data using Software Tool.....	17
3.1.10.	Extraction of video recordings data and determination of headways 19	
3.2.	Headway data analysis	20
3.2.1.	Analyze variation of headway under different traffic flow conditions.	20
3.2.2.	Identification of suitable time sub intervals	20
3.2.3.	Calculation of vehicular flow rates	20
3.2.4.	Classification of Sub-Time Intervals Having Similar Flow Rates.....	20
3.2.5.	Defining Traffic Flow Ranges	20
3.2.6.	Developing Time Headway Samples for each Flow Range.....	21
3.2.7.	Developing Frequency Distribution for each flow Range	22
3.2.8.	Developing cumulative frequency distribution for each flow range....	22
3.2.9.	Analyze headway data based on different leader-follower pairs.	22
3.2.10.	Identification of suitable vehicle types based on axel configuration	22
3.2.11.	Development of Leader-Follower pair combinations	22
3.2.12.	Development of time headway samples for each Leader-Follower pair 23	
3.2.13.	Development of frequency distributions for each Leader-Follower pair 23	
3.2.14.	Development of cumulative frequency distributions for each Leader-Follower pair	23
3.3.	Headway Distribution Modeling	23
3.3.1.	Develop Probability Density Function for Time Headway under Various Flow Conditions	23

3.3.2.	Develop Probability Density Function for Time Headway Based on the Combination of Leader Follower Pair	26
3.4.	Selection of Best Fitting Distribution.....	28
3.4.1.	Normality Tests	28
3.4.2.	Selection of Best Fitting Distribution Using Goodness of Fit Tests	29
4.	CHAPTER	32
	DATA SET	32
4.1.	Classification of Time Headway Data Sets within 15 min Interval Based on Flow for Selected Road Sections	32
4.1.1.	Vehicular Flow Rate Below 400 veh/h	33
4.1.2.	Vehicular Flow Rate Between 400 veh/hr to 1200 veh/hr.....	33
4.1.3.	Vehicular flow above 1200 veh/hr.....	33
4.2.	Classification of Time Headway Data Sets Based on Different Leader Follower pairs	33
5.	CHAPTER	34
	RESULTS AND DISCUSSION	34
5.1.	Introduction	34
5.2.	Analysis of Vehicular Flow.....	35
	Analysis of Vehicular Flow Rate Below 400 veh/hr.....	35
5.2.1.	35
5.2.2.	Analysis of Vehicular Flow Rate Between 400 veh/hr to 1200 veh/hr	47
5.2.3.	Analysis of Vehicular Flow Greater than 1200 veh/hr	59
5.3.	Analysis of Leader Follower Pairs	70
5.3.1.	Pairwise Descriptive Statistics	70
5.3.2.	Pairwise Probability Density Function and Cumulative Density Function	74
5.3.3.	Goodness of Fit Test Statics.....	99
5.3.4.	Summary of Goodness of Fit Test Results.....	116

6. CHAPTER	118
CONCLUSION.....	118
REFERENCES.....	124
APPENDIX - 1:	i
APPENDIX - 2:	x
APPENDIX - 3:	xxxviii
APPENDIX - 4:	lxvi

LIST OF FIGURES

Figure 5. 1 Probability Density Function-0-400 veh/hr-A04 Road	37
Figure 5. 2 Cumulative Density Function-0-400 veh/hr-A04 Road	37
Figure 5. 3 Probability Density Function-0-400 veh/hr-A01 Road	38
Figure 5. 4 Cumulative Density Function-0-400 veh/hr-A01 Road	38
Figure 5. 5 Probability Density Function-0-400 veh/hr-Marine Drive Road.....	39
Figure 5. 6 Cumulative Density Function-0-400 veh/hr-Marine Drive Road.....	39
Figure 5. 7 Probability Density Function-0-400 veh/hr-AB-042 Road	40
Figure 5. 8 Cumulative Density Function-0-400 veh/hr-AB-042 Road	40
Figure 5. 9 Probability Density Function-400-1200 veh/hr-A04 Road	49
Figure 5. 10 Cumulative Density Function-400-1200 veh/hr-A04 Road	49
Figure 5. 11 Probability Density Function-400-1200 veh/hr-A01 Road	50
Figure 5. 12 Cumulative Density Function-400-1200 veh/hr-A01 Road	50
Figure 5. 13 Probability Density Function-400-1200 veh/hr-Marine Dr Road ...	51
Figure 5. 14 Cumulative Density Function-400-1200 veh/hr-Marine Dr Road....	51
Figure 5. 15 Probability Density Function-400-1200 veh/hr-AB-042 Road	52
Figure 5. 16 Cumulative Density Function-400-1200 veh/hr-AB-042 Road	52
Figure 5. 17 Probability Density Function >1200 veh/hr-A04 Road.....	60
Figure 5. 18 Cumulative Density Function- >1200 veh/hr-A-04 Road	60
Figure 5. 19 Probability Density Function- >1200 veh/hr-A01 Road	61
Figure 5. 20 Cumulative Density Function- >1200 veh/hr-A 01 Road	61
Figure 5. 21 Probability Density Function- >1200 veh/hr-Marine Dr Road	62
Figure 5. 22 Cumulative Density Function- >1200 veh/hr-Marine Dr Road.....	62
Figure 5. 23 Probability Density Function->1200 veh/hr-AB-042 Road	63
Figure 5. 24 Cumulative Density Function- >1200 veh/hr-AB-042 Road	63
Figure 5. 25 Probability Density Function—MC-MC	74
Figure 5. 26 Cumulative Density Function—MC-MC	74
Figure 5. 27 Probability Density Function-MC-TW	75
Figure 5. 28 Cumulative Density Function-MC-T.....	75
Figure 5. 29 Probability Density Function-MC-CAR.....	76
Figure 5. 30 Cumulative Density Function-MC-CAR.....	76
Figure 5. 31 Probability Density Function-MC-COM.....	77
Figure 5. 32 Cumulative Density Function-MC-COM.....	77

Figure 5. 33 Probability Density Function-MC-HV	78
Figure 5. 34 Cumulative Density Function-MC-HV	78
Figure 5. 35 Probability Density Function-TW-MC.....	79
Figure 5. 36 Cumulative Density Function-TW-MC.....	79
Figure 5. 37 Probability Density Function-TW-TW	80
Figure 5. 38 Cumulative Density Function-TW-TW.....	80
Figure 5. 39 Probability Density Function-TW-CAR.....	81
Figure 5. 40 Cumulative Density Function-TW-CAR.....	81
Figure 5. 41 Probability Density Function-TW-COM.....	82
Figure 5. 42 Cumulative Density Function-TW-COM.....	82
Figure 5. 43 Probability Density Function-TW-HV	83
Figure 5. 44 Cumulative Density Function-TW-HV	83
Figure 5. 45 Probability Density Function-CAR-MC.....	84
Figure 5. 46 Cumulative Density Function-CAR-MC.....	84
Figure 5. 47 Probability Density Function-CAR-TW	85
Figure 5. 48 Cumulative Density Function-CAR-TW.....	85
Figure 5. 49 Probability Density Function-CAR-CAR.....	86
Figure 5. 50 Cumulative Density Function-CAR-CAR.....	86
Figure 5. 51 Probability Density Function-CAR-COM.....	87
Figure 5. 52 Cumulative Density Function-CAR-COM.....	87
Figure 5. 53 Probability Density Function-CAR-HV	88
Figure 5. 54 Cumulative Density Function-CAR-HV	88
Figure 5. 55 Probability Density Function-COM-MC.....	89
Figure 5. 56 Cumulative Density Function-COM-MC.....	89
Figure 5. 57 Probability Density Function-COM-TW.....	90
Figure 5. 58 Cumulative Density Function-COM-TW	90
Figure 5. 59 Probability Density Function-COM-CAR.....	91
Figure 5. 60 Cumulative Density Function-COM-CAR.....	91
Figure 5. 61 Probability Density Function-COM-COM.....	92
Figure 5. 62 Cumulative Density Function-COM-COM.....	92
Figure 5. 63 Probability Density Function-COM-HV	93
Figure 5. 64 Probability Density Function-MC-CAR.....	93
Figure 5. 65 Probability Density Function-HV-MC	94
Figure 5. 66 Cumulative Density Function-HV-MC	94

Figure 5. 67 Probability Density Function-HV-TW	95
Figure 5. 68 Cumulative Density Function-HV-TW	95
Figure 5. 69 Probability Density Function – HV-CAR	96
Figure 5. 70 Cumulative Density Function-HV-CAR	96
Figure 5. 71 Probability Density Function-HV-COM	97
Figure 5. 72 Cumulative Density Function-HV-COM	97
Figure 5. 73 Probability Density Function-HV-HV.....	98
Figure 5. 74 Cumulative Density Function-HV-HV	98
Figure 6.1 Probability Distribution nomograph.....	119

LIST OF TABLES

Table 3.1 General details of selected road sections	16
Table 3.2 General details of vehicular traffic at selected road sections.....	16
Table 3.3 Short cut keys used in Traffic Extractor software.....	18
Table 3.3 Vehicle classification	22
Table 3.4 Leader follower combinations	22
Table 3.5 Suitable distribution models based on flow condition.....	26
Table 4.1 Summary of Vehicular Flow.....	32
Table 5.1 Descriptive Statistics Less than 400 veh/hr Flow	35
Table 5.2 Goodness of Fit test statistics-0-400 veh/hr flow- A 04 Road Section	41
Table 5.3 Critical values for different significance levels of best fitting distribution for 0-400 veh/hr flow- A 04 Road Section.....	41
Table 5.4 Goodness of Fit test statistics-0-400 veh/hr -A 01 Road Section	42
Table 5.5 Critical values for different significance levels of best fitting distribution for 0-400 veh/hr flow- A 01 Road Section.....	42
Table 5.6 Goodness of Fit test statistics-0-400 veh/hr -Marine Drive Road Section	44
Table 5.7 Critical values for different significance levels of best fitting distribution for 0-400 veh/hr flow- Marine Drive Road Section.....	44
Table 5.8 Goodness of Fit test statistics-0-400 veh/hr -AB -042 Road Section ..	45
Table 5.9 Critical values for different significance levels of best fitting distribution for 0-400 veh/hr flow- A AB Road Section.....	46
Table 5.10 Goodness of Fit test Results Summary-0-400 veh/hr	47
Table 5.11 Descriptive Statistics 400-1200 veh/hr Flow	48
Table 5.12 Goodness of Fit test statistics-400-1200 veh/hr -A 04 Road Section	53
Table 5.13 Critical values for different significance levels of best fitting distribution for 400-1200 veh/hr flow- A 04 Road Section	53
Table 5.14 Goodness of Fit test statistics-400-1200 veh/hr -A 01 Road Section	54
Table 5.15 Critical values for different significance levels of best fitting distribution for 400-1200 veh/hr flow- A 01 Road Section.....	55
Table 5.16 Goodness of Fit test statistics-400-1200 veh/hr Marine Drive Road Section.....	55

Table 5.17 Critical values for different significance levels of best fitting distribution for 400-1200 veh/hr flow- Marine Drive Road Section	56
Table 5.18 Goodness of Fit test statistics-400-1200 veh/hr AB-042 Road Section	57
Table 5.19 Critical values for different significance levels of best fitting distribution for 400-1200 veh/hr flow- A 04 Road Section	57
Table 5.20 Goodness of Fit test Results Summary-400-1200 veh/hr	58
Table 5.21 Descriptive Statistics > 1200 veh/hr Flow	59
Statistic.....	59
Table 5.22 Goodness of Fit test statistics >1200 veh/hr A-04 Road Section.....	64
Table 5.23 Critical values for different significance levels of best fitting distribution for 400-1200 veh/hr flow- A 04 Road Section	64
Table 5.24 Goodness of Fit test statistics >1200 veh/hr A-01 Road Section.....	65
Table 5.25 Critical values for different significance levels of best fitting distribution for 400-1200 veh/hr flow- A 04 Road Section	66
Table 5.26 Goodness of Fit test statistics >1200 veh/hr Marine Drive Road Section	66
Table 5.27 Critical values for different significance levels of best fitting distribution for 400-1200 veh/hr flow- A 04 Road Section	67
Table 5.29 Critical values for different significance levels of best fitting distribution for 400-1200 veh/hr flow- A 04 Road Section	68
Table 5.30 Goodness of Fit test Results Summary->1200 veh/hr	69
Table 5.31 Pairwise Descriptive Statistics -MC	70
Table 5.32 Pairwise Descriptive Statistics -TW	71
Table 5.33 Pairwise Descriptive Statistics - CAR	71
Table 5.34 Pairwise Descriptive Statistics - COM.....	72
Table 5.35 Pairwise Descriptive Statistics - HV	72
Table 5.36 Goodness of Fit test statistics – MC-MC	99
Table 5.37 Goodness of Fit test statistics – MC-TW	99
Table 5.38 Goodness of Fit test statistics – MC-CAR	100
Table 5.39 Goodness of Fit test statistics – MC-COM	101
Table 5.40 Goodness of Fit test statistics – MC-HV	101
Table 5.41 Goodness of Fit test statistics – TW-MC	102
Table 5.42 Goodness of Fit test statistics – TW-TW	103

Table 5.43 Goodness of Fit test statistics – TW-CAR.....	103
Table 5.44 Goodness of Fit test statistics – TW-COM.....	104
Table 5.45 Goodness of Fit test statistics – TW-HV	105
Table 5.46 Goodness of Fit test statistics – CAR-MC.....	105
Table 5.47 Goodness of Fit test statistics – CAR-TW	106
Table 5.48 Goodness of Fit test statistics – CAR-CAR.....	107
Table 5.49 Goodness of Fit test statistics – CAR-COM.....	107
Table 5.50 Goodness of Fit test statistics – CAR-HV	108
Table 5.51 Goodness of Fit test statistics – COM-MC.....	109
Table 5.52 Goodness of Fit test statistics – COM-TW	109
Table 5.53 Goodness of Fit test statistics – COM-CAR.....	110
Table 5.54 Goodness of Fit test statistics – COM-COM.....	111
Table 5.55 Goodness of Fit test statistics – COM-HV.....	111
Table 5.56 Goodness of Fit test statistics – HV-MC	112
Table 5.57 Goodness of Fit test statistics – HV-TW	113
Table 5.58 Goodness of Fit test statistics – HV-CAR	113
Table 5.59 Goodness of Fit test statistics – HV-COM.....	114
Table 5.60 Goodness of Fit test statistics – HV-HV.....	115
Table 5.61 Summary of Pairwise Goodness of Fit test statistics.....	116

LIST OF ABBREVIATIONS

Abbreviation	Description
PDF	Probability Density Function
PCU	Passenger Car Units
ATC	Automatic Traffic Counter
SPSS	Statistical Package for the Social Science
CDF	Cumulative Density Function
EDF	Empirical Distribution Function

LIST OF APPENDICES

- Appendix – 1.....Vehicular Flow Rate Below 400 veh/h
- Appendix – 2.....Vehicular Flow Rate Between 400 -1200 veh/h
- Appendix – 3.....Vehicular Flow Rate Greater than 400 veh/h
- Appendix – 4.....Vehicular Flow Rate for different leader-follower pairs