

REFERENCE

- [1] T. Ayodele, S. Zhou, and R. Khusainov, "Email Reply Prediction: A Machine Learning Approach," in *Human Interface and the Management of Information. Information and Interaction*, G. Salvendy and M. J. Smith, Eds., in Lecture Notes in Computer Science, vol. 5618. Berlin, Heidelberg: Springer Berlin Heidelberg, 2009, pp. 114–123. doi: 10.1007/978-3-642-02559-4_13.
- [2] S. Whittaker and C. Sidner, "Email overload: exploring personal information management of email," in *Proceedings of the SIGCHI conference on Human factors in computing systems common ground - CHI '96*, Vancouver, British Columbia, Canada: ACM Press, 1996, pp. 276–283. doi: 10.1145/238386.238530.
- [3] M. Dredze *et al.*, "Intelligent Email: Aiding Users with AI," *{AAAI} Press*, p. 4, 2008.
- [4] M. Dredze, T. Brooks, J. Carroll, J. Magarick, J. Blitzer, and F. Pereira, "Intelligent email: reply and attachment prediction," in *Proceedings of the 13th international conference on Intelligent user interfaces - IUI '08*, Gran Canaria, Spain: ACM Press, 2008, p. 321. doi: 10.1145/1378773.1378820.
- [5] A. Kannan *et al.*, "Smart Reply: Automated Response Suggestion for Email," in *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, San Francisco California USA: ACM, Aug. 2016, pp. 955–964. doi: 10.1145/2939672.2939801.
- [6] A. Faulring, B. Myers, and A. Steinfeld, "Success of an Agent-Assisted System that Reduces Email Overload," *ACM*, p. 8, 2009.
- [7] W. E. Mackay, "Diversity in the use of electronic mail: a preliminary inquiry," *ACM Trans. Inf. Syst.*, vol. 6, no. 4, pp. 380–397, Oct. 1988, doi: 10.1145/58566.58567.
- [8] T. Scheffer, "Email answering assistance by semi-supervised text classification," *IDA*, vol. 8, no. 5, pp. 481–493, Oct. 2004, doi: 10.3233/IDA-2004-8505.
- [9] S. Qaiser and R. Ali, "Text Mining: Use of TF-IDF to Examine the Relevance of Words to Documents," *IJCA*, vol. 181, no. 1, pp. 25–29, Jul. 2018, doi: 10.5120/ijca2018917395.
- [10] J. Schuurmans and F. Frasincar, "Intent Classification for Dialogue Utterances," *IEEE Intell. Syst.*, vol. 35, no. 1, pp. 82–88, Jan. 2020, doi: 10.1109/MIS.2019.2954966.
- [11] S. Sah, "Machine Learning: A Review of Learning Types," *MATHEMATICS & COMPUTER SCIENCE*, preprint, Jul. 2020. doi: 10.20944/preprints202007.0230.v1.
- [12] Y. Li and H. Wu, "A Clustering Method Based on K-Means Algorithm," *Physics Procedia*, vol. 25, pp. 1104–1109, 2012, doi: 10.1016/j.phpro.2012.03.206.
- [13] P. Kherwa and P. Bansal, "Topic Modeling: A Comprehensive Review," *ICST Transactions on Scalable Information Systems*, vol. 0, no. 0, p. 159623, Jul. 2018, doi: 10.4108/eai.13-7-2018.159623.
- [14] W. Jia, M. Sun, J. Lian, and S. Hou, "Feature dimensionality reduction: a review," *Complex Intell. Syst.*, vol. 8, no. 3, pp. 2663–2693, Jun. 2022, doi: 10.1007/s40747-021-00637-x.
- [15] S. R. Joseph, H. Hlomani, K. Letsholo, F. Kaniwa, and K. Sedimo, "Natural Language Processing: A Review," *Applied Sciences*, vol. 6, no. 3, p. 10, 2016.
- [16] L. Alzubaidi *et al.*, "Review of deep learning: concepts, CNN architectures, challenges, applications, future directions," *J Big Data*, vol. 8, no. 1, p. 53, Dec. 2021, doi: 10.1186/s40537-021-00444-8.

- [17] Z. C. Lipton, “A Critical Review of Recurrent Neural Networks for Sequence Learning,” *ArXiv*, vol. abs/1506.00019, 2015.
- [18] S. Bond-Taylor, A. Leach, Y. Long, and C. G. Willcocks, “Deep Generative Modelling: A Comparative Review of VAEs, GANs, Normalizing Flows, Energy-Based and Autoregressive Models,” *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 44, no. 11, pp. 7327–7347, Nov. 2022, doi: 10.1109/TPAMI.2021.3116668.
- [19] S. Santhanam, “Context based Text-Generation using LSTM Networks,” *A2IC*, p. 11, 2018.
- [20] I. Nusrat and S.-B. Jang, “A Comparison of Regularization Techniques in Deep Neural Networks,” *Symmetry*, vol. 10, no. 11, p. 648, Nov. 2018, doi: 10.3390/sym10110648.